

1-1/4AGE 13V-TWIN PUMP

HIGH PRESSURE, LOW VOLUME, GEAR DRIVEN, ENGINE MOUNTED



ENGINE

- Briggs & Stratton Vanguard: 13 hp, V-twin, 9.35 qt. gas tank, 12-volt starter, 16 amp regulated alternator, recoil rope start back-up, control panel

DIMENSIONS & WEIGHT

- 27" L x 21" W x 23" H, 145 lbs. (66 kg)

APPLICATIONS

- Light duty brush truck, booster tank fill, transfer and supply

STANDARD FEATURES

- Electric start with recoil rope back-up
- Exhaust primer, bronze impeller and wear rings
- Stainless steel shaft
- Discharge head with check valve
- Base with fold-away carrying handles
- Aluminum alloy gear case and engine adapter
- Heat treated alloy steel helical gears
- Adjustable throttle
- 1 $\frac{1}{2}$ " NPT suction
- 2-1 $\frac{1}{2}$ " NPT discharges

OPTIONS

- Adapters, gauge, battery and caps

PERFORMANCE

60 gpm (227 L/M) @ 160 psi (11 bar)
40 gpm (151 L/M) @ 220 psi (15 bar)
20 gpm (76 L/M) @ 260 psi (17.9 bar)

