

2-1/2" AGE 23V PUMP

HIGH PRESSURE, HIGH VOLUME, GEAR DRIVEN, ENGINE MOUNTED

ENGINE

- Briggs & Stratton Vanguard: 4 cycle, 23 hp, V-twin, OHV, 6 gal. fuel tank, replaceable oil filter, 12-volt starter, 16 amp regulated alternator, recoil rope start back-up

DIMENSIONS & WEIGHT

- 24" L x 21" W x 24" H, 190 lbs. (86 kg)

APPLICATIONS

- Booster reel, multiple hand lines, wildland/attack fire suppression

STANDARD FEATURES

- Hard anodized aluminum alloy casing and discharge valve
- Sulfuric anodized aluminum alloy gear case and engine adapter
- Bronze impeller and wear ring
- Stainless steel impeller shaft
- Mechanical seal
- Helical gears
- Discharge check valve
- Adjustable discharge valve
- Throttle
- Exhaust primer
- 2 1/2" NPT suction
- 1-2 1/2" NPT and 2-1 1/2" NPT discharges

OPTIONS

- Adapters, gauge, battery and caps, control panel, Smartstart™

PERFORMANCE

290 gpm (1097 L/M) @ 45 psi (3.1 bar)

100 gpm (378 L/M) @ 135 psi (9.3 bar)

50 gpm (189 L/M) @ 175 psi (12 bar)

