

HE 64RP "HERCULES" ULTRA HIGH PERFORMANCE PORTABLE VERSION



ENGINE

- Rotax 582: Liquid-cooled, 64 HP, 2 cycle without injection, 12-volt electric starter, recoil rope start back-up, 6 gal. fuel tank, hose and adapter

DIMENSIONS & WEIGHT

- 34" L x 30" W x 26" H, 225 lbs. (102 kg)

APPLICATIONS

- Booster reel, booster tank fill, multiple hand lines, wildland/attack fire suppression

STANDARD FEATURES

- 170W lighting and recharging coil
- Aluminum alloy casing
- Bronze impeller and seal ring
- Stainless steel impeller shaft
- Mechanical seal
- Belt driven rotary primer
- Heat exchanger with thermal protection circuit
- Wrap around frame with fold out handles
- Loss of prime shutdown
- Pressure governor
- Vernier throttle
- 4" NH suction with screen
- 2-1/4 turn self-locking 2 1/2" NH discharge ball valves with caps
- Available with wheels

OPTIONS

- Adapters, gauge, battery and caps, wheels, marinization

PERFORMANCE

575 gpm (2176 L/M) @ 100 psi (6.9 bar)

320 gpm (1211 L/M) @ 200 psi (13.8 bar)

165 gpm (625 L/M) @ 250 psi (17.2 bar)

