

# LSM 500, 750, 1000

SINGLE STAGE, CENTRIFUGAL SINGLE SUCTION IMPELLER, MIDSHIP MOUNTED

## DIMENSIONS & WEIGHT

- 30"L x 17"W x 30"H, 398 lbs. (180 kg)

## APPLICATIONS

- Mini pumper, pumper tanker, tanker, wildland/attack fire

## STANDARD FEATURES

- 4" NPT discharge
- 5" or 6" NPT or weld flange suction
- 1610 or 1710 full round yokes standard
- Air shift

## OPTIONS

- Complete discharge and suction manifold
- Available as an LSMH high pressure pump
- Electric over air shift

## PERFORMANCE

### LSM 500

500 gpm (1893 L/M) @ 150 psi (10.3 bar)  
350 gpm (1325 L/M) @ 200 psi (13.8 bar)  
250 gpm (946 L/M) @ 250 psi (17.2 bar)

### LSM 750

750 gpm (2839 L/M) @ 150 psi (10.3 bar)  
525 gpm (1987 L/M) @ 200 psi (13.8 bar)  
375 gpm (1419 L/M) @ 250 psi (17.2 bar)

### LSM 1000

1000 gpm (3785 L/M) @ 150 psi (10.3 bar)  
700 gpm (2646 L/M) @ 200 psi (13.8 bar)  
500 gpm (1893 L/M) @ 250 psi (17.2 bar)

