

## 1-1/2AGE 18V VANGUARD PUMP

HIGH PRESSURE, MEDIUM VOLUME, GEAR DRIVEN, ENGINE MOUNTED

MEETS ISO CLASS 9  
PERFORMANCE RATINGS



### ENGINE

- Briggs & Stratton Vanguard: 4 cycle, 18 HP, V-twin, OHV, replaceable oil filter, 34.75 cu. in. displacement, 12 volt starter, recoil rope start back-up, 16 amp regulated alternator, 8.35 qt. fuel tank

### DIMENSIONS & WEIGHT

- 27"L x 21"W x 25"H, 145 lbs. (66 kg)

### APPLICATIONS

- Booster reel, multiple hand lines, wildland/attack fire suppression

### STANDARD FEATURES

- Aluminum alloy casing and discharge valve
- Aluminum alloy gear case and engine adapter
- Bronze impeller and seal ring
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction pump and engine
- Built-in discharge check valve
- Adjustable discharge valve
- Exhaust primer
- 2" NPT suction
- 2-1/2" NPT or 1-2 1/2" NPT discharges

VIDEO  
ONLINE



### OPTIONS

- Adapters, gauge, battery and caps, deluxe control panel

### PERFORMANCE

120 gpm (454 L/M) @ 130 psi (9 bar)  
100 gpm (757 L/M) @ 170 psi (11.7 bar)  
50 gpm (189 L/M) @ 250 psi (17.2 bar)



FAMILY OWNED  
MADE IN USA

PUMPSALES@DARLEY.COM

1.800.4.DARLEY • DARLEY.COM •   