

DARLEY P-100 (NAVY P100) 2BE10YDN

MEDIUM PRESSURE, HIGH VOLUME, ENGINE MOUNTED



ENGINE

- 2BE10YDNL100: 4 cycle, 10 HP, 1 cylinder, recoil rope start back-up, optional 12 volt electric start and alternator

DIMENSIONS & WEIGHT

- 24"L x 24"W x 23"H, 163 lbs. (74 kg)

APPLICATIONS

- Marine, dewatering, transfer and supply

STANDARD FEATURES

- Bronze or hard anodized pump
- 316 stainless shaft and fittings
- High performance ceramic coating
- Imron painted engine
- Anodized aluminum alloy casing
- Discharge head
- Engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Shredded plastic packing
- Discharge check valve
- Adjustable discharge valve
- Throttle
- Roll cage
- Pressure gauge
- Exhaust primer
- 3" NST suction with cap
- 2 1/2" NST discharge with cap
- 2"x10' engine exhaust hose

OPTIONS

- Adapters, caps, electric start, mechanical seal

PERFORMANCE

120 gpm (454 L/M) @ 75 psi (5.7 bar)
75 gpm (284 L/M) @ 125 psi (8.6 bar)
20 gpm (76 L/M) @ 145 psi (10.0 bar)

