

DOLPHIN™ FLOATING PUMP

HEF 10.5BS, HIGH VOLUME, SELF-PRIMING



ENGINE

- Briggs & Stratton: 10.5 HP, 2.8 qt. fuel tank

PUMP

- High volume, self-priming, floating pump

DIMENSIONS & WEIGHT

- 33" L x 30" W x 20" H, 110 lbs. (50 kg)

APPLICATIONS

- Booster tank fill, transfer and supply

STANDARD FEATURES

- Anodized aluminum alloy pump casing
- Bronze impeller
- 4" screened suction inlet
- 2½" NH outlet

PERFORMANCE

390 gpm (1450 L/M) @ 20 psi (1.4 bar)

250 gpm (946 L/M) @ 40 psi (2.8 bar)

200 gpm (757 L/M) @ 45 psi (3.1 bar)

100 gpm (378 L/M) @ 60 psi (4.1 bar)

ADDITIONAL DARLEY FLOATING PUMPS

2BEF-BS: PORPOISE™ FLOATING PUMP

- Engine: Briggs & Stratton, 8.75 ft.-lbs., torque, 190 cc, 1.2 qt. fuel tank
- High volume, self priming
- Anodized alloy pump casing
- Bronze impeller
- 3" screened suction inlet
- 2" NPTM outlet

2BEF-BS



HEF 11H: DOLPHIN™ FLOATING PUMP

- Engine: Honda, GVX390, 11 HP, 2.2 qt. fuel tank, OHV
- High volume, self priming
- Anodized aluminum alloy pump casing
- Bronze impeller
- 4" screened suction inlet
- 2½" NH outlet

HEF 11H

