

HSP 250

SINGLE STAGE, HIGH PRESSURE, CENTRIFUGAL, PTO DRIVEN



DIMENSIONS & WEIGHT

- 15" L x 11" W x 18" H, 127 lbs. (58 kg)

APPLICATIONS

- Mini Pumper, tanker, wildland/attack fire

STANDARD FEATURES

ASSEMBLY #1

- 2½" NPT discharge
- 3" or 4" NPT suction
- Rotation: Engine only
- Gear ratio: 3.95 to 1 or 2.85 to 1
- Heat treated gears are standard
- Mounting angles
- 1310/1410 lock on companion drive flange

ASSEMBLY #2

- 2 - 2½" NPT discharge
- 2 - 3" or 4" NPT suction

ASSEMBLY #3

- 2 - 2½" NH, 1/4 turn, ball, valves and caps
- 2 - 3" or 4" NH suction with adapters and caps
- 2 - 2½" NPT tapped openings on discharge manifolds
- 2 - 2½" NPT tapped openings on suction
- Body width: 70" - 72"

PERFORMANCE

400 gpm (1514 L/M) @ 50 psi (3.44 bar)
300 gpm (1135 L/M) @ 300 psi (20.68 bar)
200 gpm (756 L/M) @ 300 psi (20.68 bar)
150 gpm (568 L/M) @ 400 psi (27.58 bar)

