

PSD 1000, 1250, 1500 SILENT PAK®

SINGLE STAGE, CENTRIFUGAL PUMP, SINGLE SUCTION IMPELLER,
DIRECT (GEARLESS) DRIVE TO IMPELLER, PTO DRIVEN



DIMENSIONS & WEIGHT

- 16" L x 19" W x 19" H, 225 lbs. (102 kg)

APPLICATIONS

- Crash Fire Rescue, rescue pumper, tanker

STANDARD FEATURES

- 5" NPT discharge
- 6" NPT or weld suction flange
- Rotation: engine or opposite engine
- 1410 companion drive flange

PERFORMANCE

PSD 1000

1000 gpm (3785 L/M) @ 150 psi (10.3 bar)
700 gpm (2646 L/M) @ 200 psi (13.8 bar)
500 gpm (1893 L/M) @ 250 psi (17.2 bar)

PSD 1250

1250 gpm (4731 L/M) @ 150 psi (10.3 bar)
875 gpm (3312 L/M) @ 200 psi (13.8 bar)
625 gpm (2365 L/M) @ 250 psi (17.2 bar)

PSD 1500

1500 gpm (5678 L/M) @ 150 psi (10.3 bar)
1050 gpm (3974 L/M) @ 200 psi (13.8 bar)
750 gpm (2839 L/M) @ 250 psi (17.2 bar)

