

# Operator's Manual Table of Contents for Darley Midship/Split Shaft PTO

		<u>PAGE #</u>
Description, Operation & Maintenance, & Lubrication-----	1200538	1
Related Drawings-----	DKC1502	2
	DKC1503	3
	DLC0200	4
	DLC0201	5
	DLC0205	6-7
Shifting Procedure-----	1200515	8
Manual transmission / Automatic Transmission-----	1200507	9-11
Shift "Air Shift"-----	DGS0500	12
	DGC0701	13
General Operation-----	1200509	14-15
	1200510	16-20
	1201500-1201502	21-32
Tachometer-----	DGC0105	33
	1201001	34
Drawing-----	DLD1300	35
Drawing-----	DLC2200	36-37

**IF FURTHER INFORMATION IS NEEDED, CALL W.S. DARLEY & CO. AT  
CHIPPEWA FALLS, WI. AT 800-634-7812 or 715-726-2650**

Prepared by: EAS  
Revised by: EAS  
Approved by: TED

Rev.: 3  
Date: 2/15/06  
Rev Date: 10/9/07  
1200538-LDMXHDPTOE.doc

## **This manual is for DARLEY SPLIT SHAFT PTO:**

Model: HD / XHD SPLIT SHAFT PTO Transmission Serial Number: \_\_\_\_\_

### **OPERATION AND MAINTENANCE OF TYPE HD/XHD SPLIT SHAFT PTO**

#### **Lubrication**

Keep the gear case filled with oil to the level of the oil level plug, which is marked on the gear case.

Check the oil level every 25 hours or every six month, and change it every 50 hours or 12 months.

Use 80W/90 gear lube oil - not grease - in the PTO transmission.

**CAUTION: Do not overfill.**

Inject grease in zerk fittings on the driveline universal joints once a year.

#### **Operation of PTO**

The PTO gear shift consists of a sliding clutch gear splined to the transmission shaft which can be moved forward to engage the PTO clutch gear or to the rear to engage the rear drive shaft connected to the truck drive axle. A neutral position is half way between.


The sliding clutch gear is moved either by direct mechanical linkage from a shift lever, or air powered cylinder controlled by a selector switch. The shift lever must be moved all the way and locked into either ROAD position to drive the truck, or PTO position to power the PTO.

The truck clutch must always be disengaged to stop the rotation of the truck transmission output shaft before shifting into either ROAD or PTO gear to prevent clashing and damaging the gear teeth. With the manual shift lever, a butt tooth position of gears may be encountered occasionally preventing engagement. If this occurs, move PTO shift lever to neutral (half way) position, engage truck clutch momentarily, then disengage the truck clutch and try to shift the PTO again.

The PTO is always operated with the truck transmission in direct (high) gear, such as 4<sup>th</sup> on a 4-speed, or 5<sup>th</sup> on a 5-speed manual transmission, and D or 2.5 on an automatic transmission.

REVISIONS			
LR	DESCRIPTION	DATE	CHG. NO. APPR.
A	2301305 ENG. CHG. NO. 2301304	06/07/03	2052-144 26
B	ADDED WATER FLINGER	05/10/04	2052-144 26
C		05/10/04	2054-111 26

REP.#	NAME OF PART	QTY
1	GEAR CASE VENT	1
2	OIL SEAL - OUTPUT SHAFT	1
3	BEARING - OUTPUT SHAFT	1
4	BEARING CAP - .203 WIDE	1
5	BEARING LOCKNUT	1
6	BEARING LOCKWASHER	1
7	PINION KEY	1
8	PINION GEAR	1
9	BEARING CAP - IDLER	1
10	OUTPUT SHAFT - IDLER	1
11/56	BEARING - IDLER	1
12	OUTPUT SHAFT - IDLER	1
13	SPACER - IDLER GEAR	1
14	BEARING - IDLER GEAR	2
15	RETAINING RING - IDLER	1
16	CRANK PIN	1
17	CRANK PIN SOCKET HEAD CAP SCREWS	6
18	BEARING RETAINER	1
19	DRIVE YOKE	1
20	BEARING - DRIVE SHAFT	2
21	FRONT DRIVE SHAFT	1
22	BEARING - DRIVE GEAR	2
23	BEARING LOCK - 3/8NPT	1
24	BEARING SPACER - DRIVE SHAFT	1
25	OIL SEAL	2
26	90° ELBOW - OIL FILL	1
27	FRONT BEARING BRACKET	1
28	GEARCASE COVER	1
29	DRIVE GEAR	1
30	GEARCASE	1
31	GEARCASE PLUG - 3/8NPT MAGNETIC	1
32	OIL LEVEL PLUG - 3/8NPT	1
33	CLUTCH GEAR	1
34	GASKET - GEARCASE COVER	1
35	SLIDING CLUTCH GEAR	1
36	OIL WICK PELLETT	6
37	BEARING - REAR DRIVE SHAFT	1
38	BEARING - REAR DRIVE SHAFT	1
39	REAR BEARING BRACKET	1
40	REAR DRIVE SHAFT	1
41	REAR DRIVE YOKE	1
42	REAR DRIVE YOKE	1
43	POWER SHIFT OPENING COVER - SHIFT CYLINDER (OPTIONAL)	1
44	BEARING CAP	1
45	SAFETY WIRE	10*
46	LOCK BOLT - SHIFT YOKE	1
47	SHIFT BAR	1
48	SHIFT YOKE	1
49	BEARING CAP - IDLER	1
50	GASKET	3
51	GASKET - FRONT BEARING BRACKET	1
52	SPACER	1
53	BEARING BRACKET - OUTPUT SHAFT	1
54	NUT - OUTPUT FLANGE - 7/8 NYLOC	1
55	FLANGE COMPANION FLANGE - OUTPUT	1
56	FLANGE SPACER - .125 WIDE	2
57	NUT	1
58	O-RING	1
59	WATER FLINGER	2



INCH (MILLIMETERS)

**W.S. DARLEY & CO.**  
 ENGINEERING & MANUFACTURING  
 2.5" SHAFT LOCKON

DATE: JUL 14 97

SCALE: 1/2"

DC15102


MIDSHIP PTO W/2.5" DRIVE SHAFT - TP00705

DO NOT SCALE PRINT

\*TORQUE YOKE NUT TO 130-200 lb-ft

REVISIONS		DATE	BY	CHKD BY	APP'D
A	ADDED O-RING	05/05/02	2002-114	202	
B	ADDED WATER FINGER	05/07/04	2004-111	202	

REP.#	NAME OF PART	QTY
1	GEAR CASE YELT	1
2	BEARING CAP - OUTPUT SHAFT	1
3	DRIVE KEY - OUTPUT SHAFT	2
4	PINION GEAR	1
9	BEARING CAP - OUTPUT SHAFT	1
10	BEARING CAP - OUTPUT SHAFT	1
11	SPACER - PINION GEAR	1
15	RETAINING RING	2
17	O-RING	1
19	O-RING - SHIFT BAR	1
20	GRADE 8 SOCKET HEAD CAP SCREWS	6
22	BEARING RETAINER	1
23	DRIVE YOKE	1
24	DRIVE YOKE DRIVE SHAFT	1
25	FRONT DRIVE SHAFT	2
26	FRONT DRIVE SHAFT	2
27	BEARING - DRIVE GEAR	2
28	OIL FILL PLUG - 3/8NPT	1
29	BEARING SPACER - DRIVE SHAFT	1
30	OIL SEAL	2
31	90° ELBOW - OIL FILL	1
32	BEARING BRACKET	1
33	GEARCASE COVER	1
34	DRIVE GEAR	1
35	GEARCASE	1
36	OIL DRAIN PLUG - 3/8NPT MAGNETIC	1
37	OIL LEVEL PLUG - 3/8NPT	1
38	CLUTCH GEAR	1
39	GEARCASE COVER	1
40	SLIDING CLUTCH GEAR	1
41	OIL WICK PELLET	6
42	PILOT BEARING	4
43	BEARING - REAR DRIVE SHAFT	1
44	OIL SEAL	1
45	BEARING BRACKET	1
46	OIL SEAL	1
47	REAR DRIVE SHAFT	1
48	REAR DRIVE YOKE	1
49	COVER - POWER SHIFT OPENING (POWER SHIFT CYLINDER OPTIONAL)	1
50	BEARING CAP	1
51	SAFETY WIRE	10*
52	SHIFT BAR	1
53	SHIFT BAR - SHIFT YOKE	1
54	SHIFT YOKE	1
56	BEARING BRACKET - OUTPUT SHAFT	1
58	GASKET	2
59	GASKET - FRONT BEARING BRACKET	1
60	SPACER	1
80	NUT - OUTPUT FLANGE	1
81	COMPANION FLANGE - OUTPUT	1
82	FLANGE WASHER	1
214*	NUT	2
358	O-RING	1
359	WATER FINGER	2



TOLERANCE		OLD PART NO.	MATERIAL NO.	DO NOT SCALE PRINT
AS NOTED	—	—	—	—
2X DIMENSIONS	—	—	—	—
3X DIMENSIONS	—	—	—	—
4X DIMENSIONS	—	—	—	—
5X DIMENSIONS	—	—	—	—
6X DIMENSIONS	—	—	—	—
7X DIMENSIONS	—	—	—	—
8X DIMENSIONS	—	—	—	—
9X DIMENSIONS	—	—	—	—
10X DIMENSIONS	—	—	—	—
12X DIMENSIONS	—	—	—	—
15X DIMENSIONS	—	—	—	—
20X DIMENSIONS	—	—	—	—
25X DIMENSIONS	—	—	—	—
30X DIMENSIONS	—	—	—	—
40X DIMENSIONS	—	—	—	—
50X DIMENSIONS	—	—	—	—
60X DIMENSIONS	—	—	—	—
75X DIMENSIONS	—	—	—	—
100X DIMENSIONS	—	—	—	—

MIDSHIP PTO W/2.5" DRIVE SHAFT - IPO0704


W.S. DARLEY & CO. - MILWAUKEE, WIS. (MILWAUKEE, WIS.)  
 W.S. DARLEY & CO. - MILWAUKEE, WIS. (MILWAUKEE, WIS.)  
 W.S. DARLEY & CO. - MILWAUKEE, WIS. (MILWAUKEE, WIS.)

DATE: JUL 14, 1977  
 SCALE: 1/2"

W.S. DARLEY & CO. - MILWAUKEE, WIS. (MILWAUKEE, WIS.)  
 W.S. DARLEY & CO. - MILWAUKEE, WIS. (MILWAUKEE, WIS.)  
 W.S. DARLEY & CO. - MILWAUKEE, WIS. (MILWAUKEE, WIS.)

\*TORQUE YOKE NUT TO 150-200 lb-ft

REVISIONS		DATE	CHG. NO.	APPROV.
A	ADDED O-RING	05/JAN/02	2002-114	AS
B	ADDED WATER FLINGER	10/MAY/04	2004-111	AS



REP.#	NAME OF PART	QTY
1	PIPE ELBOW	1
2	PINION GEAR	1
3	KEY - PINION GEAR	1
4	COVER	1
5	SPACER	1
8	PTO OUTPUT SHAFT	1
9	BEARING CAP - OUTPUT	1
13	BALL BEARING	2
14	BEARING CAP - GASKET	1
15	SHIFTER BAR O-RING	1
16	CLUTCH SHIFT BAR	1
17	RETAINING RING - SHIFT BAR	1
18	DRIVE GEAR	1
19	BEARING RETAINER	1
20	TRANSMISSION SHAFT	1
21	TRANS. SHAFT SPACER	1
22	BALL BEARING	2
24	OIL SEAL - YOKE 2 15/16 DIA	1
25	FRONT BEARING	1
26	BALL BEARING	1
27	FRONT BEARING BRACKET GASKET	1
28	DRAIN PLUG - MAGNETIC 3/8	1
29	GEARCASE COVER GASKET	1
30	HEX HD CAP SCREW	12
31	GEARCASE COVER PLATE	1
32	DRIVE GEAR BOLT	6
34	PUMP CLUTCH GEAR	1
35	SLIDING CLUTCH GEAR	1
36	BALL BEARING	1
37	BALL BEARING	1
38	OIL SEAL	1
39	GREASE ZERK	1
40	OIL SEAL	1
41	BALL BEARING	1
42	BEARING CAP - REAR	1
43	BEARING BACK UP WASHER	1
44	YOKE	2
45	COVER	1
46*	LOCK NUT, YOKE	2
47	NUT	1
48	REAR DRIVE SHAFT	1
49	OIL SEAL	1
50	SAFETY WIRE	1
51	REAR BEARING BRACKET	1
52	LOCK BOLT, SHIFT YOKE	1
53	CLUTCH SHIFT YOKE	1
54	TACHOMETER PLUG	1
55	TACH CABLE DRIVE NUT	1
56	OIL SEAL - TACH SHAFT	1
57	BEARING CAP - IDLER	1
58	IDLER BEARING CAP GASKET	1
59	PTO OUTPUT FLANGE	1
60	OIL SEAL	1
61	PIPE PLUG	2
65	VENT PLUG - 1/8 NPT	1
66	GEARCASE	1
66	WASHER	1
359	WATER FLINGER	2


\*TORQUE YOKE NUT  
TO 150-200 lb-ft

DESIGN NO.	LDMTA29	REV.	0
DATE	10/09/07	BY	TED
CHECKED		DATE	
APPROVED		DATE	

LDMTA29  
 ALL DIMENSIONS IN  
 INCHES UNLESS NOTED  
 DO NOT SCALE PRINT  
 SCALE 1/2  
 THIS DRAWING IS THE PROPERTY OF  
 WISCONSIN POWER & LIGHT  
 COMPANY  
 ALL RIGHTS RESERVED  
 REPRODUCTION IS PROHIBITED

WISCONSIN POWER & LIGHT  
 COMPANY  
 1223  
 L123  
 LOW PTO, OP. ENG. ROT.  
 CROSS SECTION  
 DATE MARCH 90  
 Dwg. No. 1223  
 Scale 1/2  
 Dwg. No. 1223  
 Scale 1/2  
 Dwg. No. 1223  
 Scale 1/2

REVISED		DATE	CHG. NO.	APP'D
A	ADDED O-RING	06/JAN/02	2002-114	MS
B	ADDED WATER FLINGER	10/MAY/04	2004-111	MS




\*TORQUE YOKE NUT  
TO 150-200 lb-ft

W.S. DARLEY & CO. INC. MILWAUKEE, WISCONSIN 53211 U.S.A.	
LDM XHD SPLITSHAFT PTO	
ENGINE ROTATION	
DATE: MAR14/90	SCALE: 1/2
DESIGN: S. LEE	DATE: MAR14/90
DRW: MCR	SCALE: 1/2
REV: MCR	SCALE: 1/2
OLD PART NO. L116	LDMTA21
DLC0201	

NO.	DESCRIPTION	PART NO.	QTY.
1	GEAR - PINION, N. BRP, 20 PA	-	1
2	GEAR - DRIVE, PSP, 80P, 20DEG PA	-	1
3	KEY - SQ. - 0.38 X 2.50	-	1
4	HOUSING - BEARING, N. OUTBOARD	-	1
5	SPACER - 1.57 X 2.00 X 0.71	-	1
6	BEARING-BALL	-	1
8	SHAFT - INNER GEAR, N	-	1
9	BEARING CAP - IDLER	-	1
10	KEY - SQ. - 0.25 X 2.50 GR2	-	1
11	SPACER - 1.15 X 2.0 X 1.43	-	1
12	SHAFT - OUTPUT, PFD	-	1
13	BEARING - 22206 RC-3	-	2
14	ID-RING - 3.50 X 3.69 X 0.09	-	2
15	ID-RING - 0.88 X 1.12 X 0.12	-	1
16	SHIFT BAR - PSM	-	1
17	RING - RETAINER, 3169-87	-	1
18	GEAR - DRIVE, N. BRP, 20 DEGREE PA	-	1
20	SHAFT - TRANSMISSION	-	1
21	SPACER - 2.56 X 2.88 X 1.58	-	1
22	BEARING-BALL, 1138SF	-	2
25	BRACKET - BEARING, FRONT, N	-	1
26	BEARING-BALL, 2138F	-	1
27	ID-RING - 5.00 X 5.25 X 0.12	-	2
28	FLUID - PIPE, 0.315, WMS 50 HD	-	1
35	GEAR - SLIDING CLUTCH, N	-	1
36	BEARING-BALL, 3058F	-	1
37	BEARING-BALL, 1148SC0	-	1
39	OIL SEAL - 2.000 ID X 2.875 OD	-	1
40	OIL SEAL - 2.150 ID X 3.355 OD	-	2
41	BEARING-BALL, 2138F	-	1
42	REAR BEARING CAP, N	-	1
43	WASHER - 2.56 X 3.00 X .00 STL	-	2
44	END YONE	-	2
46	LOCUTIT	-	2
47	NUT - FLANGE, 718-14	-	1
48	SHAFT - TRANSMISSION	-	1
49	OIL SEAL - 2.338 ID X 3.156 OD	-	2
50	WIRE - SAFETY	-	1
51	BRACKET - BEARING, REAR MD BRK	-	1
52	LOCK BOLT - SHIFT BAR	-	1
53	SHIFT YOKE	-	1
54	FLUID - TACK, 88-80BMS	-	1
55	NUT - CABLE DRIVE, 40M, 5, 104	-	1
56	OIL SEAL - 0.315 ID X 0.688 OD	-	1
57	CAP - BEARING, IDLER, TACH	-	1
59	COMP FLANGE - 1410	-	1
61	BEARING-BALL, 3058F	-	1
65	VENT	-	1
66	GEARCASE - LOW/MID/HC, PUMP PFD	-	1
67	CAP - BEARING, PUMP SHAFT	-	1
101	WHS - 375-16 X 0.86, GRS	-	8
102	WASHER - LOCK, 0.315 ID	-	24
103	WHS - 500-13 X 1.75, GRS	-	3
104	SWS - 375-16 X 1.00, GRS	-	1
105	SWS - 375-16 X 1.25, GRS	-	7
106	WHS - 375-16 X 1.25, GRS	-	4
107	WHS - 375-16 X 1.75, GRS	-	4
108	WASHER - LOCK, 0.500 ID	-	3
109	WASHER - LOCK, MC, 0.315 ID	-	8
110	WHS - 375-16 X 1.00, GRS	-	8
120	SPACER - 1.15 X 2.40 X 0.86	-	1
124	PIN - DOWEL, .250 X 0.62, GRB	-	2
358	ID-RING - 4.50 X 4.69 X 0.09	-	1
359	FLINGER - WATER	-	2
362	PELLET - OIL WICK	-	6
363	ID-RING - 2.0M X 2.5M	-	1
365	ARE CULMER - 1.75 BORE	-	1
366	DIPSTICK - M2242.5 THE D	-	1
368	SPACER - 1.19 X 2.00 X .25	-	1
369	RING - RETAINER, 16000-383	-	1
372	TRANSMISSION COVER ASSEMBLY	-	1

REV	DESCRIPTION	DATE	CHK NO.	APPR




NO. 1200538	REV. 3	DATE: 02/15/06	SCALE: 1/1
DESIGNED BY: W.S. Dreyer & Co.	CHECKED BY: W.S. Dreyer & Co.	DATE: 02/15/06	SCALE: 1/1
APPROVED BY: W.S. Dreyer & Co.	DATE: 02/15/06	SCALE: 1/1	SCALE: 1/1
W.S. Dreyer & Co.	1100 W. 10th St.	Wichita, KS 67202	TEL: 316-261-1111
WICHITA GEAR, U.S.A.	1100 W. 10th St.	Wichita, KS 67202	TEL: 316-261-1111
DATE: 02/15/06	SCALE: 1/1	SCALE: 1/1	SCALE: 1/1
DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT
REMOVE SHARP EDGES	REMOVE SHARP EDGES	REMOVE SHARP EDGES	REMOVE SHARP EDGES
ALL DIMENSIONS IN INCH UNLESS NOTED	ALL DIMENSIONS IN INCH UNLESS NOTED	ALL DIMENSIONS IN INCH UNLESS NOTED	ALL DIMENSIONS IN INCH UNLESS NOTED
WAVELENGTHS IN MILLIMETERS	WAVELENGTHS IN MILLIMETERS	WAVELENGTHS IN MILLIMETERS	WAVELENGTHS IN MILLIMETERS
UNLESS OTHERWISE SPECIFIED	UNLESS OTHERWISE SPECIFIED	UNLESS OTHERWISE SPECIFIED	UNLESS OTHERWISE SPECIFIED
ALL DIMENSIONS IN INCH UNLESS NOTED	ALL DIMENSIONS IN INCH UNLESS NOTED	ALL DIMENSIONS IN INCH UNLESS NOTED	ALL DIMENSIONS IN INCH UNLESS NOTED
DATE: 02/15/06	SCALE: 1/1	SCALE: 1/1	SCALE: 1/1
DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT
DATE: 02/15/06	SCALE: 1/1	SCALE: 1/1	SCALE: 1/1
DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT
DATE: 02/15/06	SCALE: 1/1	SCALE: 1/1	SCALE: 1/1
DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT	DO NOT SCALE PRINT

NOTE: DIPSTICK, OIL WICK PELLETS, DOWEL PINS AND FASTENERS SHOWN ON EXPLODED VIEW (SHEET 2)  
 NOTE: BEARINGS WITH SINGLE SHIELDS - SHIELDED SIDE GOES TOWARD OUTSIDE OF TRANSMISSION

DLC0205

REV. NO.	DESCRIPTION	DATE	CHK. NO.	CHK. BY



NO.	DESCRIPTION	PART NO.	QTY.
1	GEAR - PINION, N, ROP, 20 PA	-	1
2	GEAR - DRIVE, RSP, ROP, 20DCG PA	-	1
3	KEY - SQ., 0.38 X 1.50	-	1
4	HOUSING - BEARING, N, OUTBOARD	-	1
5	SPACER - 1.57 X 2.40 X 0.71	-	1
6	BEARING-BALL	-	1
8	SHIM - IDLER GEAR, N	-	1
9	BEARING CAP, IDLER	-	1
10	KEY - SQ., 0.25 X 2.50 GR2	-	1
11	SPACER - 1.75 X 2.8 X 1.43	-	1
12	SHIM - OUTPUT PFD	-	1
13	BEARING - 22206 RC-3	-	2
14	O-RING - 3.50 X 3.69 X 0.09	-	2
15	O-RING - 0.88 X 1.12 X 0.12	-	1
16	SHIM BAR - PSH	-	1
17	RING - RETAINER, 5160-87	-	1
18	GEAR - DRIVE, N, ROP, 20 DEGREE PA	-	1
20	SHIM - TRANSMISSION	-	1
21	SPACER - 2.56 X 2.88 X 1.58	-	1
22	BEARING-BALL, 114K5CC	-	2
25	BEARING-BALL, 2135F	-	1
26	BEARING-BALL, 2135F	-	1
27	O-RING - 5.00 X 5.25 X 0.12	-	2
28	PLUG - PIPE, 0.375, MAG 50 HD	-	1
35	GEAR - SLIDING CLUTCH, N	-	1
36	BEARING-BALL, 3055FF	-	1
37	BEARING-BALL, 114K5CC	-	1
39	OIL SEAL - 2.000 ID X 2.879 OD	-	1
40	OIL SEAL - 2.150 ID X 3.055 OD	-	2
41	BEARING-BALL, 2135FF	-	1
42	REAR BEARING CAP, N	-	1
43	WASHER - 2.56 X 3.00 X .09 STL	-	1
44	END TONE	-	2
46	LOCKWUT	-	2
47	NUT - FLANGE, 7/8-14	-	1
48	SHIM - TRANSMISSION	-	1
49	OIL SEAL - 2.838 ID X 3.158 OD	-	2
50	WIRE - SAFETY	-	1
51	BRACKET - BEARING, REAR NO BRK	-	1
52	LOCK BOLT - SHIM BAR	-	1
53	SHIFT TUBE	-	1
54	PLUG - TACK, 48-10UNS	-	1
55	NUT - CABLE DRIVE, RHM, 0.104	-	1
56	OIL SEAL - 0.315 ID X 0.688 OD	-	1
57	CAP - BEARING, IDLER, TACH	-	1
59	COMP FLANGE - 1410	-	1
61	BEARING-BALL, 3055FF	-	1
65	VENT	-	1
66	GEARCASE - LOW/IDMG, PUMP FND	-	1
67	CAP - BEARING, PUMP SHFT	-	1
101	IMCS - 2375-16 X 0.88, GR5	-	8
102	WASHER - LOCK, 0.315 ID	-	24
103	IMCS - 550-13 X 1.75, GR5	-	3
104	IMCS - 2375-16 X 1.00, GR8	-	1
105	IMCS - 2375-16 X 1.25, GR8	-	7
106	IMCS - 2375-16 X 1.75, GR5	-	4
107	IMCS - 2375-16 X 1.75, GR5	-	4
108	WASHER - LOCK, 0.500 ID	-	3
109	WASHER - LOCK, 0.315 ID	-	8
110	IMCS - 2375-16 X 1.00, GR5	-	8
124	PIN - DOWEL, .250 X 0.86	-	2
158	O-RING - 4.50 X 4.69 X 0.09	-	1
359	FLINGER - WATER	-	2
362	PELLET - OIL WICK	-	6
363	O-RING - 2.000 X 2.500 X 2.500	-	1
365	AIR CYLINDER - 1.75 BORE	-	1
366	DIPSTICK - M2242.2 THRD	-	1
368	SPACER - 1.19 X 2.00 X .25	-	1
369	RING - RETAINER, R2000-393	-	1
372	TRANSMISSION COVER ASSEMBLY	-	1

REMOVE SHARP EDGES  
 INCH (MILLIMETERS)  
 THIS DRAWING IS THE PROPERTY OF W.S. DAY & CO. INC. AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.  
 DATE 04-10-95  
 W.S. DAY & CO. INC.  
 175 W. MAIN ST., SUITE 100  
 CANTON, MASS. 01921  
 U.S.A.  
 W.S. DAY & CO. INC.  
 175 W. MAIN ST., SUITE 100  
 CANTON, MASS. 01921  
 U.S.A.  
 DATE 04-10-95  
 W.S. DAY & CO. INC.  
 175 W. MAIN ST., SUITE 100  
 CANTON, MASS. 01921  
 U.S.A.

SCALE	1/2"
DATE	04-10-95
BY	W.S. DAY & CO. INC.
CHK. NO.	175
CHK. BY	W.S. DAY & CO. INC.
REV. NO.	1
DESCRIPTION	TRANSMISSION COVER ASSEMBLY
DATE	04-10-95
BY	W.S. DAY & CO. INC.
CHK. NO.	175
CHK. BY	W.S. DAY & CO. INC.
REV. NO.	1
DESCRIPTION	TRANSMISSION COVER ASSEMBLY

Prepared By: EAP  
 Revised By: EAP  
 Approved By: TED

Rev. 3  
 Date: 02/15/06  
 Rev Date: 10/09/07  
 1200538.doc



## PUMP SHIFTING PROCEDURE

For trucks equipped with manual transmissions, the following shifting procedure should be followed for pump operation:

1. Set parking brake.
2. Disengage truck clutch to stop shaft rotation.
3. Move pump shift lever to PUMP position.
4. Move truck transmission shift lever to neutral position.
5. Engage truck clutch.
6. Prime the pump (see priming instructions).
7. Disengage the truck clutch.
8. Move truck transmission shift lever to direct drive position and lock in place with safety latch.
9. Engage truck clutch to begin pumping.

If the power pump shift is provided, the procedure is identical except green indicator light (if provided) will come on at step #3 to show pump gear has been engaged.

To return to road operation:

1. Disengage truck clutch to stop shaft rotation.
2. Move truck transmission shift lever to neutral position.
3. Move pump shift lever to ROAD position.

When the truck is equipped with an automatic transmission, a danger exists that if the operator forgets to move the pump shift lever to PUMP position, and at the same time place transmission selector lever in high gear before leaving cab, the engine will continue to run due to converter slip. Upon advancing the vernier throttle at the pump operators panel, the engine could overcome the parking brake and accidentally move the truck. To prevent this possibility, the following shifting procedure should be followed for pump operation:

1. Set parking brake.
2. Place automatic transmission shift selector in neutral.
3. Move pump shift lever to PUMP position. "Pump Engaged" light in cab should now come on.
4. Prime the pump (see Priming Instructions).
5. Move automatic transmission shift selector to direct drive position (See Automatic Transmission Instructions).
6. Lock automatic transmission shift selector in direct drive position with safety latch provided.
7. Check that the parking brake is fully engaged.
8. Depress foot accelerator and observe that speedometer registers MPH. If pump is not engaged, speedometer will not indicate MPH.
9. Listen for pump shift and sound of pump gears turning.
10. At pump operators position, observe that the green indicator light above vernier throttle control is on. **Do not** operate throttle unless light is on.
11. Observe discharge pressure gage on panel while advancing vernier throttle, to ensure that it is indicating pressure. If Pump is not engaged, no pressure will show.
12. Remember, the vernier throttle has a quick release emergency center button. Push it all the way in immediately, should the truck move.

To return to ROAD OPERATION:

1. Place the truck transmission selector lever in reverse position to stop forward rotation of transmission shaft.
2. Move transmission selector to neutral, and at the same time, move the pump shift lever from PUMP to the ROAD position.

# **OPERATION OF PUMP SHIFT WITH AUTOMATIC TRANSMISSION**

The pump gear shift consists of a sliding clutch gear splined to the transmission shaft which can be moved forward to engage the pump clutch gear, or to the rear to engage the rear drive shaft connected to the truck drive axle.

The sliding clutch gear is moved either by direct mechanical linkage from a notched quadrant shift lever, or by an air power cylinder controlled by a selector valve. The shift lever or selector valve must be moved all the way and locked for either ROAD position to drive truck or PUMP position to pump.

## **MANUAL PUMP GEAR SHIFT PROCEDURE**

With trucking parking brake set, the truck transmission shift selector must be in neutral position to stop rotation of truck transmission output shaft before shifting into either ROAD or PUMP gear to prevent clashing and damage to gear teeth. With a manual pump gear shift control, a butt tooth position of gears may be encountered preventing engagement and "Pump Engaged" light from coming on. If this occurs, move transmission shift selector momentarily into any forward gear position with engine idling, then return to neutral. Wait approximately 5 seconds until shaft stops turning. Moving the pump shift lever to PUMP position again should complete the pump shift and turn on the "Pump Engaged" light. Repeat this procedure if a butt tooth condition is again encountered. Pump priming should be completed before shift to PUMP position.

## **AIR POWER PUMP GEAR SHIFT PROCEDURE**

With the air power pump gear shift control a butt tooth condition may also occur preventing engagement and "Pump Engaged" light from coming on. This can be easily overcome by momentarily placing truck transmission in any forward gear position with engine idling after the pump shift valve is placed in the PUMP position. Shaft rotation will complete the shift and turn on green "Pump Engaged" light. Transmission shift should be returned to neutral position after "Pump Engaged" light comes on for the pump priming period.

The above procedure insures that the pump shift is completed and the "Pump Engaged" light comes on. An alternate procedure in case of a butt tooth condition is simply to wait until the transmission is placed into pump drive gear position, when shaft rotation will immediately permit pump gears to mesh into full engagement.

The pump is usually operated with truck transmission in direct (high) gear such as D or 2-5. Overdrive may be required with very low speed engines.

When the truck is equipped with an automatic transmission, a danger exists that should the operator forget to move the pump shift valve to PUMP position, and at the same time place transmission selector in high gear before leaving cab, the engine will continue to run due to converter slip. If the operator advances the vernier throttle at the pump operators panel, the engine could overcome the parking brake and cause the truck to move. To prevent this possibility, the following shifting procedure should be followed for PUMP position:

1. Read and fully understand pump Operators Manual before proceeding.
2. Set parking brake and idle engine.
3. Place automatic transmission shift selector in neutral.
4. Move pump shift lever or valve to PUMP position. "Pump Engaged" green light in cab should now come on. If not, momentarily place truck transmission shift selector in a forward gear to complete pump shift, then return to neutral position. Green light will now be on.

5. Prime pump.
6. Move automatic transmission shift selector to direct drive position. "OK to Pump" green light in cab should now be on.
7. Lock automatic transmission shift selector in direct drive.
8. Listen for sound of pump gears turning. Speedometer will show MPH unless connected to the wheel.
9. At pump operators position, observe the green indicator warning light near vernier throttle control.  
WARNING: DO NOT OPEN THROTTLE UNLESS LIGHT IS ON.
10. Advance throttle to provide a minimum of 900 rpm idle speed. Observe discharge pressure gage on panel while advancing vernier throttle to make sure it is indicating pressure. If pump is not engaged or the pump is not primed, no pressure will show.

The vernier throttle has a quick release emergency red center button. Push it all the way in to return the engine to idle if necessary in an emergency situation

To return to ROAD operation:

1. Throttle engine back to idle.
2. Place the truck transmission selector lever in neutral position. Wait approximately 5 seconds until drive shaft stops rotating.
3. Move pump shift lever or valve from PUMP to ROAD position. "Pump Engaged" green indicator light should be off. A butt tooth condition may require momentary engagement of transmission to complete the shift.

## **OPERATION OF PUMP SHIFT WITH MANUAL TRANSMISSION**

The pump gear shift consists of a sliding clutch gear, splined to the transmission shaft which can be moved forward to engage the pump clutch gear, or to the rear to engage the rear drive shaft connected to the truck drive axle. A neutral position is half way between.

The sliding clutch gear is moved either by direct mechanical linkage from a notched quadrant shift lever, or by a vacuum or air power cylinder controlled by a selector switch. The shift lever must be moved all the way and locked for either ROAD position to drive truck or PUMP position to power pump.

The truck clutch must always be disengaged to stop rotation of truck transmission output shaft before shifting into either ROAD or PUMP gear to prevent clashing and damage to gear teeth. With the manual shift lever, a butt tooth position of gears may be encountered occasionally preventing engagement. If this occurs, move pump shift lever to neutral (half way) position, engage truck clutch momentarily, then disengage truck clutch and try pump shift again.

The pump is always operated with truck transmission in direct (high) gear, such as 4th on a 4 speed or 5th on 5 speed transmission.

The following shifting procedure should be followed for PUMP operation:

1. Set parking brake.
2. Disengage truck clutch.
3. Move pump shift lever (valve) to PUMP position. "PUMP ENGAGED" green light in cab should now come on.
4. Move truck transmission shift lever to neutral position.
5. Engage truck clutch.
6. Prime pump (See Priming Instructions).
7. Disengage truck clutch.
8. Move truck transmission shift lever to direct drive position and lock in place with safety latch provided.
9. Slowly engage truck clutch to begin pumping.

### **TO RETURN TO ROAD OPERATION**

1. Disengage truck clutch to stop shaft rotation. Allow 10 seconds for shaft to stop rotating.
2. Move truck transmission shift lever to neutral position.
3. Move pump shift lever (valve) to ROAD position.

### **CAUTION**

Follow the procedures step by step as indicated.



**IF FURTHER INFORMATION IS NEEDED, CALL W.S. DARLEY & CO. AT  
CHIPPEWA FALLS, WI. AT 800-634-7812 or 715-726-2650**

REVISIONS			
LTR	DESCRIPTION	DATE	CHG NO.
			APPR'D

NOTE: CONNECT TO AIR SOURCE THAT HAS AN 80 PSI PRESSURE PROTECTION VALVE

75 TO 120 PSI AIR SUPPLY

CHECK VALVE



AIR PRESSURE SHIFT PIPING DIAGRAM  
1-1/8 DIA. CYLINDER

TO NO. 3 PORT TO NO. 4 PORT TO NO. 4 PORT

VACUUM SHIFT PIPING DIAGRAM  
3" DIA. CYLINDER

INCH [MILLIMETER]




	<b>W.S. DARLEY &amp; CO.</b> MELROSE PARK, IL - CHIPPEWA FALLS, WI	
	DWG - POWER SHIFT VALVE	
DR'N	TED	DATE
CHKD		MAR10,97
TRCD		SCALE
		NTS

DGS0500

DO NOT SCALE PRINT

ALL DIMENSIONS IN INCHES UNLESS NOTED

THIS DESIGN IS THE PROPERTY OF W.S. DARLEY AND CO. - UNAUTHORIZED REPRODUCTION IS PROHIBITED



REFERENCE SPEC AY00201 (G427A1)  
& AY00202 (G427A2)

THIS DESIGN IS THE PROPERTY OF  
W.S. DARLEY AND CO. - UNAUTHORIZED  
REPRODUCTION IS PROHIBITED

ALL DIMENSIONS IN  
INCHES UNLESS NOTED

DO NOT SCALE PRINT

OLD PART NO.  
G2514

	<b>W.S. DARLEY &amp; CO.</b> MELROSE PARK, IL - CHIPPEWA FALLS, WI	DWG - 1.75" AIR CYLINDER
	DRN DWS CHKD TRCD	DATE JUN02.93 SCALE 1/1

DGC0701

## **WARNING: DO NOT USE THIS PUMP FOR HOSE TESTING**

### **OPERATING THE ENGINE**

After the pump has been primed, the engine speed should be increased gradually -- never jerk throttle wide open. Likewise, the engine speed should be decreased gradually when shutting down.

Watch the pump pressure gage and open throttle only enough to give the desired pressure. The pressure may rise high enough to burst the discharge hose, when using small nozzles, if the engine is given full throttle (except pumps equipped with pressure regulators set for desired pressure).

Never run engine at high speeds except when pump is primed and ready to discharge water.

### **COOLING THE ENGINE**

NFPA 1901 requires that a supplementary heat exchanger cooling system be provided. On most models, this heat exchanger is an integral part of the pump, and the installation of two hoses from the engine cooling system to the pump is all that is required.

On some models an external heat exchanger must be used. In that case two hoses from the engine cooling system and two lines from the pump will run to the heat exchanger.

The cooling line should not be opened until pressure develops in the pump, and pump should never be operated under heavy loads prolonged without an adequate supply of cooling water flowing.

Coolant temperatures should never be allowed to exceed 200° F while pumping and 180° F is usually taken as a safe operating temperature.

Always shut off cooling line when through pumping.

### **SUCTION STRAINERS**

A large suction strainer, which will prevent the passage of a body larger than the pump impeller ports, must always be used on the free end of the suction line when pumping from draft.

The small hydrant strainer must always be inserted in the suction manifold of pump, when pumping from hydrants and at all other times except when maximum capacity is required from draft.

Failure to use a strainer at all times when pumping will cause serious trouble by clogging the pump because, even in water mains, foreign matter is invariably present, and will be drawn into pump by the high velocity of the water entering.

### **SUCTION LINE**

The suction line of a fire pump can be the source of more operating difficulties than all the rest of the pump when working with a suction lift. Faults in the suction line which cause trouble in operation are as follows:

**AIR LEAKS** -- A small amount of air, expanding in the vacuum of the suction line, displaces a considerable volume of water which subtracts from the capacity that the pump is able to deliver, makes the priming difficult or causes pump to lose its prime. Therefore, it is absolutely essential to keep the suction line and the suction side of pump casing air tight at all time when drafting water.

Air leakage into pump while operating is usually indicated by a rattling sound in pump casing, miniature explosions in stream issuing from the nozzle, or by losing of prime when operating at very low capacities.

The usual cause of leaky suction lines is carelessness in handling of suction hose. Bruising of hose threads by bumping against hard surfaces or sand in the coupling often prevents tightening of the joints up against the gaskets. The hose gaskets are often defective and are sometimes lost without being noticed by the operator.

**INSUFFICIENT SUBMURGENCE** -- The free end of suction hose must be submerged to a sufficient depth to prevent the entrance of air that may be sucked down from the surface of the water to a considerable depth when operating at large capacities.

Entrance of air into suction lines in this manner is indicated by a small whirlpool, or vortex, on the surface of the water over the end of the hose.

A minimum submergence of 4 times the hose diameter to the upper holes in suction strainer is recommended where full capacity of pump is required. Where sufficient submergence is not possible, a board or sheet of metal laid over end of suction line will keep air from entering.

**SUCTION LINE ENTRANCE TOO CLOSE TO BOTTOM** -- If the end of suction line is laid on the bottom of the source of supply, a part of the suction opening will be shut off; and if the bottom is soft the hose will suck itself down into the earth, closing more of the opening and loosening sand and mud to be carried into the pump.

The suction entrance should be suspended a foot or more above the bottom, or if this is not possible, it should be laid on a board or piece of sheet metal. A rope tied to the suction strainer is a convenient means of holding it off the bottom.

**OBSTRUCTION OF SUCTION STRAINER BY FOREIGN MATTER** -- The high velocity of water entering the suction line will carry loose foreign bodies in against the strainer from a considerable distance. Therefore, all weeds and refuse should be removed from close proximity of the suction entrance.

**SUCTION LINE TOO SMALL OR TOO LONG** -- The flow of water into the pump is opposed by the frictional resistance in the suction line. This friction loss must be added to the height of the pump above the water (static lift) to determine the "total lift" of the pump. When all of the vacuum in the pump (atmospheric pressure) is consumed in raising water through this total lift, then the limit of capacity has been reached. This capacity can be increased only by decreasing total lift. If the static lift cannot be reduced, then the friction loss must be reduced by using a shorter or larger suction hose.

The rated capacity of the pump is guaranteed for a static lift of 10 feet, with 20 feet of recommended suction hose at sea level. To increase the capacity without reducing the static lift, or to increase lift without sacrificing capacity, requires larger suction hose.

An excessively long suction line is a handicap to any pump, for besides reducing capacity through the added friction loss, it retards priming and it produces a detrimental effect known as "cavitation". This means a separation of the water column in the pump suction, or void spaces, produced by the inertia of the heavy mass of water in the line resisting sudden change in the velocity when the pump starts to deliver or when discharge valves are opened or closed. This phenomenon reduces capacity further, and usually sets up a vibratory motion and "water hammer" as the water surges in and out of the void spaces.

When operating with a long suction line, the driving engine should be accelerated gradually, the discharge gates opened gradually, and the capacities of the pump should be held down to within the range of smooth performance.

**AIR TRAP IN SUCTION LINE** -- If the suction line is laid so that part of it is higher than any other part that is nearer to the pump, as when hose is laid over a high bridge rail, an air trap is formed at the highest part of the hose from which the air cannot be sucked out by the primer. This trapped air is expanded and carried into the pump with the first rush of water causing the pump to immediately lose its prime.

If suction line cannot be laid so that it slopes all the way from pump to water, it can still be primed easily by simply allowing the primer to continue to function until all the trapped air in the hose has been carried into the pump and picked up by the primer.



## TESTING FOR AIR LEAKS

Tests for leakage should be made with the suction hose attached and capped, discharge gate open, and all other openings closed tightly.

Run electric priming pump with primer shut-off valve open, until maximum vacuum is shown on the gage. The vacuum should hold for several minutes before satisfactory performance of pump can be expected.

If excessive leakage of air occurs, the source of leaks can be located by shutting off primer motor, with vacuum at its highest point, and listening for the hiss of air.

In the absence of a vacuum gage, the vacuum in pump may be judged by closing suction opening with the flat of hand or a rubber pad.

Water or air pressure may be applied to pump casing to test for air leakage if more convenient. DO NOT pressurize with air beyond 10 PSI

## SOURCE OF WATER SUPPLY

Water may be drafted from a pond, lake, stream, cistern, stock tank, or well; but whatever the source, the static lift must not exceed 20 feet from the center of the pump to the surface of the water and a lift not exceeding 10 feet is recommended. The source of supply should be reasonably clear and free from foreign matter. It is recommended that all water holes, which may be needed for fire protection, be deepened if necessary and kept free from weeds and refuse. In many fire protection areas, cisterns or reservoirs are built and allowed to fill up with rain water to be used in emergencies.

## PUMPING IN COLD WEATHER

The first insurance against cold weather trouble is to keep fire apparatus stored in heated quarters. All water must be eliminated from pump casing and primer line between periods of operations.

When setting up for pumping, unnecessary delays should be avoided by having thoroughly trained pump operators. Be sure that primer and booster lines are kept closed until ready for use. Having discharge lines ready so that pump may be started as soon as it have become primed. Do not stop flow of water through the pump until ready to drain and return to the station.

Engine Coolant from the engine circulated through the heater jacket in pump casing prevents all ordinary freezing troubles.

## WHEN FINISHED PUMPING

Drain water out of pump casing immediately. (Drain valve is located at lowest point in pump casing, and accessible from underneath chassis.)

Don't forget to close all drain cocks after all water has been drained out. Trouble in priming will follow on the next run if this is forgotten.

Shut off cooling line to make pump ready for priming again.

If pump transmission is equipped with a transmission cooler it must be drained also. If the master drain is located below the cooler outlets it can be connected to the master drain, if not, two separate drains must be connected to the transmission cooler. **Failure to drain transmission cooler will result in water in the gearcase if water in the cooling coil freezes.**

If pump is equipped with an external heat exchanger, drain heat exchanger using gravity and vacuum drain on all trucks as follows: Close all open lines and drain cocks. Open cooler valve and open air vent at top or drain cock at bottom of heat exchanger depending on model. With the pump air-tight open primer with engine running for about a minute and then close primer. Drain pump of water which was deposited when heat exchanger and lines were being drained.

Pump not often used for fire service should be inspected and run periodically to ensure that they will be in readiness for an emergency.

## **PUMPING SALT WATER**

The pump should be flushed out with fresh water immediately after pumping salt water to prevent excessive rusting. (Except pumps which are built of special material to resist the corrosive action of the brine.)

When measuring sea water with a Pitot Gage, capacities shown in Table No. 2 should be discounted approximately 1 1/2% to determine the correct capacity.

A centrifugal pump will show 2 1/2% higher pressure and require 2 1/2% more power when handling sea water than when handling fresh water if operated at the same speed and capacity.

### **TESTING OF EQUIPMENT FOR PRACTICE**

It frequently happens that operators of fire apparatus, who are not thoroughly familiar with its operations, become confused under the stress of emergency and neglect some little detail that may cause trouble or delay in getting the equipment into operation. Therefore, we urge that practice tests be conducted repeatedly until operators are thoroughly trained. More than one person in the department should be a competent operator.

Practice should include pumping from low lifts, high lifts with short and long suction lines, with suction line elevated to form an air trap, and from hydrants, at large and small capacities.

It is well, also, to note the effects of air leaks in hose, insufficient submergence and restriction of suction line. (Suction line can be restricted by placing a can or other strong closure around the suction strainer).

**NEVER BREAK OR RESTRICT SUCTION OR ALLOW AIR TO ENTER SUCTION LINE WHILE ENGINE IS OPERATING WITH THROTTLE OPEN.** This will release the load and allow engine to run away.

Do not allow personnel to hold a large nozzle while working at high pressures for serious accidents may result if hose breaks loose.

### **MEASURING PUMP PERFORMANCE**

Pump performance is measured by the quantity of water it can deliver per minute against a certain pressure called "Total Head" or "Net Pump Pressure", as it is usually termed in fire pump testing.

The net pump pressure is the sum of the pump discharge pressure, as shown on the pressure gage with which the pump is regularly equipped, and the total suction lift converted to equivalent pounds per square inch. If pump is operating from a hydrant, the net pump pressure is the discharge pressure less the incoming pressure from hydrant measured at the suction entrance of pump.

Capacity of fire pump is measured in gallons per minute. The usual method of measurement is to determine the pressure of the jet of water leaving a given size of nozzle by means of a "Pitot Gage" from which the capacity is computed mathematically.

A Pitot Gage consists of a small tube adapted to a point directly into the hose nozzle from the center of the issuing stream, the other end of the tube being connected to an accurate pressure gage.

The nozzle jet drives straight into the Pitot tube and converts the velocity of the jet to pressure which is an accurate measure of velocity of the water as it leaves the nozzle. The tip of the Pitot tube should be one-half the diameter of the nozzle away from nozzle tip while taking reading. Table No. 2 gives nozzle capacities for various Pitot Gage readings.

If a Pitot gage is not available approximate pump capacities can be determined by reference to Table No.3

## ACCEPTANCE TESTS

Acceptance tests require continuous tests of three hours duration: 2 hours at 100% rated capacity and 150 PSI net pump pressure; one-half hour at 70% capacity and 200 PSI; one-half hour at 50% capacity and 250 PSI; and a spurt test at 100% capacity and 165 PSI.

Table No. 1 shows recommended set-ups and gage readings for rating tests.

To adjust nozzle pressure for the correct capacity, while maintaining the correct pump pressure, it is necessary to make simultaneous adjustments of engine throttle and the discharge gate valve, partially closing the latter until just the right discharge resistance is built up.

## ENGINES

An Underwriter fire pump imposes heavy loads on the engine that drives it, often absorbing all of the power the engine is capable of delivering at full throttle. Continuous pumping gives the engine no time to rest. Therefore, a new engine and pump unit must be thoroughly broken-in before it is required to deliver prolonged maximum pump performance.

We recommend a minimum break in period of 20 hours at light pumping loads, with occasional spurt tests and interruptions. Temperature and lubrication should be checked during this period.

Engine manufacturers' power ratings usually show maximum performance of a selected, factory adjusted engine, operating without fan, generator, muffler or other accessories, and corrected for "ideal" conditions, i.e. sea level barometer (29.92" of mercury) 60°F and high humidity. Therefore, the actual power delivered by an average truck mounted engine is considerably lower than the manufacturers' rating, and allowances must be made in predicting pump performance.

### EFFECTS OF ATMOSPHERIC CONDITIONS ON ENGINE AND PUMP PERFORMANCE

Each one inch of drop in Barometric pressure or each 1000 feet of elevation of the pumping site reduces engine power approximately 3 1/2% for engines not equipped with a turbo charger.

Each 12° rise in temperature above 60° F of carburetor intake air reduces engine power approximately 1%.

Lowering of humidity reduces power slightly.

Each one inch drop in Barometric pressure or each 1000 feet of elevation reduces the maximum possible static lift of a pump approximately one foot.

Temperature of the water supply affects the attainable suction lift of a pump. The effect is slight at low water temperatures but becomes increasingly detrimental as the temperature rises.

A 10° rise from 70°F will subtract about 1/2 foot from the maximum attainable suction lift, while an equal rise from 100°F will reduce the lift at least 1 1/2 feet.

Temperature is an important consideration when pumping from a test pit where the water is heated by recirculation.

**IF FURTHER INFORMATION IS NEEDED, CALL W.S. DARLEY & CO. AT  
CHIPPEWA FALLS, WI. AT 800-634-7812 or 715-726-2650**

## DEFINITIONS

**HEAD OF WATER** -- vertical depth of water measured in feet or in pressure per unit or area. In hydraulics, head always represents pressure and it is expressed interchangeably in feet of water or pounds per square inch and sometimes in inches of depth of mercury.

**STATIC HEAD** -- the pressure that is exerted by a stationary column of water of a given height or depth.

**TOTAL HEAD OR TOTAL DYNAMIC HEAD** -- the maximum height above the source of supply to which the pump would elevate the water plus all the resistance to flow in the pipe or hose line.

**DISCHARGE HEAD** -- the pressure measured at the discharge outlet of a pump.

**SUCTION HEAD** -- the positive pressure measured at the suction entrance of a pump (when pumping from an elevated tank or hydrant).

**VELOCITY HEAD** -- the equivalent pressure represented by fluid in motion as measured by means of a Pitot Gage.

**STATIC LIFT** -- the vertical height of the center of the pump above the source of supply (when pump from draft).

**TOTAL SUCTION LIFT** -- the static lift plus the friction in suction line plus entrance losses.

**NET PUMP PRESSURE** -- the total dynamic head of the pump.

**EFFECTIVE NOZZLE PRESSURE** -- the pump discharge pressure minus hose friction plus or minus the difference in elevation above or below pump.

**WATER HORSEPOWER** - the theoretical power required to deliver a given quantity of water per minute against a given head.

**BRAKE HORSEPOWER** -- Actual power as delivered by a motor or engine to a driven machine.

**PUMP EFFICIENCY** -- The quotient of the water horsepower divided by brake horsepower required to produce it.

**WATER HAMMER** -- a series of shock waves produced in a pipeline or pump by a sudden change in water velocity. A sudden change in flow velocity can result from rapid closure of valves. A pressure wave is set up which travels back and forth in the water column at extremely high speed producing rapid vibrations that may be violent and destructive if the water column is long.

**THE MAXIMUM THEORETICAL LIFT** of a pump is 34 feet, which is the pressure of the atmosphere at sea level. The maximum practical total lift at sea level is 20 to 25 feet (depending on the type and condition of the pump) and this decreases with drops in barometric pressure.

## **OPERATING CHARACTERISTICS OF PUMPS**

**CENTRIFUGAL PUMPS:** A centrifugal pump develops pressure by centrifugal force of the liquid rotating in the impeller wheel. The pressure developed depends upon the peripheral speed of the impeller (increasing as the square of the speed) and it remains fairly constant over a wide range of capacities up to the maximum output of the pump, if speed remains constant.

If the discharge outlet of a centrifugal pump is entirely shut off, with speed kept constant, there is a small rise in pressure, the water churns in the pump casing and the power drops to a low value. If the discharge is opened wide, with little resistance to flow the pressure drops while the capacity and power both increase to their maximum.

A centrifugal pump is an extremely simple mechanism mechanically, but rather complex hydraulically; in that many factors enter into the design of the impeller and water ways which will affect the pump's efficiency.

**DISPLACEMENT PUMPS:** Rotary and piston pumps are termed "Positive Displacement" pumps because each revolution displaces or discharge (theoretically) an exact amount of liquid, regardless of the resistance. The capacity is, therefore, proportional to the number of revolutions of the pump per minute and independent of the discharge pressure except as it is reduced by "slip" (leakage past the pistons or rotors). For a given speed the power is directly proportional to the head. If the discharge is completely shut off, the pressure, power, and torque climb indefinitely until the drive power is stalled or breakage occurs.

Slip is the greatest factor affecting efficiency of a displacement pump, and this factor is greatly influenced by the condition of and wears on the working parts.

**IF FURTHER INFORMATION IS NEEDED, CALL W.S. DARLEY & CO. AT  
CHIPPEWA FALLS, WI. AT 800-634-7812 or 715-726-2650**

## CONVERSION FACTORS

One pound per square inch	=	2.31 feet of water
	=	2.04 inches of mercury
	=	27.7 inches of water
One foot of water	=	0.43 pounds per square inch
One inch of mercury	=	1.13 feet of water
	=	0.49 pounds per square inch
One cubic foot of water	=	62.4 pounds
	=	7.5 gallons
One gallon of water	=	231 cubic inches
	=	0.13 cubic feet
	=	8.34 pounds
	=	3.8 liters
One Imperial Gallon	=	1.2 U.S. gallons
Atmospheric Pressure (Sea Level)	=	14.8 pounds per square inch
	=	29.9 inches of mercury
	=	34 feet of water

**TABLE NO. 1**  
**NFPA 1901 TEST**

Class A							
TEST No.	GPM	Recom- mended Nozzles	Min. Nozzle Press. PSI	Min. Disch. Press. PSI	Min. Net Pump Press. PSI	Disch. Lines	Suction Hose
250 GPM Fire Pump							
1	250	(1), 1"	72	143	150		
2	175	(1), 7/8"	62	194	200	(1), 50'	20' of 3"
3	125	(1), 3/4"	56	244	250		
4	250	(1), 1"	72	158	165		
350 GPM Fire Pump							
1	350	(1), 1-1/4"	58	144	150		
2	245	(1), 1"	69	195	200	(1), 50'	20' of 4"
3	175	(1), 7/8"	62	245	250		
4	350	(1), 1-1/4"	58	159	165		
500 GPM Fire Pump							
1	500	(1), 1-1/2"	57	143	150	(1), 50'	
2	350	(1), 1-1/4"	58	194	200		20' of 4"
3	250	(1), 1"	72	245	250		
4	500	(1), 1-1/2"	57	158	165		
750 GPM Fire Pump							
1	750	(1), 1-3/4" or (2), 1-1/4"	68 66	142	150	(2), 50'	
2	525	(1), 1-1/2"	62	193	200	or	20' of 4-1/2"
3	375	(1), 1-1/4"	66	244	250	(2), 100'	
4	750	(1), 1-3/4" or (2), 1-1/4"	68 66	157	165	Siamesed	
1000 GPM Fire Pump							
1	1000	(1), 2" or (2), 1-1/2"	71 57	142	150	(2), 50'	
2	700	(1), 1-3/4" or (2), 1-1/4"	60 58	193	200	or	20' of 5"
3	500	(1), 1-1/2"	57	244	250	(3), 100'	
4	1000	(1), 2" or (2), 1-1/2"	71 57	157	165	Siamesed	

Min. discharge pressures listed above are for pumps operating with full 10' static suction lift. These pressures must be increased by 1 PSI for each 2.3 ft. less than 10' of lift.

**TABLE NO. 1**  
**NFPA 1901 TEST**

Class A							
TEST No.	GPM	Recom- mended Nozzles	Min. Nozzle Press. PSI	Min. Disch. Press. PSI	Min. Net Pump Press. PSI	Disch. Lines	Suction Hose
1250 GPM Fire Pump							
1	1250	(1), 2-1/4" or (2), 1-1/2"	69 88	143	150	(3), 50'	20' of 6"
2	875	(1), 2" or (2), 1-3/8"	55 61	194	200	or	
3	625	(1), 1-1/2"	88	245	250	(3), 100'	
4	1250	2-1/4" or (2), 1-1/2"	69 88	158	165	and (1), 50'  Siamesed	
1500 GPM Fire Pump							
1	1500	(2), 1-3/4" or (3), 1-1/2"	68 57	142	150	(3), 50'	20' of
2	1050	(1), 2" or (2), 1-1/2"	78 62	194	200	or	6" Min
3	750	(1), 1-3/4" or (2), 1-1/4"	68 66	245	250	(3), 100' and (1), 50'	or (2) 20' of
4	1500	(2), 1-3/4" or (3), 1-1/2"	68 57	157	165	Siamesed	6" Max

Min. discharge pressures listed above are for pumps operating with full 10' static suction lift. These pressures must be increased by 1 PSI for each 2.3 ft. less than 10' of lift.



**TABLE NO. 1**  
**NFPA 1901 TEST**

Class A							
TEST No.	GPM	Recom- mended Nozzles	Min. Nozzle Press. PSI	Min. Disch. Press. PSI	Min. Net Pump Press. PSI	Disch. Lines	Suction Hose
1750 GPM Fire Pump							
1	1750	(2), 2" or (3), 1-1/2" (2), 1-5/8" or	55 76 61	143	150	(4), 50'	(2) 20' of 6"
2	1225	(2), 1-1/2" or (3), 1-1/4"	84 79	194	200	or	
3	875	(1), 2" or (2), 1-3/8" (2), 2" or	55 61 55	245	250	(4), 100'	
4	1750	(3), 1-1/2"	76	158	165		
2000 GPM Fire Pump							
1	2000	(2), 2" or (4), 1-1/2" (2), 1-3/4" or	71 57 60	147	150	(4), 50'	(2) 20' of 6"
2	1400	(3), 1-1/2" (1), 2" or	49 71	199	200	or	
3	1000	(2), 1-1/2" (2), 2" or	57 71	249	250	(4), 100'	
4	2000	(4), 1-1/2"	57	163	165		
2250 GPM Fire Pump							
1	2250	(2), 2-1/4"	56	144	150	(2 Groups) (3), 100'	20' of 8"
2	1575	(2), 1-3/4"	76	196	200	Siamesed	
3	1125	(2), 1-1/2"	72	246	250		
4	2250	(2), 2-1/4"	56	153	165		

Min. discharge pressures listed above are for pumps operating with full 10' static suction lift. These pressures must be increased by 1 PSI for each 2.3 ft. less than 10' of lift.

**TABLE NO. 1  
NFPA 1901 TEST**

Class A							
TEST No.	GPM	Recom- mended Nozzles	Min. Nozzle Press. PSI	Min. Disch. Press. PSI	Min. Net Pump Press. PSI	Disch. Lines	Suction Hose
2500 GPM Fire Pump							
1	2500	(2), 2-1/4"	69	144	150	(2 Groups) (3), 100'	20' of 8"
2	1750	(2), 2"	55	195	200	Siamesed	
3	1250	(2), 1-1/2"	88	246	250		
4	2500	(2), 2-1/4"	69	159	165		
3000 GPM Fire Pump							
1	3000	(2), 2-1/2"	65	146	150	(2 Groups) (3), 100'	(2) 20' of 8"
2	2100	(2), 2"	78	196	200	Siamesed	
3	1500	(2), 1-3/4"	68	247	250		
4	3000	(2), 2-1/2"	65	161	165		
3000 GPM Industrial Fire Pump							
1	3000	(2), 2-1/2"	65	96	100	(2 Groups) (3), 100'	(2) 20' of 8"
2	2100	(2), 2"	78	146	150	Siamesed	
3	1500	(2), 1-3/4"	68	197	200		
3500 GPM Industrial Fire Pump							
1	3500	(2), 2-1/2" and (1), 2-1/4"	45 44	95	100	(2 Groups) (3), 100' Siamesed	(2) 20' of 8"
2	2450	(2), 2-1/4"	67	146	150	& (2)-50'	
3	1750	(2), 2"	55	197	200	Siamesed	

Min. discharge pressures listed above are for pumps operating with full 10' static suction lift. These pressures must be increased by 1 PSI for each 2.3 ft. less than 10' of lift.

**IF FURTHER INFORMATION IS NEEDED, CALL W.S. DARLEY & CO. AT  
CHIPPEWA FALLS, WI. AT 800-634-7812 or 715-726-2650**

**TABLE NO. 2**  
**DISCHARGE FROM SMOOTH BORE NOZZLE**  
**Pressures measured by Pitot gage.**

Nozzle Pressure PSI	1/4	3/8	1/2	5/8	3/4	7/8	1	1 1/8	1 1/4	1 3/8	1 1/2	1 5/8	1 3/4	2	2 1/4	2 1/2
	GALLONS PER MINUTE DELIVERED															
5	4	9	16	26	37	50	66	84	103	125	149	175	203	266	337	415
6	4	10	18	28	41	55	72	92	113	137	163	192	223	292	369	455
7	4	11	19	30	44	59	78	99	122	148	176	207	241	315	399	491
8	5	11	21	32	47	64	84	106	131	158	188	222	257	336	427	525
9	5	12	22	34	50	67	89	112	139	168	200	235	273	357	452	557
10	6	13	23	36	53	71	93	118	146	177	211	248	288	376	477	587
12	6	15	25	40	58	78	102	130	160	194	231	271	315	412	522	643
14	7	15	27	43	63	84	110	140	173	210	249	293	340	445	564	695
16	7	16	29	46	67	90	118	150	185	224	267	313	364	475	603	743
18	7	17	31	49	71	95	125	159	196	237	283	332	386	504	640	788
20	8	18	33	51	75	101	132	167	206	250	298	350	407	532	674	830
22	8	19	34	54	79	105	139	175	216	263	313	367	427	557	707	871
24	8	20	36	56	82	110	145	183	226	275	327	384	446	582	739	909
26	9	21	37	59	85	115	151	191	235	286	340	400	464	606	769	947
28	9	21	39	61	89	119	157	198	244	297	353	415	481	629	799	982
30	10	22	40	63	92	123	162	205	253	307	365	429	498	651	826	1017
32	10	23	41	65	95	127	167	212	261	317	377	443	514	673	854	1050
34	11	23	43	67	98	131	172	218	269	327	389	457	530	693	880	1082
36	11	24	44	69	100	135	177	224	277	336	400	470	546	713	905	1114
38	11	25	45	71	103	138	182	231	285	345	411	483	561	733	930	1144
40	11	26	46	73	106	142	187	237	292	354	422	496	575	752	954	1174
42	11	26	47	74	109	146	192	243	299	363	432	508	589	770	978	1203
44	12	27	49	76	111	149	196	248	306	372	442	520	603	788	1000	1231
46	12	28	50	78	114	152	200	254	313	380	452	531	617	806	1021	1259
48	12	28	51	80	116	156	205	259	320	388	462	543	630	824	1043	1286
50	13	29	52	81	118	159	209	265	326	396	472	554	643	841	1065	1313
52	13	29	53	83	121	162	213	270	333	404	481	565	656	857	1087	1339
54	13	30	54	84	123	165	217	275	339	412	490	576	668	873	1108	1364
56	13	30	56	86	125	168	221	280	345	419	499	586	680	889	1129	1389
58	13	31	56	87	128	171	225	285	351	426	508	596	692	905	1149	1414
60	14	31	57	89	130	174	229	290	357	434	517	607	704	920	1168	1437
62	14	32	58	90	132	177	233	295	363	441	525	617	716	936	1187	1462
64	14	32	59	92	134	180	237	299	369	448	533	627	727	951	1206	1485
66	14	33	60	93	136	182	240	304	375	455	542	636	738	965	1224	1508
68	14	33	60	95	138	185	244	308	381	462	550	646	750	980	1242	1531
70	15	34	61	96	140	188	247	313	386	469	558	655	761	994	1260	1553
72	15	34	62	97	142	191	251	318	391	475	566	665	771	1008	1278	1575
74	15	35	63	99	144	193	254	322	397	482	574	674	782	1023	1296	1597
76	15	35	64	100	146	196	258	326	402	488	582	683	792	1036	1313	1618
78	15	36	65	101	148	198	261	330	407	494	589	692	803	1050	1330	1639

**TABLE NO. 2**  
**DISCHARGE FROM SMOOTH BORE NOZZLE**  
**Pressures measured by Pitot gage.**

Nozzle Pressure PSI	1/4	3/8	1/2	5/8	3/4	7/8	1	1 1/8	1 1/4	1 3/8	1 1/2	1 5/8	1 3/4	2	2 1/4	2 1/2
	GALLONS PER MINUTE DELIVERED															
80	16	36	66	103	150	201	264	335	413	500	596	700	813	1063	1347	1660
82	16	37	66	104	152	204	268	339	418	507	604	709	823	1076	1364	1681
84	16	37	67	105	154	206	271	343	423	513	611	718	833	1089	1380	1701
86	16	37	68	107	155	208	274	347	428	519	618	726	843	1102	1396	1721
88	16	38	69	108	157	211	277	351	433	525	626	735	853	1115	1412	1741
90	17	39	70	109	159	213	280	355	438	531	633	743	862	1128	1429	1761
92	17	39	70	110	161	215	283	359	443	537	640	751	872	1140	1445	1780
94	17	39	71	111	162	218	286	363	447	543	647	759	881	1152	1460	1800
96	17	40	72	113	164	220	289	367	452	549	654	767	890	1164	1476	1819
98	17	40	73	114	166	223	292	370	456	554	660	775	900	1176	1491	1838
100	18	41	73	115	168	225	295	374	461	560	667	783	909	1189	1506	1856
105	18	42	75	118	172	230	303	383	473	574	683	803	932	1218	1542	1902
110	19	43	77	121	176	236	310	392	484	588	699	822	954	1247	1579	1947
115	19	43	79	123	180	241	317	401	495	600	715	840	975	1275	1615	1991
120	19	44	80	126	183	246	324	410	505	613	730	858	996	1303	1649	2033
125	20	45	82	129	187	251	331	418	516	626	745	876	1016	1329	1683	2075
130	20	46	84	131	191	256	337	427	526	638	760	893	1036	1356	1717	2116
135	21	47	85	134	195	262	343	435	536	650	775	910	1056	1382	1750	2157
140	21	48	87	136	198	266	350	443	546	662	789	927	1076	1407	1780	2196
145	21	49	88	139	202	271	356	450	556	674	803	944	1095	1432	1812	2235
150	22	50	90	141	205	275	362	458	565	686	817	960	1114	1456	1843	2273

**TABLE NO. 3**  
**Approximate Discharge Flow From Different Nozzles**  
**At the end of Fifty Feet of Average, 2 1/2”**  
**Rubber Lined Fire Hose, for Various**  
**Pump Pressures with Discharge**  
**Valve Wide Open**

PUMP PRESSURE LBS	SIZE OF NOZZLE & GALLONS PER MINUTE						
	3/4	7/8	1	1 1/8	1 1/4	1 3/8	1 1/2
30	90	119	153	187	217	250	282
40	103	137	177	216	253	290	327
50	115	153	198	242	284	325	367
60	126	168	216	265	311	357	402
70	136	182	234	287	337	385	435
80	145	194	250	308	361	414	465
90	154	206	265	325	383	437	492
100	162	217	280	343	405	462	520
110	171	228	295	360	425	485	549
120	179	239	307	377	444	510	572
130	186	249	318	392	462	530	596
140	193	258	330	407	480	549	618
150	200	267	341	421	497	567	
175	215	288	374	455	538		
200	230	309	395	486			
225	243	328	420				
250	257	345					

This table is offered as an aide in testing pump performance where facilities for accurate measurement of capacity are not available. The capacities given above are conservative, and will not vary more than 5% from actual capacities with any of the standard hose that might be used.

**TABLE NO. 4**

**Pump or Hydrant Pressure required to give Effective Nozzle Pressure through various Lengths of Rubber Lined Hose.**

Size of Hose		1				1 1/2		2		2 1/2				3	
Size of Nozzle		1/4	3/8	1/2	5/8	5/8	3/4	3/4	7/8	1	1 1/4	1 1/2	1 1/4	1 1/2	
Nozzle Press PSI	Length of Hose Feet	PUMP OR HYDRANT PRESSURE - PSI													
40	100	45	43	48	60	42	50	44	46	51	64	88	51	62	
	200	49	46	56	79	43	60	47	52	60	86	130	59	78	
	400	58	51	73	118	46	79	53	62	79	129	212	75	110	
	600	67	57	89	158	50	99	59	74	97	172		92	143	
	800	76	62	106	196	53	119	65	85	116	215		108	176	
	1000	85	68	122	235	56	138	72	96	134	258		124	208	
	1500	108	72	142		64	187	87	118	181			165		
	2000	130	96	204		72	226	103	151	227			205		
60	100	67	64	72	89	63	73	65	69	75	95	132	76	92	
	200	74	68	84	117	65	86	70	78	89	126	196	88	115	
	400	87	76	107	173	69	112	79	94	116	188		111	161	
	600	101	85	131	231	74	138	88	111	143	250		135	208	
	800	114	93	153		79	164	98	127	170			158		
	1000	127	101	178		83	190	107	143	197			182		
	1500	161	122	237		95	155	130	184	264					
	2000	195	142			106		153	225						
80	100	88	85	96	117	83	99	87	92	99	126	175	101	103	
	200	97	91	112	154	86	117	93	103	115	167		116	154	
	400	115	102	143	228	92	154	105	125	148	249		147		
	600	132	112	174		98	191	117	147	181			178		
	800	150	123	206		104	228	129	167	214			209		
	1000	167	134	238		110		141	191	247					
	1500	211	161			125		171	245						
	2000	254	188			140		201							
100	100	111	107	120	146	104	123	108	115	125	157		126	152	
	200	122	113	139	192	108	145	116	128	150	209		146	190	
	400	143	127	177	284	115	190	130	154	200			184		
	600	165	140	217		123	235	145	180	250			223		
	800	186	154	256		131		159	206						
	1000	208	167			138		174	232						
	1500	262	200			157		211							
	2000		234			175		253							

**TABLE NO. 5  
REACH OF FIRE STREAMS**

<b>Size of Nozzle</b>	<b>1/4"</b>	<b>3/8"</b>	<b>1/2"</b>	<b>5/8"</b>	<b>3/4"</b>	<b>7/8"</b>	<b>1"</b>	<b>1-1/4"</b>	<b>1-1/2"</b>
-----------------------	-------------	-------------	-------------	-------------	-------------	-------------	-----------	---------------	---------------

**NOZZLE  
PRESSURE      EFFECTIVE VERTICAL REACH - Feet**

40	30	35	40	50	59	62	64	65	69
60	35	40	45	60	74	77	79	84	87
80	38	42	48	65	81	85	89	94	96
100	40	44	50	68	84	89	94	100	102

**NOZZLE  
PRESSURE      MAXIMUM VERTICAL REACH - Feet**

40	60	65	70	75	78	79	80	80	80
60	70	75	85	95	105	106	108	110	110
80	78	83	95	105	117	125	132	140	140
100	80	88	100	110	122	135	145	155	155

**NOZZLE  
PRESSURE      EFFECTIVE HORIZONTAL REACH - Feet**

40	20	25	30	40	44	50	55	62	66
60	25	32	37	50	54	61	67	75	80
80	28	35	40	57	62	70	76	84	88
100	30	37	42	60	66	76	84	93	95

**NOZZLE  
PRESSURE      MAXIMUM HORIZONTAL REACH - Feet**

40	65	80	90	100	108	120	125	138	140
60	80	95	95	120	127	142	156	176	183
80	90	105	105	135	143	160	175	201	210
100	95	110	110	140	153	180	205	215	223

**TABLE NO. 6**  
**Friction Loss in Fire Hose**  
 Loss in PSI per 100 Feet of Hose

SIZE HOSE G.P.M.	LINEN HOSE			BEST RUBER LINED HOSE							
	1 1/2	2	2 1/2	3/4	1	1 1/2	2	2 1/2	3	3 1/2	(2)-2 1/2
10	1.0			13.5	3.5	0.5	.1				
15	2.2			29.0	7.2	1.0	0.3				
20	3.6			50.0	12.3	1.7	0.4				
25	5.5			75.0	18.5	2.6	0.6				
30	8.0	1.9		105.0	26.0	3.6	0.9				
40	13.0	3.2		180.0	44.0	6.1	1.5				
50	20.0	4.9	1.6		67.0	9.3	2.3				
60	28.0	7.0	2.2		96.0	13.5	3.3				
70	37.0	9.0	3.1		131.0	17.0	4.3				
80	47.0	11.5	3.8		171.0	23.0	5.6				
90	59.0	14.5	5.0		217.0	29.0	7.0				
100	72.0	17.5	5.9		268.0	33.0	8.4				
120		25.0	8.3		386.0	47.0	11.7				
140		34.0	11.0			62.0	16.0	5.2	2.0	0.9	1.4
160		43.0	14.0			78.0	20.0	6.6	2.6	1.2	1.9
180		53.0	17.7			97.0	25.0	8.3	3.2	1.5	2.3
200		63.0	21.5			121.0	30.6	10.1	3.9	1.8	2.8
220						146.0		12.0	4.6	2.1	3.3
240						173.0		14.1	5.4	2.5	3.9
260						204.0		16.4	6.3	2.9	4.5
280						237.0		18.7	7.2	3.3	5.2
300						272.0		21.2	8.2	3.7	5.9
320								23.8	9.3	4.2	6.6
340								26.9	10.5	4.7	7.4
360								30.0	11.5	5.2	8.3
380								33.0	12.8	5.8	9.2
400								36.2	14.1	6.3	10.1
425								40.8	15.7	7.0	11.3
450								45.2	17.5	7.9	12.5
475								50.0	19.3	8.7	13.8
500								55.0	21.2	9.5	15.2
525									23.2	10.5	16.6
550									25.2	11.4	18.1
575									27.5	12.4	19.6
600									29.9	13.4	21.2
650									34.5	15.5	24.8
700									39.5	17.7	28.3
750									45.0	20.1	32.2
800									50.5	22.7	36.2
850									56.5	25.4	40.7
900									63.0	28.2	45.2
1000									76.5	34.3	55.0

Losses in rough walled, rubber hose may be 50% higher than values given above.



**TABLE NO. 7**  
**Friction Loss in 15-year-old Steel Pipe**  
 Loss in PSI per 100 Feet of Pipe

PIPE SIZE G.P.M.	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	6	8
1	52.0	12.0	2.8	0.9										
2		45.0	10.0	3.2	4.0									
5			55.0	18.0	4.5	1.4	0.4							
10				64.0	16.0	5.0	1.3	0.6						
15				135.0	34.0	11.0	2.7	1.3	0.5					
20					59.0	18.0	4.7	2.2	0.8					
25					89.0	27.0	7.1	3.4	1.2					
30					125.0	39.0	10.0	4.7	1.7	0.6				
35						51.0	13.0	6.3	2.2	0.7				
40						66.0	17.0	8.0	2.9	0.9				
45						82.0	21.0	10.0	3.6	1.2				
50						99.0	26.0	12.0	4.3	1.4	0.6			
60						140.0	38.0	17.0	6.1	2.0	0.8			
70							49.0	23.0	8.0	2.7	1.1			
80							63.0	29.0	10.0	3.4	1.5			
90							78.0	36.0	13.0	4.3	1.8			
100							96.0	44.0	15.0	5.1	2.2	0.5		
125							144.0	66.0	24.0	7.8	3.3	0.8		
150								93.0	33.0	11.0	4.6	1.1		
175								125.0	44.0	15.0	6.1	1.5		
200									56.0	19.0	7.8	1.9		
250									84.0	28.0	12.0	2.9		
300									114.0	40.0	16.0	4.0	0.6	
350										53.0	22.0	5.4	0.8	
400										68.0	28.0	6.9	1.0	
450										84.0	35.0	8.6	1.2	
500										102.0	42.0	10.0	1.4	0.4
600											60.0	15.0	2.1	0.6
800												25.0	3.5	1
1000												37.0	5.2	1.3
1500													11.0	2.7
2000													19.0	4.7
2500													29.0	7.1
3000														10

**TABLE NO. 8**  
**Resistance of Fittings**  
**Equivalent Lengths of Straight Pipe - Feet**

PIPE SIZE	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4	5	6	8
Gate Valve	0.4	0.6	0.8	1.1	1.4	1.8	2.2	2.8	4.1	5.3	6.7	9.4
Global Valve	3.0	4.5	6.0	8.5	10.5	14.0	17.0	22.0	32.0	42.0	53.0	75.0
Angle Valve	1.4	2.0	2.7	3.8	4.8	6.3	7.9	10.5	14.5	18.5	23.0	33.0
Std. Elbow	1.1	1.5	2.0	2.8	3.5	4.7	5.8	7.5	11.0	14.0	18.0	24.0
45 Elbow	0.6	0.8	1.0	1.4	1.6	2.1	2.5	3.1	4.2	5.2	6.3	8.5
Long Sweep EI Str Run Tee	0.5	0.8	1.0	1.4	1.7	2.3	2.8	3.7	5.3	7.0	9.0	12.5
Std. Tee Thru Side Outlet	2.1	2.9	3.9	5.5	6.9	9.1	11.6	14.8	21.0	27.0	34.0	49.0
Sudden Enlarg or contraction	1.8	2.5	3.2	4.2	5.0	6.5	7.5	9.5	13.0	16.0	19.0	25.0
Entrance to Pipe	1.0	1.3	1.6	2.2	2.6	3.3	3.9	4.9	6.5	8.2	10.0	13.0

**TABLE NO. 9**  
**To Convert Pounds per Square Inch to**  
**Feet Elevation of Water**

**2.308ft head = 1.0 psi**  
**1ft head = .433psi**

Feet	5	10	15	20	25	30	35	40	45	50	60	70	80	90
Pounds	2.2	4.3	6.5	8.7	11	13	15	17	20	22	26	30	35	39
<b>Feet</b>	<b>100</b>	<b>120</b>	<b>130</b>	<b>140</b>	<b>150</b>	<b>160</b>	<b>170</b>	<b>180</b>	<b>190</b>	<b>200</b>	<b>220</b>	<b>240</b>	<b>260</b>	<b>280</b>
<b>Pounds</b>	<b>43</b>	<b>52</b>	<b>56</b>	<b>61</b>	<b>65</b>	<b>69</b>	<b>74</b>	<b>78</b>	<b>82</b>	<b>87</b>	<b>95</b>	<b>104</b>	<b>113</b>	<b>121</b>
Feet	300	320	340	360	380	400	425	450	475	500	525	550	600	700
Pounds	130	139	147	156	165	173	184	195	206	217	227	238	260	303


**Table NO. 10**  
**American National Fire Hose Connection Screw Thread - NH**

Size of Hose	4-Mar	1	1 1/2	2 1/2	3	3 1/2	4	4 1/2	5	6	8
Thr'ds per inch	8	8	9	7.5	6	6	4	4	4	4	4
Thread Designation	0.75-8 NH	1-8 NH	1.5-9 NH	2.5-7.5 NH	3-6 NH	3.5-6 NH	4-4 NH	4.5-4 NH	5-4 NH	6-4 NH	8-4 NH
Max. O.D. Male	1.375	1.375	1.99	3.0686	3.6239	4.2439	5.0109	5.7609	6.26	7.025	9.05

Ref. NFPA 1963

Underwriters Nozzle Tip Thread: 2.1875 O.D. - 12 threads per inch.

**IF FURTHER INFORMATION IS NEEDED, CALL W.S. DARLEY & CO. AT**  
**CHIPPEWA FALLS, WI. AT 800-634-7812 or 715-726-2650**



REF. PART No.	PART No.	NAME OF PART
6	PA153	TACHOMETER
5	G19A2	HAND SPEED CNTR
4	S1107	TACH. CABLE
3	PA152	SENDING UNIT
2	S1106	SPACER
1	PA154	TACH. DRIVE KEY

VARIABLE  
VARIABLE

# W.S. DARLEY & CO.

## SWITCHING DIESEL TACHOMETER

1. CAUTION: Disconnect the battery during installation. Tighten nuts on back clamp only slightly more than you can tighten them with our fingers. Six inch pounds of torque is sufficient. Over tightening may result in damage to the instrument and may void your warranty!
2. Location: The tachometer should be located at least 18" from a magnetic compass. Some interference (erratic operation) may be noticed on the tachometer during radio transmission. This will neither damage a Faria tachometer nor affect accuracy when not transmitting.
3. Be certain to use insulated wire not less than 18 gauge that is approved for marine use. It is recommended that insulated wire terminals, preferably ring type, be used on all connections to the tachometer except for the light which requires a 1/4" female blade terminal.
4. The tach sender, DK-3 or equivalent, must be used in conjunction with the tachometer. One DK-3 sender will operate two tachometers. Mount the sender to the pump at the mechanical tachometer drive take-off using the correct drive tip (supplied with DK-3) to properly engage the sender.
5. Using a small screwdriver, SLIGHTLY depress and turn the selector switch on the back of the tachometer to match the tachometer drive take-off (see label on side of tachometer).  
DEPRESSING THE SWITCH TOO HARD MAY CAUSE DAMAGE TO THE TACHOMETER.  
Be sure the selector switch has locked into the detent at the correct position by slightly rotating the switch back and forth with the screwdriver. (PTO Pump tach ratio = 1/2, Midship Pump tach ratio = 1/1).
6. Cut a 3-3/8" diameter hole in the dash and mount the tach with back clamp supplied.
7. Connect a wire to the tach stud marked "BAT" (battery) and secure with nut and lockwasher. Connect opposite end of the 12 VDC circuit that is activated by the ignition switch.
8. Connect a wire to the tach stud marked "SIGNAL" and secure with a nut and lockwasher. Connect the opposite end to the gray wire of the diesel tachometer sender. Connect the black wire of the diesel tachometer sender to the engine ground.
9. Connect a wire to the tach stud marked "GND" (ground) and secure with a nut and lockwasher. Connect opposite end to the electrical ground.
10. Connect the blade terminal adjacent to the twist-out light assembly to the positive "+" side of the vehicle's instrument lighting circuit. No separate ground is required for lighting.
11. Reconnect the battery.
12. NOTE: To change light bulb, twist black socket assembly one-eighth (1/8) turn counter clockwise until it pops out. Bulb pulls straight out of socket assembly. It is a GE #158 instrument lamp.

**IF FURTHER INFORMATION IS NEEDED, CALL W.S. DARLEY & CO. AT  
CHIPPEWA FALLS, WI. AT 800-634-7812 or 715-726-2650**

REVISIONS





NO.	DESCRIPTION	DATE	BY
1	ISSUED FOR PRODUCTION	08/28/09	MM

YOKE SIZE	A	B	CC
1550	5.75 (146.1)	28.90 (734.1)	2.25 (57.2)
1610	6.12 (155.4)	29.84 (757.9)	1.88 (47.8)
1710	5.83 (148.0)	28.86 (738.0)	2.38 (60.5)
1760	6.00 (152.4)	29.40 (746.8)	2.00 (50.8)
1810	5.86 (149.4)	29.16 (740.7)	2.12 (53.8)

SEE DRAWING DHD000 FOR DRIVE LINE PART DETAILS

BODY PANEL DIMENSIONS

SW	NS	DS
70 (1778)	5 (127)	13 (330)
72 (1829)	4 (102)	14 (356)



FRONT VIEW

REAR VIEW

SEE DETAIL DRAWING DGA1300 FOR MOUNTING BRACKET DIMENSIONS

NET WEIGHT: 1200 LBS

REMOVE SHARP EDGES

INCH DIMENSIONS


DO NOT SCALE PRINT

SCALE: 1/16" = 1"



DATE: 08/28/09

DL1300

NO.	DESCRIPTION	PART NO.	QTY.
1	BEARING - 2204 PC-3	-	2
2	BEARING CAP - IDLER	-	1
3	BEARING BALL	-	1
4	BEARING-BALL-308SF	-	1
5	BEARING-BALL-208SF	-	1
6	BEARING-BALL-208SF	-	1
7	CAP - BEARING, FRONT	-	1
8	CAP - BEARING, IDLER, TACH	-	1
9	CAP - BEARING, PTO DRIVE	-	1
10	CAP-BEARING, PS	-	1
11	CAMP FLANGE - 1350/1410, 1.50-10	-	2
12	COVER - GEARCASE, ENC., LOWC	-	1
13	DIPSTICK - M22 THRD, W/GROOVE	-	1
14	DRUMLOCK - 0.250 WPTM, 9HC BR	-	1
15	GASSET - GEARCASE COVER, LOWH	-	1
16	GEAR - DRIVE, M, 8DP, 20 PA	-	1
17	GEAR - DRIVE/IDLER, 8DP, 20 PA	-	1
18	GEAR - PINION, M, 8DP, 20 PA	-	1
19	GEARCASE - VERT 3 GR PTO	-	1
20	HEAT EXCHANGER - LOW TRANS	-	1
21	HMCS - 313-18 x 1.00, GR5	-	10
22	HMCS - 313-18 x 1.00, GR5	-	8
23	HMCS - 315-16 x 1.00, GR5	-	6
24	HMCS - 315-16 x 1.00, GR5	-	12
25	HOUSING - BEARING, OUTBOARD	-	1
26	RET - SO. - 315 X 2.375	-	2
27	RET - SO. - 0.25 X 2.50 GR2	-	1
28	RIPPLE - PIPE, .25 CLOSE, BR	-	1
29	MUT - CABLE DRIVE, RDM, 0.104	-	1
30	MUT - FLANGE, 178-14	-	2
31	NO-RING - 2.0MM X 2.5MM	-	1
32	NO-RING - 3.50 X 3.69 X 0.09	-	2
33	NO-RING - 5.00 X 5.25 X 0.12	-	4
34	NO-RING - 7.00 X 7.25 X .12	-	2
35	OIL SEAL - 0.315 ID X 0.688 OD	-	1
36	OIL SEAL - 2.125 ID X 3.068 OD	-	2
37	PLUG - PIPE, .250 X 0.62, GR8	-	2
38	PLUG - PIPE, 0.315, MAG 50 HD	-	1
39	PLUG - TACK, 88-108MS	-	1
40	SHAFT - IDLER GEAR, M	-	1
41	SHAFT - OUTPUT, LOW LIFT BOX	-	1
42	SHAFT - PTO INPUT, LOCATION	-	1
43	SHAFT - 1.19 X 2.00 X .25	-	1
44	SPACER - 1.50 X 2.00 X .46	-	1
45	SPACER - 1.57 X 2.00 X 0.71	-	1
46	SPACER - 1.75 X 2.00 X 1.43	-	1
47	SPACER - 1.75 X 2.40 X 0.86	-	1
48	SPACER - 1.75 X 2.40 X 0.86	-	1
49	TIE - PIPE, .25 WPT	-	1
50	TIE - PIPE, .25 WPT	-	1
51	TUBE FITTING - EL, .25 X .25	-	1
52	WREN - AIP, STRAIGHT	-	1
53	WASHER - LOCK, 0.215 ID	-	18
54	WASHER - LOCK, 0.215 ID	-	24
55	HMCS - 315 X 1.50, GR5	-	4
56	HMCS - 315 X 1.50, GR5	-	1
57	MOUNTING BRACKET	-	1



SECTION A-A



REVISIONS	
NO.	DESCRIPTION
1	INITIAL RELEASE

REV. NO.	REV. DATE	REV. BY	REV. REASON
1	03/04/10	DL	INITIAL RELEASE

DESIGNER	DATE	SCALE
DL	03/04/10	1:1

PROJECT NO.	REV. NO.	REV. DATE
DL2200	1	03/04/10

PROJECT NAME	PROJECT NO.
DL2200	DL2200


PROJECT NO.	REV. NO.	REV. DATE
DL2200	1	03/04/10

PROJECT NAME	PROJECT NO.
DL2200	DL2200

NO.	DESCRIPTION	PART NO.	QTY.
1	BEARING - 22206 AC-3	1729600	2
2	BEARING CAP - IDLER	2937298	1
3	BEARING-BALL	1729003	1
4	BEARING-BALL - 3095F	1729801	1
5	BEARING-BALL-2085F	1726801	1
6	BEARING-BALL-2085F	1726802	1
7	CAP - BEARING - FRONT	2312900	1
8	CAP - BEARING - IDLER, TACH	2309937	1
9	CAP - BEARING - PTO DRIVE	2304101	1
10	CAP-BEARING - PS	2935502	1
11	COMP FLANGE - 1350/1410, 1.50-14	4817816	2
12	COVER - GEARCASE, ENC, LDMC	2933300	1
13	DIPSTICK - M22 THRD, W/GROOVE	4219001	1
14	DRAINCOCK - 0.250 W/IN, 9/16 BR	5023800	1
15	GASNET - GEARCASE COVER, LOW	3015300	1
16	GEAR - DRIVE, H, 80P, 20 PA	2711700	1
17	GEAR - DRIVE/IDLER, 80P, 20 PA	2711300	1
18	GEAR - P/IDLOM, H, 80P, 20 PA	2712807	1
19	GEARCASE - VERT 3 GR PTO	1804202	1
20	HEAT EXCHANGER - LOW TRANS	4218900	1
21	HMCS - 313-18 x 0.63, GR5	5400017	10
22	HMCS - 313-18 x 1.00, GR5	5400020	8
23	HMCS - 315-16 x 0.75, GR5	5400034	8
24	HMCS - 315-16 x 1.00, GR5	5400036	12
25	HOUSING - BEARING, OUTBOARD	2306802	1
26	KEY - SO, .315 X 2.375	3602447	2
27	KEY - SO, 0.25 X 2.50 GR2	3602438	1
28	NUCLE - PIPE, .25 CLOSE, BR	1081005	1
29	MUT - CABLE DRIVE, RM, 0.104	1141900	1
31	MUT - FLANGE, 7/8-14	4814501	2
32	O-RING - 20MM x 2.5MM x 2.5MM	3601702	1
33	O-RING - 3.50 x 3.68 x 0.69	3601724	2
34	O-RING - 5.00 x 5.25 x 0.12	3601227	4
35	O-RING - 7.00 x 7.25 x .12	3601298.1FM	1
36	OIL SEAL - 0.315 ID X 0.688 OD	3605324	1
37	OIL SEAL - 2.125 ID X 3.085 OD	3605509	2
38	PIN - DOWEL, .250 X 0.62, GR8	3605401	2
39	PLUG - PIPE, 0.315, MFG SO HO	1080336	1
40	PLUG - TACH, 60S-100MS	1142101	1
41	SHAFT - IDLER GEAR, W	5005201	1
42	SHAFT - OUTPUT, LOW LIFT BOX	5005304	1
43	SHAFT - PTO INPUT, LOCION	5009002	1
44	SPACER - 1.19 X 2.00 x .25	3302204	1
45	SPACER - 1.50 X2.00 x .46	3307600	1
46	SPACER - 1.57 X 2.00 X 0.71	3303400	1
47	SPACER - 1.75 X 2.00 X 1.43	3306702	1
48	SPACER - 1.75 X 2.00 X 1.77	3306701	1
49	SPACER - 1.75 X 2.40 X 0.86	3305700	1
50	TEE - PIPE, .25 WPI	1080404	1
51	TUBE FITTING - EL, .75 x .75	3500509	1
52	TUBE FITTING - STR, .75 x .75	3500009	1
53	VERT - AIR, STRAIGHT	4034001	1
54	WASHER - LOCK, 0.313 ID	3603502	18
55	WASHER - LOCK, 0.315 ID	3603503	24
56	HMCS - 315-16 x 1.50, GR5	5400038	4
57	MOUNTING BRACKET	4037000	1

REVISIONS		
NO.	DESCRIPTION	DATE
1	INITIAL RELEASE	03/10/04
2	REVISED	03/10/04



SCALE 3/16

REMOVE SHARP EDGES  
 FINISH: MILL/TURN  
 MATERIAL: 304 SS  
 PARTS LISTED AS LISTED  
 THIS DRAWING IS THE PROPERTY OF  
 THE MANUFACTURER. IT IS TO BE USED ONLY FOR THE PARTS LISTED.  
 DO NOT SCALE PRINT  
 DATE: 03-10-04  
 DRAWN: JLB  
 CHECKED: JLB  
 APPROVED: JLB  
 TITLE: MECHANICAL ASSEMBLY  
 PROJECT: 2200  
 DRAWING NO: DLC2200