

2BE 21H

MEDIUM PRESSURE, HIGH VOLUME, DIRECT DRIVE, ENGINE MOUNTED



Honda GX 630: 4 cycle, 21 HP, V-twin, OHV, replaceable oil filter, 38.5 cu. in. displacement, 12 volt starter, 20 amp regulated alternator, 6 gal. fuel tank, hose and adapter

DIMENSIONS & WEIGHT


• 24"L x 27"W x 22"H, 190 lbs. (86 kg)

APPLICATIONS

ENGINE

• Booster reel, multiple hand lines, wildland/attack fire suppression

STANDARD FEATURES



- Discharge valve
- Sulfuric anodized aluminum alloy gear case and engine adapter
- Bronze impeller and wear ring
- Mechanical seal
- Built-in discharge check valve
- Adjustable discharge valve
- 3" NPT suction
- 1-21/2" NPT and 2-11/2" NPT or 1-21/2" NPT discharge

OPTIONS

2BE 21H marine pump also available, dual electronic controls, Smartstart™

PERFORMANCE



380 gpm (1438 L/M) @ 25 psi (1.7 bar) 150 gpm (568 L/M) @ 115 psi (7.9 bar) 100 gpm (378 L/M) @ 135 psi (9.3 bar)



