

2-1/2 AGE 65K KUBOTA WITH DigiTrol™ PANEL

TIER 4
DIESEL
DRIVEN
PUMP



STANDARD DIGITROL™ PANEL



OPTIONAL SECONDARY PANEL

OPTIONAL INTEGRAL PRESSURE GOVERNOR
AND LOSS OF WATER PROTECTION AVAILABLE
ON PANELS

- Kubota D1803T Turbo Diesel: 65 HP, liquid cooled, 12 volt starter, 40 amp alternator, fuel and oil pump filters

ENGINE

- 47.5" L x 50.2" W x 27.8" H, 760 lbs. (344.7 kg)

DIMENSIONS & WEIGHT

- Hard anodized aluminum alloy pump casing and discharge
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction
- Electronic throttle
- Power indicator light
- Digital pressure readout
- Hour meter
- Oil psi
- Tachometer
- Engine coolant temperature
- Volt meter
- Overridable engine shutdowns
- 2 1/2" NPT suction
- 2-1 1/2" NPT or 1-2 1/2" NPT discharges
- Skid base

STANDARD FEATURES

- Dual panels (can add multiple panels)
- Optional pressure governor and loss of water protection panel feature
- 12 volt primer

OPTIONS

250 gpm (946 L/M) @ 235 psi (16.2 bar)

200 gpm (757 L/M) @ 270 psi (18.6 bar)

150 gpm (567 L/M) @ 315 psi (21.7 bar)

100 gpm (378 L/M) @ 360 psi (24.8 bar)

Meets type 2 and type 3 wildland requirements

PERFORMANCE

PUMPSALES@DARLEY.COM

1.800.4.DARLEY • DARLEY.COM •

