



TRUSTED WORLDWIDE SINCE 1908

2-1/2AGE 48K KUBOTA WITH DigiTrol™ PANEL

TIER 4
DIESEL
DRIVEN
PUMP



STANDARD DIGITROL™ PANEL



OPTIONAL SECONDARY PANEL

OPTIONAL INTEGRAL PRESSURE GOVERNOR
AND LOSS OF WATER PROTECTION AVAILABLE
ON PANELS

- Kubota D1803T Diesel: 48 HP, liquid cooled, 12 volt starter, 40 amp. alternator, fuel and oil pump filters

ENGINE

- 45.65" L x 24.78" W x 47.32" H, 740 lbs. (335.6 kg)

DIMENSIONS & WEIGHT

- Hard anodized aluminum alloy pump casing and discharge
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction
- Electronic throttle
- Power indicator light
- Digital pressure readout
- Hour meter
- Oil psi
- Tachometer
- Engine coolant temperature
- Volt meter
- Overridable engine shutdowns
- 2 1/2" NPT suction
- 2-1 1/2" NPT or 1-2 1/2" NPT discharges

STANDARD FEATURES

- Dual panels (can add multiple panels)
• Optional pressure governor and loss of water protection panel feature
• 12 volt primer

OPTIONS

- 250 gpm (946 L/M) @ 190 psi (13.1 bar)
200 gpm (757 L/M) @ 225 psi (15.5 bar)
150 gpm (567 L/M) @ 250 psi (17.2 bar)
100 gpm (378 L/M) @ 260 psi (17.9 bar)

PERFORMANCE



PUMPSALES@DARLEY.COM
1.800.4.DARLEY • DARLEY.COM •