

2-1/2AGE 37V (EFI)

MEDIUM PRESSURE, HIGH VOLUME, GEAR DRIVEN, ENGINE MOUNTED



ENGINE

- Briggs & Stratton: 37 HP, V-Twin, OHV, EFI 4 cycle, air cooled gas engine, electric start, flywheel alternator, fuel and oil pump filters

DIMENSIONS & WEIGHT

- 28" L x 27" W x 31" H, 217 lbs. (98 kg)

APPLICATIONS

- Booster reel, multiple hand lines, wildland/attack fire suppression

STANDARD FEATURES

- Hard anodized aluminum alloy casing and discharge head
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Helical gears
- Discharge check valve and adjustable discharge valve
- Sulfuric anodized aluminum alloy gear case and engine adapter
- Exhaust primer
- **Control Panel:** Mounted with engine controls and pressure gauge (also available for remote mounting)
- 2 1/2" NPT suction inlet
- 2-1 1/2" NPT and 1-2 1/2" NPT discharges



OPTIONS

- Battery, adapters and caps

PERFORMANCE

300 gpm (1135 L/M) @ 100 psi (6.8 bar)
200 gpm (757 L/M) @ 150 psi (10.3 bar)
50 gpm (189 L/M) @ 280 psi (19.3 bar)
25 gpm (95 L/M) @ 310 psi (21.4 bar)

