

# 2-1/2AGE 24K WITH DigiTrol™ PANEL

MEDIUM PRESSURE, MEDIUM VOLUME, GEAR DRIVEN, ENGINE MOUNTED



## ENGINE

- Kubota D902 Diesel: 24 HP, liquid cooled, 12 volt starter, 40 amp alternator, fuel and oil pump filters

## DIMENSIONS & WEIGHT

- 36"L x 22"W x 26"H, 376 lbs. (170 kg)

## APPLICATIONS

- Booster reel, multiple hand lines, transfer and supply, wildland/attack fire suppression

## STANDARD FEATURES

- Aluminum alloy casing and discharge valve
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction
- 2½" NPT suction
- 2-1½" NPT or 1-2½" NPT discharges

## OPTIONS

- Dual panels, electric and manual throttles, rotary vane primer

## PERFORMANCE

225 gpm (851 L/M) @ 100 psi (8.9 bar)  
125 gpm (473 L/M) @ 150 psi (10.3 bar)  
50 gpm (189 L/M) @ 170 psi (11.7 bar)



OPTIONAL INTEGRAL PRESSURE GOVERNOR AND LOSS OF WATER PROTECTION AVAILABLE ON PANELS

