

2-1/2AGE 250DTZ

SINGLE STAGE, ENGINE DRIVEN, CENTRIFUGAL PUMP



ENGINE

- Deutz D914L03 Diesel: 57 HP, air-cooled, 12 volt, electric starter, alternator

DIMENSIONS & WEIGHT

- 45" L x 27.4" W x 31.3" H, 925 lbs. (419.5 kg)

APPLICATIONS

- Meets 250 gpm @ 150 psi for Type 2 Structure engines
- Meets 150 gpm @ 250 psi for Type 3 Wildland engines

STANDARD FEATURES

- Aluminum alloy casing
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat-treated alloy steel helical gears
- Ball bearing construction
- Heavy duty air cleaner
- Engine control panel
- Tachometer
- Hour meter
- Oil pressure gauge
- Ammeter
- Throttle
- Muffler
- Start/stop key switch
- 2 1/2" NPT suction
- 2 1/2" NPT flanged discharge

OPTIONS

2-1/2AGE 250CM

- Cummins B3.3 Diesel: 60 HP, liquid cooled, 12 volt electric starter, alternator
- 53.44" L x 27.88" W x 58.83" H, 700 lbs. (317.5 kg)

2-1/2 AGE 250JD

- John Deere 4024HF295 Diesel - 61 HP, 4 cycle, liquid cooled, 12 volt, electric starter, alternator
- 56" L x 28.6" W x 53.5" H, 825 lbs. (374.2 kg)

PERFORMANCE

250 gpm (946 L/M) @ 150 psi (10.3 bar)
175 gpm (662 L/M) @ 200 psi (13.8 bar)
125 gpm (473 L/M) @ 250 psi (17.2 bar)

