

2BE 23V VANGUARD

MEDIUM PRESSURE, HIGH VOLUME, DIRECT DRIVE, ENGINE MOUNTED



ENGINE

- Briggs & Stratton Vanguard: 4 cycle, 23 HP, V-twin, OHV, replaceable oil filter, 12-volt starter, recoil rope start back-up, 16 amp regulated alternator, 6 gal. fuel tank, control panel

DIMENSIONS & WEIGHT

- 24" L x 21" W x 24" H, 195 lbs. (89 kg)

APPLICATIONS

- Booster reel, multiple hand lines, wildland/attack fire suppression

STANDARD FEATURES

- Aluminum alloy casing
- Discharge valve
- Bronze impeller and seal rings
- Stainless steel impeller shaft
- Shredded plastallic packing
- Exhaust primer
- Built-in discharge check valve
- Adjustable discharge valve
- 3" NPT suction
- 2-1/2" NPT and 1-2/2" NPT discharges (not shown)

OPTIONS

- Adapters, gauge, battery, caps, Smartstart™

PERFORMANCE

390 gpm (1476 L/M) @ 30 psi (2.1 bar)
200 gpm (757 L/M) @ 110 psi (7.6 bar)
100 gpm (378 L/M) @ 140 psi (9.7 bar)

