



2BE 24K Portable Pump

Portable Diesel-Powered Pump

Specifications

Dimensions & Weight

- 35" L x 23.3" W x 26.3" H
- 386 lbs. (175 kg)

Applications

- Booster reel
- Multiple hand lines
- Wildland/attack fire suppression

Engine

- Kubota D902 Diesel: 24 HP, 3600 RPM, liquid cooled, 12 volt starter, 40 amp alternator, fuel and oil pump filters

Features

- Aluminum alloy casing and discharge valve
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction
- 3" NPT suction
- 2-1/2" NPT or 1-2/2" NPT discharges

Options

- Dual panels (can add multiple panels)
- Optional pressure governor and loss of water protection panel feature
- 12 volt primer



Medium Pressure, High Volume, Gear Driven, Engine Mounted

Performance

390 gpm (1476 L/M) @ 20 psi (1.4 bar)
300 gpm (1135 L/M) @ 80 psi (5.5 bar)
200 gpm (757 L/M) @ 115 psi (7.9 bar)



Standard DIGITROL™ Panel



Optional Secondary Panel



darley.com/pumps
630.735.3500