



2-1/2AGE 24K

Portable Diesel-Powered Pump

Specifications



Dimensions & Weight

- 36"L x 22"W x 26"H
- 376 lbs. (170 kg)



Applications

- Booster reel
- Multiple hand lines
- Transfer and supply
- Wildland/attack fire suppression



Engine

- Kubota D902 Diesel: 24 HP, liquid cooled, 12 volt starter, 40 amp alternator, fuel and oil pump filters



Features

- Aluminum alloy casing and discharge valve
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction
- 2 1/2" NPT suction
- 2-1 1/2" NPT or 1-2 1/2" NPT discharges



Options

- Dual panels (can add multiple panels)
- Optional pressure governor and loss of water protection panel feature
- 12 Volt primer



Medium Pressure, Medium Volume, Gear Driven, Engine Mounted

Performance

275 gpm (1041 L/M) @ 75 psi (5.2 bar)

150 gpm (568 L/M) @ 135 psi (9.3 bar)

50 gpm (189 L/M) @ 180 psi (12.4 bar)



Standard DIGITROL™ Panel



Optional Secondary Panel



darley.com/pumps
630.735.3500