

2BE 23V Vanguard

Portable Gasoline-Powered Pump

Specifications



Dimensions & Weight

- 24"L x 21"W x 24"H
- 195 lbs. (89 kg)



Applications

- Booster reel
- Multiple hand lines
- Wildland/attack fire suppression



Engine

 Briggs & Stratton Vanguard: 4 cycle, 23 HP, V-twin, OHV, replaceable oil filter, 12-volt starter, recoil rope start back-up, 16 amp regulated alternator, 6 gal. fuel tank, control panel



Features

- · Aluminum alloy casing
- · Discharge valve
- Bronze impeller and seal rings
- Stainless steel impeller shaft
- Mechanical seal
- Exhaust primer
- Built-in discharge check valve
- · Adjustable discharge valve
- 3" NPT suction
- 2-1¹/₂" NPT and 1-2¹/₂" NPT discharges (not shown)



Options

- Smartstart™
- Adapters, gauge, battery and caps



Medium Pressure, High Volume, Direct Drive, Engine Mounted

Performance

390 gpm (1476 L/M) @ 30 psi (2.1 bar) 200 gpm (757 L/M) @ 110 psi (7.6 bar) 100 gpm (378 L/M) @ 140 psi (9.7 bar)









darley.com/pumps 630.735.3500