



# HSP

PTO Driven Pump

## Specifications



### Industry's Longest Warranty

- 10 year manufacturer's, 10 year parts and 3 year labor



### Dimensions & Weight

- 15"L x 11"W x 18"H
- 127 lbs. (58 kg)



### Applications

- Mini Pumper
- Tanker
- Wildland/attack fire



### Features

#### Assembly #1

- 2 1/2" NPT discharge
- 3" or 4" NPT suction
- Rotation: Engine only
- Gear ration: 3.95 to 1 or 2.85 to 1
- Heat treated gears are standard
- Mounting angles
- 1310/1410 lock on companion drive flange

#### Assembly #2

- 2 - 2 1/2" NPT discharge
- 2 - 3" or 4" NPT suction

#### Assembly #3

- 2 - 2 1/2" NH, 1/4 turn, ball, valves and caps
- 2 - 3" or 4" NH suction with adapters and caps
- 2 - 2 1/2" NPT tapped openings on discharge manifolds
- 2 - 2 1/2" NPT tapped openings on suction
- Body Width: 70" - 72"



## 250 GPM, Single Stage, High Pressure, Centrifugal

- 400 gpm (1514 L/M) @ 50 psi (3.44 bar)
- 300 gpm (1135 L/M) @ 300 psi (20.68 bar)
- 200 gpm (756 L/M) @ 300 psi (20.68 bar)
- 150 gpm (568 L/M) @ 400 psi (27.58 bar)



darley.com/pumps  
800.323.0244

