



ZSM

Midship Mounted NFPA Pump



Specifications

- Industry's Longest Warranty**
 - 10 year manufacturer's, 10 year parts and 3 year labor
- Dimensions & Weight**
 - 31"L x 24"W x 41"H
 - 752 lbs. (341 kg)
- Applications**
 - Industrial
 - ARFF
- Features**
 - Manual override
 - Aluminum gear case
 - Auto lubrication system
 - 6" weld discharge
 - 8" weld flange suction
- Options**
 - Complete discharge and suction manifold
 - Swept tee suction head with 8" victaulic or 8" NH threaded couplings
 - Bronze available

2500 – 3000 GPM, Single Stage, Centrifugal, Single Suction Impeller

ZSM 2500 NFPA Fire Pump

2500 gpm (9463 L/M) @ 150 psi (10.3 bar)

2500 gpm (9463 L/M) @ 165 psi (11.3 bar)

1750 gpm (6624 L/M) @ 200 psi (13.8 bar)

1250 gpm (4732 L/M) @ 250 psi (17.2 bar)

Using 1 - 8" or 3 - 6" suction hose

Rated at 2500 gpm for NFPA 1901 fire pump application

ZSM 3000 NFPA Industrial Pump

3000 gpm (11,356 L/M) @ 100 psi (6.9 bar)

2100 gpm (7949 L/M) @ 150 psi (10.3 bar)

1500 gpm (5678 L/M) @ 200 psi (13.8 bar)

Using 2 - 8" or 4 - 6" suction hose

Rated at 3000 gpm for NFPA 1901 fire pump application

ZSM 3000 NFPA Fire Pump

3000 gpm (11,356 L/M) @ 150 psi (10.3 bar)

3000 gpm (11,356 L/M) @ 165 psi (11.4 bar)

2100 gpm (7949 L/M) @ 200 psi (13.8 bar)

1500 gpm (5678 L/M) @ 250 psi (17.2 bar)

Using 2 - 8" or 4 - 6" suction hose

Rated at 3000 gpm for NFPA 1901 fire pump application



darley.com/pumps
800.323.0244