

HE 48K KUBOTA

ENGINE

- Kubota D1803T Diesel: 48 HP, liquid cooled, 12 volt starter, 40 amp. alternator, fuel and oil pump filters

DIMENSIONS & WEIGHT

- 47.3"L x 47.8"W x 24.8"H, 790 lbs. (358.3 kg)

STANDARD FEATURES

- Hard anodized aluminum alloy pump casing and discharge
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction
- Electronic throttle
- Power indicator light
- Digital pressure readout
- Hour meter
- Oil psi
- Tachometer
- Engine coolant temperature
- Volt meter
- Overridable engine shutdowns
- 4" NPT suction
- 3" NPT discharges

PERFORMANCE

- 500 gpm (1892 L/M) @ 75 psi (5.1 bar)
- 400 gpm (1514 L/M) @ 110 psi (7.6 bar)
- 250 gpm (946 L/M) @ 180 psi (12.4 bar)
- 100 gpm (378 L/M) @ 240 psi (16.6 bar)



STANDARD DIGITROL™ PANEL



OPTIONAL SECONDARY PANEL

OPTIONAL INTEGRAL PRESSURE GOVERNOR AND LOSS OF WATER PROTECTION AVAILABLE ON PANELS

