

HE 65K KUBOTA

ENGINE

- Kubota V2403T Diesel: 65 HP, liquid cooled, 12 volt starter, 40 amp. alternator, fuel and oil pump filters

DIMENSIONS & WEIGHT

- 47.4" L x 52.3" W x 27.8" H, 840 lbs. (381 kg)

STANDARD FEATURES

- Hard anodized aluminum alloy pump casing and discharge
- Aluminum alloy gear case and engine adapter
- Bronze impeller and wear rings
- Stainless steel impeller shaft
- Mechanical seal
- Heat treated alloy steel helical gears
- Ball bearing construction
- Electronic throttle
- Power indicator light
- Digital pressure readout
- Hour meter
- Oil psi
- Tachometer
- Engine coolant temperature
- Volt meter
- Overridable engine shutdowns
- 4" NPT suction
- 3" NPT discharge

PERFORMANCE

- 600 gpm (2271 L/M) @ 100 psi (6.9 bar)
- 500 gpm (1893 L/M) @ 130 psi (9 bar)
- 250 gpm (946 L/M) @ 250 psi (17.2 bar)
- 100 gpm (379 L/M) @ 255 psi (17.6 bar)



STANDARD DIGITROL™ PANEL



OPTIONAL SECONDARY PANEL

OPTIONAL INTEGRAL PRESSURE GOVERNOR AND LOSS OF WATER PROTECTION AVAILABLE ON PANELS

