

## HE 18V

LOW PRESSURE, HIGH VOLUME, DIRECT DRIVE, ENGINE MOUNTED



### DIMENSIONS & WEIGHT

- 27"L x 21"W x 25"H, 215 lbs. (98 kg)

### APPLICATIONS

- Booster reel, transfer and supply

### STANDARD FEATURES

#### ASSEMBLY #1

- Aluminum alloy casing
- Bronze impeller and seal ring
- Stainless steel impeller shaft
- Mechanical seal
- Exhaust primer
- Built-in discharge check valve
- 4" NPT suction
- 3" NPT discharge

#### ASSEMBLY #2

- 4" NH suction and screen
- 1-2<sup>1</sup>/<sub>2</sub>" or 2-1<sup>1</sup>/<sub>2</sub>" NPT discharge head with check valve

#### ASSEMBLY #3

- Built-in discharge check valve
- 4" NH suction and screen
- 2-1<sup>1</sup>/<sub>2</sub>" NH discharges, 1/4 turn, ball, self-locking, bronze valves



### OPTIONS

- Adapters, gauge, battery and caps

### PERFORMANCE

520 gpm (1968 L/M) @ 15 psi (1 bar)  
300 gpm (1135 L/M) @ 55 psi (3.7 bar)  
100 gpm (378 L/M) @ 70 psi (4.7 bar)

