

# HF 500

## SINGLE STAGE, CENTRIFUGAL, FRONT MOUNT PUMP



### DIMENSIONS & WEIGHT

- 25" L x 19" W x 25" H, 235 lbs. (107 kg)

### APPLICATIONS

- Mini pumper, tanker, wildland/attack fire

### STANDARD FEATURES

- 2 - 2½" NH, ¼ turn, ball, discharge valves and caps
- 4" NH or 3" NH suction adapter, screen and cap
- 1 - 2½" NPT or 3" NPT suction tap
- 1 - 2½" NPT discharge tap
- Complete mounting kit
- Heavy duty 400 lb-ft electric clutch
- Shock Control Module - prevents engaging clutch at high speeds

### HF IC500

- 4" NH or 3" NH suction adapter, screen and cap
- 1 - 2½" NPT or 3" NPT suction tap
- 1 - 2½" NPT discharge flange
- Complete mounting kit
- Heavy duty 400 lb-ft electric clutch
- Shock Control Module - prevents engaging clutch at high speeds

### PERFORMANCE

#### HF 500

500 gpm (1893 L/M) @ 150 psi (10.3 bar)  
350 gpm (1325 L/M) @ 200 psi (13.8 bar)  
250 gpm (946 L/M) @ 250 psi (17.2 bar)

#### HF - IC 500

500 gpm (1893 L/M) @ 150 psi (10.3 bar)  
350 gpm (1325 L/M) @ 200 psi (13.8 bar)  
250 gpm (946 L/M) @ 250 psi (17.2 bar)

