

# HH 250, 350, 500

SINGLE STAGE, CENTRIFUGAL, HYDRAULIC DRIVEN

## DIMENSIONS & WEIGHT

- 12"L x 19"W x 14"H, 145 lbs. (66 kg)

## APPLICATIONS

- Mini pumper, tanker, wildland/attack fire

## STANDARD FEATURES

### ASSEMBLY #1

- Rotation: Engine or opposite engine
- Gear ratio: 4.38 to 1 or 2.90 to 1
- Heat treated gears are standard
- Tachometer/speed counter output
- SAE "C" adapter
- 12/24-14T involute female spline
- Mounting angles
- 4" NPT suction
- 2½" NPT discharge

### ASSEMBLY #2

- SAE "C" adapter
- 12/24-14T involute female spline
- Mounting angles
- 3 - 4" NPT suction
- 2 - 2½" NPT discharge

### ASSEMBLY #3

- Mounting angles
- 2 - 2½" NH, ¼ turn, ball, valves and caps
- 2 - 3" NH suction adapters and caps
- 3" NPT suction
- 2 - 2½" NPT tapped openings on discharge manifolds
- 2 - 2½" NPT tapped openings on suction
- Body width: 70" - 72"

## PERFORMANCE

### HH 250

250 gpm (946 L/M) @ 150 psi (10.3 bar)  
175 gpm (662 L/M) @ 200 psi (13.8 bar)  
125 gpm (473 L/M) @ 250 psi (17.5 bar)

### HH 500

500 gpm (1893 L/M) @ 150 psi (10.3 bar)  
350 gpm (1325 L/M) @ 200 psi (13.8 bar)  
250 gpm (946 L/M) @ 250 psi (17.2 bar)

### HH 350

350 gpm (1325 L/M) @ 150 psi (10.3 bar)  
245 gpm (927 L/M) @ 200 psi (13.8 bar)  
175 gpm (662 L/M) @ 250 psi (17.2 bar)

