

KSP 500, 750, 1000

SINGLE STAGE, CENTRIFUGAL PUMP, PTO DRIVEN, 2 GEAR GEARCASE

DIMENSIONS & WEIGHT

- 18" L x 14" W x 22" H, 215 lbs. (98 kg)

APPLICATIONS

- Pumper, pumper tanker, tanker, wildland/attack fire

STANDARD FEATURES

- 4" NPT discharge
- 5" or 6" NPT, weld flange
- Rotation: engine or opposite engine
- 1410 lock on yoke
- Mounting angles

OPTIONS

- 3 gear transmission

PERFORMANCE

KSP 500

500 gpm (1893 L/M) @ 150 psi (10.3 bar)

350 gpm (1325 L/M) @ 200 psi (13.8 bar)

250 gpm (946 L/M) @ 250 psi (17.2 bar)

KSP 750

750 gpm (2839 L/M) @ 150 psi (10.3 bar)

525 gpm (1987 L/M) @ 200 psi (13.8 bar)

375 gpm (1419 L/M) @ 250 psi (17.2 bar)

KSP 1000

1000 gpm (3785 L/M) @ 150 psi (10.3 bar)

700 gpm (2646 L/M) @ 200 psi (13.8 bar)

500 gpm (1893 L/M) @ 250 psi (17.2 bar)

