


LDM 1000, 1250, 1500, 1750

SINGLE STAGE, CENTRIFUGAL, MIDSHIP MOUNTED



DIMENSIONS & WEIGHT

- 46" L x 84" W x 44" H, 1,250 lbs. (568 kg)

APPLICATIONS

- Aerial, pumper, pumper tanker, rescue pumper, tanker

STANDARD FEATURES

- Air shift
- Injection packing
- Heat treated gears
- Pressure relief valve
- Mechanical seal
- Oil-less primer
- Vacuum cast impeller
- AutoControl governor
- Overheat protection system
- Discharge check valve
- Manual or electric behind-the-panel butterfly valves
- 4 - 2 1/2" NH, 1/4 turn, ball self-locking valves and caps, mounted
- 2 - 5" or 6" NH suction adapters and caps
- Dual cutwater design to eliminate radial thrust
- 1610 or 1710 full round yokes standard
- 2 1/2" driveline, 12 1/4" driveline drop

OPTIONS

- Mechanical seal, available with MegaTrans™ transmission

PERFORMANCE

LDM 1000

1000 gpm (3785 L/M) @ 150 psi (10.3 bar)
700 gpm (2646 L/M) @ 200 psi (13.8 bar)
500 gpm (1893 L/M) @ 250 psi (17.2 bar)

LDM 1500

1500 gpm (5678 L/M) @ 150 psi (10.3 bar)
1050 gpm (3974 L/M) @ 200 psi (13.8 bar)
750 gpm (2839 L/M) @ 250 psi (17.2 bar)

LDM 1250

1250 gpm (4731 L/M) @ 150 psi (10.3 bar)
875 gpm (3312 L/M) @ 200 psi (13.8 bar)
625 gpm (2365 L/M) @ 250 psi (17.2 bar)

LDM 1750

1750 gpm (6624 L/M) @ 150 psi (10.3 bar)
1225 gpm (4637 L/M) @ 200 psi (13.8 bar)
875 gpm (3312 L/M) @ 250 psi (17.2 bar)

