



HORNET™

LOWER COST, LIGHTWEIGHT, COMPACT, MINI-CAFS

ENGINE



Briggs & Stratton Vangaurd: 23 HP @ 3600 rpm, 4 cycle, air-cooled, gasoline-powered, pressure lubricated, 16 amp alternator, 12 vdc electric start

PUMP

Darley 2BE: 2BE single-stage centrifugal pump

DIMENSIONS & WEIGHT

• 40"W x 24"H x 32"D, 450 lbs. (204 kg)

APPLICATIONS

• Wildland, quick attack, rescue, skid unit

STANDARD FEATURES



- Screw compressor
- FF50 foam system
- 1¹/₂" CAFS discharge
- 1¹/₂" direct tank fill
- 2¹/₂" suction/tank to pump
- Exhaust primer

OPTIONS

- 3" tank to pump valve assembly with 4" front tank connection
- 3" LDH discharge
- 2" water only discharge
- Manual intake butterfly
- Electric intake butterfly

PERFORMANCE

80 gpm (313 L/M) & 40 cfm @ 100 psi (6.9 bar) 250 gpm (946 L/M) @ 40 psi (2.8 bar) - Water only 40 cfm (1133 L/M) @ 125 psi (8.6 bar) - Air only



