

OHLER PUMP

MODEL 4300 SELF CONTAINED DEWATERING SYSTEM

Model 4300 Specifications:

Self contained w/23HP Gasoline Engine

100 feet of Tri-hose

Manual control valves

Positive displacement pump head

Reversible pump head

Up to 200 foot heads



This unit features a 3.75 inch diameter, single stage, hydraulically powered progressive cavity, positive displacement pump for proven process performance under adverse conditions. Manually controlled hydraulics extend, retract and swing the boom side to side allowing easy positioning of pump head and hole guard over the blast hole. Manually controlled level wind provides for smooth hose build up. Manual hydraulic valve permits raising and lowering of pump head with infinite speed control. Hydraulic reverse allows for cleaning of drill cuttings. The pump automatically stops pumping and an indicator light signals when the dewatering cycle is completed. This unit features a 23 HP engine and comes standard with 100 feet of Tri-hose for 80 foot deep blast holes. Optional - 200 feet of Tri-hose and reel for 180 foot deep blast holes.

This unit is self contained and designed for truck or trailer mounting.

OHLER PUMP

501 Maple St.
P.O. Box 386
Janesville, Iowa 50647

Phone: 319-987-2121
Fax: 319-987-2161
Email: ohler@ohler-machinery.com

*WHEN YOU THINK
PUMPS - THINK OHLER*

