

PORPOISE™ FLOATING PUMP

2BEF-BS, HIGH VOLUME, SELF PRIMING



ENGINE

- Briggs & Stratton: 8.75 ft.-lbs., torque, 190 cc, 1.2 qt. fuel tank

PUMP

- High volume, self-priming, floating pump

DIMENSIONS & WEIGHT

- 26.5" L x 21" W x 15.62" H, Under 59 lbs. (27 kg)

STANDARD FEATURES

- Aluminum alloy pump casing
- Bronze impeller
- 3" screened suction inlet
- 2½" NHM outlet

PERFORMANCE

100 gpm (379 L/M) @ 40 psi (2.8 bar)

290 gpm (1098 L/M) @ 6 psi (0.4 bar)

ADDITIONAL DARLEY FLOATING PUMPS

HEF 10.5BS: DOLPHIN™ FLOATING PUMP

- Engine: Briggs & Stratton, 10.5 HP, 2.8 qt. fuel tank
- High volume, self priming
- Anodized aluminum alloy pump casing
- Bronze impeller
- 4" screened suction inlet
- 2½" NH outlet

HEF 10.5BS



HEF 11H: DOLPHIN™ FLOATING PUMP

- Engine: Honda, GVX390, 11 HP, 2.2 qt. fuel tank, OHV
- High volume, self priming
- Anodized aluminum alloy pump casing
- Bronze impeller
- 4" screened suction inlet
- 2½" NH outlet

HEF 11H

