

ZSD 2500 & 3000

SINGLE STAGE, CENTRIFUGAL, SINGLE SUCTION IMPELLER,
DIRECT DRIVE, PTO DRIVEN



DIMENSIONS & WEIGHT

- 23"L x 25.4"W x 29.2"H, 575 lbs. (261 kg)

APPLICATIONS

- Industrial, chemical, aerial, ARFF, fire boat

STANDARD FEATURES

- 6" weld discharge
- 8" NPT or weld suction flange
- Rotation: Engine or opposite engine
- 1550 companion drive flange

OPTIONS

- Suction and discharge heads can be built to suit
- Sweep suction T with 8" Victaulic or 8" NH threaded couplings
- Salt water capable
- Integral belt driven primer capable of drafting within 30 sec.

PERFORMANCE

ZSD 2500 NFPA FIRE PUMP

2500 gpm (9464 L/M) @ 150 psi (10.3 bar)

1750 gpm (6624 L/M) @ 200 psi (13.8 bar)

1250 gpm (4732 L/M) @ 250 psi (17.2 bar)

Using 1 - 8" or 3 - 6" suction hose

Rated at 2500 gpm for NFPA 1901 fire pump application

ZSD 3000 NFPA FIRE PUMP

3000 gpm (11,356 L/M) @ 150 psi (10.3 bar)

2100 gpm (7949 L/M) @ 200 psi (13.8 bar)

1500 gpm (5678 L/M) @ 250 psi (17.2 bar)

Using 2 - 8" or 4 - 6" suction hose

Rated at 3000 gpm for NFPA 1901 fire pump application

