

KSPBC 1000

PTO DRIVEN PUMP WITH 220 CFM CAFS



DIMENSIONS & WEIGHT

- 24.3" L x 24.19" W x 37.06" H, per drawing DKD0414, 704 lbs. (319 kg)

APPLICATIONS

- Aerial
- Pumper
- Wildland/Urban Interface
- Rescue Pumper

STANDARD FEATURES

- 4" NPT discharge flange
- 5" or 6" NPT or weld suction flange
- AutoCAFS Commander Controls
- Electric clutch for 220 cfm compressor package
- Rotation: Engine
- Belt driven compressor package
- 1310/1410 drive flange

OPTIONS

- 3" tank to pump valve assembly with 4" front tank connection
- Electric intake butterfly
- FoamPro 2001 Foam System
- Odin AutoFill™ system for use with hydrants or incoming pressure
- Darley AutoValves

PERFORMANCE

KSPBC 1000

- 1000 gpm (3785 L/M) @ 150 psi (10.3 bar)
- 700 gpm (2646 L/M) @ 200 psi (13.8 bar)
- 500 gpm (1893 L/M) @ 250 psi (17.2 bar)

SIMULTANEOUS WATER PERFORMANCE

- 1000 gpm (3785 L/M) @ 125 psi (8.6 bar)
- NFPA ratings from 500 - 1000

SIMULTANEOUS COMPRESSED AIR PERFORMANCE

- 220 gpm (832 L/M) @ 125 psi (8.6 bar)

