



1-1/2AGE 25H EFI

Portable Gasoline-Powered Pump

Specifications

Dimensions & Weight

- 24"L x 28"W x 23"H
- 145 lbs. (66 kg)

Applications

- Booster reel
- Multiple hand lines
- Wildland/attack fire suppression

Engine

- Honda IGX 800: Electronic fuel injection, electric STR governor, drive-by-wire control, 4 cycle, 25 hp, V-twin, OHV, 6 gal. fuel tank, replaceable oil filter, 38.5 cu. in. displacement, 12 volt starter, 20 amp regulated alternator, hose and adapter

Features

- Electronic fuel injection
- Digital displays
- Aluminum alloy casing and discharge valve
- Discharge valve
- Sulfuric anodized aluminum alloy gear case and engine adapter
- Bronze impeller and wear ring
- Stainless steel impeller shaft
- Mechanical seal
- Built-in discharge check valve
- Adjustable discharge valve
- 2" NPT suction
- 2-1/2" NPT discharge

Options

- Dual remote control panels
- Adapters, gauge, battery and caps



NEW
Features
Electronic
Fuel Injection

High Pressure, Low Volume, Gear Driven, Engine Mounted

- 120 gpm (454 L/M) @ 175 psi (12.1 bar)
- 80 gpm (303 L/M) @ 250 psi (17.2 bar)
- 30 gpm (114 L/M) @ 275 psi (19.0 bar)



Optional Dual Remote Panels



darley.com/pumps
800.323.0244

