



Tactical Pumper™

International CV515 Chassis

Specifications

Chassis

- International CV515
- 4 door 4x4 chassis (199" wheelbase, 84" CA)
- 6.6 L diesel engine rated at 350 hp
- "Shift on the fly" 4-wheel drive
- Automatic transmission
- Seating for four with two SCBA seats (Both rear SCBA seats)
- Battery conditioner with AutoEject™
- Polished aluminum wheels

Fire Pump

- Darley model PSMC midship pump with a UL rating of 1500 gpm at 150 psi
- Gear driven 120 cfm rotary screw air compressor for the AutoCAFS® pumping system with a FoamPro 2001 foam proportioner
- All stainless steel plumbing package
- Maintenance free reliable mechanical seal
- 3 CAFS crosslay discharges (2 - 1½" NSTM and 1 - 2½" NSTM)
- Rear preconnect and/or deck gun (Optional)

Body

- PolyBilt™ copolymer
- Integral 400 gallon water tank (25 gallon foam tank)
- 7 large compartments with roll-up doors
- Enclosed ladder and suction hose storage
- Rear compartment (Can be used for optional 150' booster reel)

Quick
Delivery



Darley's new Tactical Pumper™ is engineered to safely get to the fire quickly and into places that a full-size pumper just can't access.

Please contact Darley for a full set of specifications or to schedule a demonstration.

Features

- NFPA compliant
- Rear receiver hitch with trailer wiring and optional portable winch power leads
- Includes a 2½" Darley AutoFill™ - Once connected to a pressurized source of water, this direct fill feature keeps the water tank between ½ and "FULL" automatically
- Low cost of maintenance
- Ease of driver training - Drivers report having greater confidence when driving this vehicle over larger trucks

darley.com/tactical-vehicles
800.323.0244

