

W.S. Darley & Co.



W.S. Darley & Co.

FIRE APPARATUS SPECIFICATIONS

Darley Ford F550 4x4

Tactical Pumper™ with PSMC 1500 AutoCAFS

for

A Well Prepared FD



Date: January 8, 2025
Sales Rep:

W.S. Darley & Co.

One (1)
00-00-6000

GENERAL INFORMATION

These specifications are a detailed description of the apparatus, and equipment (if specified), to be furnished by W.S. Darley & Co. and is intended to outline the quality and design of the apparatus desired. The apparatus covered by this specification shall be new, unused, and the latest production design and that which is furnished to Fire Departments in general.

This apparatus shall be constructed in its entirety within the continental United States.

One (1)
00-00-9500

THANK YOU

Thank you for the opportunity to present these specifications. Our company looks forward to working with you to provide the best service possible, and the best product possible, as detailed within these specifications.

One (1)
00-01-0700

ADMINISTRATION

One (1)
00-05-1000

PRODUCT QUALITY AND WORKMANSHIP

The components provided and workmanship performed shall be of the highest quality available for this application. Special consideration shall be given to the following areas:

- A). Accessibility to various components that require periodic maintenance or lubrication checks.
- B). Ease of vehicle and pump operation (as applicable).
- C). Features beneficial to the intended operation of the apparatus.

Construction of the complete apparatus shall be designed to carry the loads intended to meet the road and terrain conditions and speed requirements desired when specified by the purchaser.

Welding shall not be employed in the assembly of the apparatus in a manner that will prevent the removal of any major component part for service and/or repair.

One (1)
00-10-0010

SAFETY GUIDE

One (1) copy of the FAMA Fire Apparatus Safety Guide shall be provided. This guide provides safety instructions for operators of fire apparatus.

One (1)
00-10-1025

DOT/NFPA COMPLIANCE

The proposal for fire apparatus conforms with all Federal Department of Transportation (DOT) rules and regulations in affect at the time of bid, and with all National Fire Protection Association (NFPA) guidelines for automotive fire apparatus as published at the time of bid, except as modified by customer

W.S. Darley & Co.

specifications. Any increased costs incurred by Seller because of future changes in, or additions to said DOT or NFPA standards will be passed along to the Buyer as an addition to the price set forth above in the contract. The apparatus is designed to meet the applicable and available recommendations of NFPA 1900 which goes into effect Jan 1, 2024. This was previously known as NFPA 1901 (Fire Pump/Tank) and NFPA 1906 (Storage, equipment and equipment allowance).

One (1)
00-15-0600

PAYMENT REQUIREMENTS

One (1)
00-16-1500

Payment for the value of the chassis shall be made to Darley upon chassis completion and invoicing by Darley.

The balance of the contract shall be paid in full upon completion of the apparatus at the Darley facilities and invoicing by Darley.

A down payment of \$95,000 for the chassis is expected within 30 days of Darley invoicing the Fire Department once the chassis is received at the Darley factory.

One (1)
00-38-0300

DELIVERY REQUIREMENTS

One (1)
00-39-4200

DELIVERY AFTER CONTRACT

The completed apparatus is estimated to be ready for delivery within 12 to 18 months, following the signing of a contract by the purchaser, and the counter-signing of the same contract by Darley.

One (1)
00-39-2200

F.O.B. DARLEY

The completed apparatus shall be picked up by the customer, at the Darley manufacturing facility in Chippewa Falls, Wisconsin.

None (0)
00-45-0750

INSPECTION TRIPS

There are no inspection trips included in the specifications.

INSPECTION TRIP(S) - One inspection trip to Darley is recommended prior to final delivery. No funds are set aside to cover any inspection trip costs and are therefore expected to be the buyer's responsibility.

One (1)
00-50-0600

DRAWING REQUIREMENTS

One (1)
00-50-3000

APPARATUS DRAWINGS

W.S. Darley & Co.

Darley will submit with the specification, a minimum of one (1) set of drawings of the base apparatus as proposed. The drawings shall include left side, right side, top, front and rear views of the apparatus.

Critical dimensions such as overall height, overall length, body width, cab dimensions, pump module dimensions, compartment dimensions, and overall body dimensions are on the base drawings. Water tank size and fire pump flow rate are also to be stated on the drawings. Note: optional equipment added to the base drawings may not be shown on the base drawings. See contract to clarify optional items.

One (1)
00-55-0710

WARRANTY REQUIREMENTS

One (1)
00-55-1410

WARRANTY

The following warranties shall be provided:

One (1)
00-60-2200

ONE YEAR DARLEY APPARATUS WARRANTY

The Darley apparatus herein shall include a warranty against defects in materials and workmanship for a period of twelve (12) months, effective upon pick up or delivery of the apparatus to the destination, as found in the available warranty document.

One (1)
00-60-4700

DARLEY FIRE PUMP WARRANTY

Upon pick up or delivery, for a period of ten (10) years, the Darley Company guarantees to replace any defective part or parts in the Champion pump. This Champion pump is guaranteed to deliver the performance as specified on the certification label.

This warranty does not obligate the Darley Company to bear costs of labor or transportation of repairs or alterations not previously authorized by same.

The Darley Company shall not be responsible, under the terms of this warranty, for the cost of repairs or alterations of any Champion pump.

The Darley Company makes no warranty of trade accessories incorporated in the assembly or employed in conjunction with any Champion pump. Improper use of the pump or excessive overloading of the pump beyond recommended limits of capacity and pressure shall void this warranty.

One (1)
00-60-5500

LIFETIME TANK WARRANTY

The water and foam tanks herein are warrantied, to the original owner of the apparatus, to be free from defects in material and workmanship for the normal service life of the apparatus in which the tanks are installed, per the available warranty document.

One (1)
00-61-7055

COPOLYMER BODY WARRANTY

W.S. Darley & Co.

The Darley Company provides a limited lifetime warranty on its copolymer PolyBilt bodies, to the original owner of the apparatus, the body to be free from defects in material and workmanship, per the available warranty document.

One (1)
00-62-2550

TEN YEAR DARLEY COPOLYMER BODY PAINT WARRANTY

Subject to the provisions, limitations, and conditions set forth, Darley hereby warrants to the original Purchaser, the finish paint on the copolymer body is free of defects and blisters and further warrants that it will maintain such integrity and shall not result in unreasonable gloss or color loss, for a period of ten (10) years following the date the apparatus leaves the Seller facility. Per the available warranty document.

One (1)
00-65-7000

ONE DAY DEMONSTRATION AT PURCHASER

Upon delivery of the completed apparatus, a minimum of one Darley authorized and trained individual shall conduct a one day demonstration session for purchaser personnel. Demonstration shall include all aspects of apparatus operation. The demonstration schedule shall be mutually agreed upon by the purchaser and the manufacturer's representative.

One (1)
00-68-0500

MANUAL AND DATA REQUIREMENTS

One (1)
00-68-4525

FIRE APPARATUS DOCUMENTATION

At the time of delivery, Darley shall supply the following information:

- The manufacturer's record of construction details (MRCD).
- The operations and service documentation/manuals for the pump and body including electrical.

The above will be provided electronically and a SharePoint link will be given for the customer to access their vehicle manuals from anywhere they have internet access.

- Any printed vendor component parts manuals, such as chassis paperwork, will be shipped in the truck

One (1)
00-80-0500

CHASSIS PROVIDER

One (1)
00-80-2000

The chassis, as detailed in these specifications, shall be ordered and supplied by Darley. The chassis portion of the contract shall be paid for as detailed in the Darley proposal and contract verbiage.

One (1)
00-99-2500

MANUFACTURER RIGHTS

The Darley Company reserves the right to incorporate the latest technology or standards, including changes to apparatus features and brand names, or model or equipment being supplied with the vehicle.

One (1)
05-05-1750

W.S. Darley & Co.

CHASSIS SPECIFICATIONS

MODEL

Current (2025) Ford F550 Super Crew 4x4

DIMENSIONS

Wheelbase: 203"

C/A: 84"

GAWR front: 7,500 lbs.

GAWR rear: 14,706 lbs.

GVW total: 19,500 lbs.

ENGINE

6.7L 4V OHV Power Stroke Diesel V8

Stainless steel exhaust

TRANSMISSION

Torqshift 10 speed automatic W/3OD

AXLES

7500 lb. rated front

Disc brakes

Power steering

7,500 lb. front suspension

2-speed transfer case

14,706 lb. rated rear

Disc brakes

14,706 lb. rear suspension

BRAKE SYSTEM

Brake package

Power disc

Four wheel ABS

CHASSIS AND FUEL TANK

Chassis

-Fire/Rescue prep package

-Front tow hooks

Fuel tank

-40 gallon tank rear axle

W.S. Darley & Co.

TIRES AND WHEELS

19.5" Aluminum wheels
225/70RX19.5G BSW Max-Traction tires (four rear - two front)

CAB

AM/FM stereo w/CD/MP3 player with Sync 3, 8" video screen
Chrome steel front bumper
Chrome grille surround
Power door locks
Remote keyless entry
Power windows
Rear camera kit
4X4 Electronic shift on the fly and auto rotary control on instrument panel
Cloth seats - Earth Gray
Driver side manual lumbar support
40/20/40 Front bench seat
4-way adjustable driver and passenger headrests.
Crew bench seat
Air conditioning
Heater/defroster
Air bags
Tinted glass
Powerscope trailer tow mirrors (includes power heated glass, power telescoping, power fold-away, heated spotter mirror and integrated clearance lights and turn signals)

GAUGES AND CONTROLS

Gauge package (volt/tach/trans temp)
Self-canceling turn signals

ELECTRICAL AND LIGHTING

Front Fog Lights
Dual heavy duty alternators
Dual 78 AH 750 CCA batteries
Single electric horn
Halogen headlights
Clearance/Marker lamps
Front turn signals
Windshield wipers w/delay
12 volt/120v power outlets in dash

PAINT

One color finish paint (PQ RED)
Clear coat paint

W.S. Darley & Co.

One (1)
07-00-1000

CHASSIS MODIFICATIONS

The following modifications and installations shall be performed on the chassis upon delivery to the apparatus manufacturer:

One (1)
07-00-1162

TIRE PRESSURE INDICATORS

There shall be LED air pressure sensor caps shipped loose for the customer to install on each tire's valve stem. Each shall be self-calibrating, memorizing pressure when initially installed. Each shall be easily recalibrated by simply removing and reinstalling. The bright LED allows for visual checks in daylight. This active tire pressure monitoring system shall start flashing RED if the tire pressure drops 5 to 10 psi.

One (1)
07-02-8423

CENTER CONSOLE BETWEEN FRONT SEATS

A center control console shall be installed, on the cab floor, between the driver and officer seats.

The top surface of the console shall contain items such as the rocker switch panel and door and accessory ajar lighting. It shall also contain the pump shift controls, electronic siren head, and traffic advisor controls (as applicable).

The top shall either be hinged or have removable sections to allow easy access to components and wiring inside the console.

There shall be a storage area built into the console designed to store Fire Department 3-ring binders, maps, or books. Space shall be approximately 3" to 4" wide and approx. 12" deep.

One (1)
07-06-6200

CREW SECTION SCBA SEATS

The rear seating provided with the chassis shall be replaced with two (2) individual Bostrom 400 CT seats with SCBA seat backs and Secure-All brackets. A seat riser shall be included. Note that each SCBA seat shall have a headrest.

NOTE: Each headrest shall have the Darley logo.
Sample Photo:



One (1)
07-16-8000

REAR HITCH-WINCH RECEIVER ASSEMBLY

A 2" square hitch receiver assembly shall be provided at the rear of the chassis, to allow attachment of a trailer or portable winch. A 12 volt, high amperage circuit with appropriate protected wiring shall be provided, with a receptacle near the receiver. A round 7-wire covered trailer connector, in a bracket, shall be installed near the rear hitch receiver and wired into the vehicle.

W.S. Darley & Co.

One (1)
07-24-1000

AIR HORNS

Two (2) trumpet style air horns shall be mounted under the chassis cab. The air horns shall be connected to a 3-gallon air tank also added underneath the chassis cab. The 3-gallon tank shall be supplied by the onboard 12 volt air compressor being used to power the pneumatic pump shift valve(s). A petcock drain requiring occasional maintenance is to be provided on the bottom of the tank. The 1-gallon air system for the pump shift valve(s) shall be equipped with a pressure protection valve to ensure reliable operation of the fire pump.

One (1)
07-24-9300

AIR HORN CONTROL

A toggle switch shall be provided at the dash area or center console to activate the air horns. A second toggle switch shall be provided at the pump panel as a firefighter evacuation warning. The toggle switch cover(s) shall be red in color for easy identification.

One (1)
07-27-0555

FUEL FILL - AT LEFT REAR WHEELWELL

The chassis fuel fill inlet and vent shall be routed from the fuel tank to a recessed area at the side of the body, near the rear wheel well on the left side of the vehicle. A fuel cap shall be provided. A label designating the type of fuel to be used shall be installed near the fuel fill. No hinged door or cover for this fuel fill is to be provided.

One (1)
07-28-2310

NFPA COMPLIANT TREADPLATE RUNNING BOARDS

A pair of NFPA compliant running boards, with compliant stepping depth and abrasiveness, shall be provided and installed on the chassis. The running boards shall be fabricated from bright aluminum embossed treadplate and shall be supplied and installed below the cab doors.

The running board height, from the ground to the top of the first step shall not exceed 24" from the ground. A bright aluminum diamond plate vertical back splash, from the top of the running board to below the cab shall be provided and installed. The back splash shall be mounted to allow for independent movement of the cab.

One (1)
07-30-1500

MASTER SWITCH - CHASSIS ON/OFF

A master battery cut-off switch shall be provided inside the chassis cab near the driver's seat, accessible from inside the driver's door area in a convenient location. This switch shall cut/supply all 12 volt power to the fire and emergency related body and pumping accessories. This master switch shall include a green colored, LED, master switch "ON" pilot light.

One (1)
07-31-0500

BATTERY CHARGER

A Kussmaul Auto Charge 1000 battery charger, designed for single battery systems, shall be installed in the cab and connected to the chassis batteries. The system automatically becomes inactive when the batteries are fully charged.

W.S. Darley & Co.

A built in battery saver feature shall be included for auxiliary electrical loads such as hand lights and portable radios.

A weatherproof bar graph display shall be included and mounted in a remote location outside the cab.

This onboard battery charger shall be located in the back of the 4-door cab on the floor and shall have a protective cover built around it. It shall be plugged into or powered by a household style outlet/junction box powered by the Auto-Eject mentioned elsewhere in these specifications. This leaves an open 120V port on the outlet for FD to use for in-station charging of equipment.

One (1)
07-31-7700

120V SUPER AUTO-EJECT

A Kussmaul 20 amp, 120 volt Super Auto Eject receptacle with weatherproof cover shall be provided and connected to the onboard charger, specified elsewhere. The receptacle shall be wired so when the vehicle ignition is energized, the receptacle automatically ejects the external plug from the receptacle. The Super Auto Eject shall be a completely sealed assembly to prevent internal contamination. The internal switch arrangement shall eliminate the possibility of arcing at the contacts.

The receptacle shall be located below the driver door area.
A mating plug shall be furnished and shipped loose.

One (1)
07-39-5100

No Customer Radio installation

One (1)
07-52-2200

REAR MUD FLAPS

Two (2) black hard rubber mud flaps shall be installed behind the rear wheels, one each side.

One (1)
07-80-0185

CHASSIS EXHAUST

The chassis exhaust pipe shall discharge at the rear wheels as provided with the chassis.

One (1)
07-90-0750

BACK-UP ALARM (Chassis Provided)

One (1) electronic back up alarm shall be provided with the chassis. See the chassis specifications.

One (1)
07-95-0500

IDENTIFICATION DATA PLATE

An identification plate shall be installed in the driver's area of the cab specifying the quantity and types of fluids used in the vehicle.

--- Engine oil
--- Engine coolant

W.S. Darley & Co.

- Chassis transmission fluid
- Pump transmission lubrication fluid
- Pump primer fluid
- Drive axle lubrication fluid
- Air conditioning refrigerant
- Air conditioning lubrication oil
- Power steering fluid
- Transfer case fluid
- Air compressor system lubricant

The ID plate shall also include the following:

- 1.) Build Date
- 2.) Delivery Date
- 3.) Paint Information
- 4.) VIN Number

One (1)
07-95-2000

OCCUPANT PLATE

An identification plate shall be installed in the driver's area of the cab, specifying the quantity of personnel allowed to ride in the apparatus.

One (1)
07-95-4000

TRAVEL HEIGHT AND GVWR LABEL

A "high visibility" plate shall be permanently mounted in the cab, visible to the driver when seated.

The plate shall show the overall height of the completed apparatus in feet and inches (or meters), the overall length of the completed apparatus in feet and inches (or meters).

The plate shall also show the gross vehicle weight rating (GVWR) in pounds or kilograms.

Text shall also be supplied on the plate, indicating that the information shown is current upon completion of the apparatus. If the overall height of the apparatus changes after the apparatus is put into service, then the purchaser must revise the dimensions on the plate.

W.S. Darley & Co.

One (1)
09-00-0050

PUMP, PUMP MODULE, AND RELATED ITEMS

One (1)
09-03-1000

NFPA COMPLIANT PUMP

The fire pump and related plumbing shall be installed in accordance with applicable NFPA guidelines at the time the contract was placed.

One (1)
17-00-0750

SIDE DESIGN PUMP OPERATOR'S PANEL & MODULE

One (1)
17-02-1000

SIDE PANEL PUMP MODULE

A side operated pump panel shall be provided on the pump module. It shall be assembled and mounted independently from both the chassis and the body, to allow sufficient flexing and prevent component fatigue. The module shall be constructed using square aluminum tubing. The welded ends of the tubing shall be chamfered prior to welding and shall be ground smooth. A heavy duty isolation material shall be provided between dissimilar metals during the mounting process.

One (1)
17-10-3023

SIDE OPERATED PUMP PANEL

The pump operator's control panel shall be located on the left (driver) side of the pump module.

PANELS

The pump panels shall be removable using screws.

TRIM RINGS

All suction and discharge ports shall be fitted with removable trim rings.

GAUGES AND CONTROLS

All controls and gauges shall be functionally grouped and installed to allow easy access for service and replacement. Gauges (and/or flowmeters if present) shall be located as nearly adjacent to the valve control as possible.

One (1)
17-10-3510

TREADPLATE - FRONT OF MODULE

The front of the pump module is to be fitted with aluminum treadplate to enclose the entire front of the pump house framework. It shall be attached with stainless steel sheet metal screws and will be designed to be removable.

One (1)
17-10-5200

SIDE PANELS

The pump compartment module shall have left and right side pump panels constructed of brushed stainless steel sheets. The side pump panels shall be removable.

W.S. Darley & Co.

One (1)
17-30-1500

GAUGE PANEL - STAINLESS STEEL

The pump operator's upper gauge panel shall be located on the left side pump module above the main control panel. It shall be constructed from brushed stainless steel. It shall be vertically hinged and shall have two latches.

One (1)
17-30-2500

ACCESS PANEL - STAINLESS STEEL

There shall be a hinged upper access panel located above the main pump panel on the right side pump module. It shall be constructed from brushed stainless steel. It shall be vertically hinged and shall have two latches.

One (1)
17-35-3000

COLOR CODED LABELS WITH BEZELS

A set of color coded and function described labels shall be provided on the apparatus for the pump operator's controls, gated inlets, discharge outlets, drains, and pressure gauges (as applicable). The labels shall be a high quality plastic material mounted in an adhesive backed chrome plated bezel, attached to the vehicle using stainless steel fasteners.

One (1)
17-32-1010

PUMP PANEL LIGHT SHIELD (LED) LEFT

One (1) mirror finish, stainless steel, light shield assembly shall be provided above the left side pump panel area. There shall be LED lights installed within the shield. A switch located on the pump operator's panel shall be provided to activate the lights.

One (1)
17-32-2010

PUMP PANEL LIGHT SHIELD (LED) RIGHT

One (1) mirror finish, stainless steel, light shield assembly shall be provided above the right side pump panel area. There shall be LED lights installed within the shield. A switch located on the pump operator's panel shall be provided to activate the lights.

Two (2)
17-32-2210

PUMP COMPARTMENT LIGHTS (LED)

Two (2) LED lights shall be provided inside the pump compartment area. Each shall be controlled with a switch mounted next to each light.

One (1)
17-32-3000

RUNNING BOARDS

Running boards shall be installed on each side of the pump compartment module. The running boards shall be constructed of 1/8" embossed bright aluminum tread plate. Each shall be a minimum of approximately 11" deep x the length of the module. The running boards shall have a 1.25" upward bend on the inside edge to act as a kick plate. The aluminum tread plate shall meet recommendations for slip resistant surfaces at the time of proposal.

W.S. Darley & Co.

The running boards shall be attached to a frame mounted outrigger support structure. Each running board to have a 3" downward bend on the front and side faces with a 1" underside return for superior strength.

One (1)
17-32-4100

GRIP INSERTS IN RUNNING BOARDS

Two (2) extruded aluminum inserts, each with an open grated grip type surface, shall be installed, one each side, in the pump module running boards. The inserts shall occupy nearly the entire running board surface area.

One (1)
10-43-0515

SINGLE STAGE FIRE PUMP (CAFS)

The pump shall be a Darley PSMC single stage fire pump, capable of 1500 GPM rating.

The pump casing shall be a fine grain cast iron alloy, vertically split, with a minimum 40,000 psi tensile strength and bronze fitted.

The pump shall contain a cored heating jacket feature that, if selected, can be connected into the vehicle antifreeze system to protect the pump from freezing in cold climates as well as cooling the vehicle chassis engine.

The impeller shall be a high strength bronze alloy of a radial flow design for high suction lift capacity, accurately balanced and splined to the pump shaft for precision fit and durability.

The pump shaft shall be precision ground stainless steel with long wearing, very hard, chrome oxide coating. The shaft shall be splined to receive broached impeller hubs, for greater resistance to wear, torsional vibration, and torque imposed by engine. Shaft seal comes standard with face-type, self-adjusting corrosion and wear-resistant mechanical seals.

The bearings provided shall be heavy duty, deep groove, and radial type ball bearings. They shall be oversized for extended life. The bearings shall be protected at all openings from road dirt and water splash with oil seals and water slingers.

The transmission case shall be heavy duty cast iron alloy with adequate oil reserve capacity for low operating temperatures. A magnetic drain plug shall be provided. Transmission case shall include a dip stick for checking oil level. The transmission shall be cooled with patented "AutoCool" cooler plate. Due to potential damage from freezing, designs which send water into the transmission are prohibited.

The pump drive shaft shall be precision ground, heat treated alloy steel, with a minimum 2.50 inch by 10.00 inch spline ends. Gears shall be helical design, and shall be precision cut for quiet operation and extended life. The gears shall be cut from high strength alloy steel, heat treated, precision ground and carburized.

The gear shift shall be a heat treated alloy steel splined spur gear to engage either the pump drive gear or the truck drive shaft gear. The gear teeth shall be bullet nosed to minimize potential for a butt-tooth condition. The gear ratio of the pump shall be selected by the pump and apparatus manufacturer's Engineering Department.

W.S. Darley & Co.

Due to the advantages of the above gear and drive feature, chain drive and designs requiring additional lubrication are not acceptable.

A discharge manifold, as supplied as part of the pump by the pump manufacturer, shall include a discharge head check valve assembly to allow priming of the pump from draft with discharges open and caps off, and to prime faster than designs that require the air to be evacuated from the discharge manifolding.

Discharge outlets shall have extensions with companion flange openings to allow ease of service.

CAFS COMPATIBLE

The pump transmission shall be designed to accommodate an integrated continuous duty, rotary screw air compressor for CAFS.

One (1)
10-47-1200

DARLEY MECHANICAL SEAL

The fire pump shall be furnished with a Darley maintenance free mechanical seal; manufactured using the material silicon carbide (no exceptions). The mechanical seal shall be a non-contacting, non-wearing dual seal design. The lip seal shall eliminate leakage on a wet pump while parked on standby. The second seal shall allow a drip rate for cooling and lubrication while pumping.

One (1)
10-90-1500

U.L. CERTIFICATION - 1500 GPM

The fire pump shall meet and perform the following tests to receive a U.L. Certification.

100% of rated capacity at 150 PSI net pump pressure
100% of rated capacity at 165 PSI net pump pressure
70% of rated capacity at 200 PSI net pump pressure
50% of rated capacity at 250 PSI net pump pressure

One (1)
11-00-2000

PUMP SHIFT

One (1) air powered pump shift shall be installed in the cab. The shift shall engage the fire pump. The apparatus pump shift shall be engaged only when apparatus is in a stationary position and the parking brake is engaged. The following indicator lights shall be included with pump shift.

A green indicator light labeled "**PUMP ENGAGED**" shall indicate pump shift has successfully been completed.

A green indicator light labeled "**OK TO PUMP**", shall indicate the chassis transmission is in pump gear and parking brake is engaged.

One (1)
11-00-4100

AIR SYSTEM PACKAGE

A compressed air package shall be installed on the chassis to provide compressed air for the pump shift and other pneumatic accessories. This package shall include a 12 volt DC powered piston type air

W.S. Darley & Co.

compressor rated at no less than 1.0 CFM at 125 PSI. It shall be mounted up high in the front body compartment to take up as little compartment space as possible. A pressure switch shall be installed to keep the system pressure maintained between 90 and 120 PSI. A 1 gallon corrosion resistant air reservoir shall be installed under the driver's side rear cab area outside the frame rail and shall include a pressure protection valve as well as a manual petcock drain.

One (1)
10-44-3000

PUMP ANODES

The pump shall be supplied with two (2) anodes for corrosion protection. The anodes shall be mounted at a 3/4" tap location on the pump manifolds. One (1) anode shall be mounted on the suction side of the pump and one (1) anode on the discharge side of the pump.

One (1)
10-48-5700

TRANSMISSION LOCK-UP DEVICE

The automatic chassis transmission shall be delivered to the body builder with high gear lock up device installed on the automatic transmission, to allow proper gear ratio for pump operation. The transmission shall be programmed by the chassis manufacturer to include this feature.

One (1)
10-49-0550

DRIVELINE MODIFICATION

The chassis driveline shall be modified to accommodate any changes required by the installation of the fire pump.

One (1)
11-00-5000

CAFS AIR COMPRESSOR SHIFT

An air powered (CAFS) air compressor shift shall be installed to engage the air compressor complete with a single green colored "ENGAGED" indicator light. The air compressor shift shall include an interlock system, installed to eliminate the possibility of improperly shifting the compressor while the water pump is rotating. The compressor can be engaged only when the water pump is disengaged and the apparatus is in a stationary position. NO EXCEPTIONS

One (1)
11-01-2000

ELECTRIC PRIMER (FLUIDLESS)

One (1) 12 volt positive displacement type rotary vane primer of a fluidless design shall be provided for the fire pump priming system. A single, push-pull control shall be located on the pump operator's panel with a "Pull to Prime - Push To Close" label. The primer shall not require a lubrication tank. The priming pump shall be constructed of heat treated aluminum and hard coat anodized.

One (1)
11-01-2800

The pump priming system shall include a light to indicate when the pump priming system has been activated. The light shall be red in color and shall be labeled "WARNING - Primer Engaged".

One (1)
17-64-5200

PRESSURE GOVERNOR

W.S. Darley & Co.

A Darley "**AUTO CONTROL**" electronic pressure governor and engine monitoring system shall be installed on the pump operator's control panel. The governor shall be configured to operate with the chassis engine. It shall regulate engine RPM to maintain a consistent pressure out of the water pump over a wide range of outgoing flows. The unit shall operate in both RPM and PSI modes. The 6" tall x 7-1/2" wide control unit shall include the following features:

DISPLAY:

- A 4-digit LED readout for pump discharge pressure.
- A 4-digit LED readout for pump intake pressure.
- A 20 segment LED bar graph for the pressure or RPM setting.
- A 4-digit readout for engine RPMs.
- Four (4), 10 segment bar graphs for engine oil pressure, engine temperature, transmission temperature, and battery voltage. The bar graph display shall flash if low voltage, low oil pressure, high transmission temperature, or high engine temperature condition occurs.
- "Throttle Ready" green LED. It shall indicate that the pump is engaged in the proper stationary pumping position, and that the parking brake is set.

FUNCTION SWITCHES:

Idle Mode - Preset - Increase - Decrease - Silence.
This system shall utilize information from the chassis engine ECU.
An audible alarm buzzer shall be included.

One (1)
11-02-4000

INTAKE RELIEF VALVE(S)

One (1) bronze, Elkhart intake relief valve(s) shall be provided and mounted on the suction side of the pump, adjustable from 50-250 psi, on the valve itself. Each valve specified shall be factory preset at approximately 125 psi. The system does not include an on/off control.

One (1)
11-04-1005

HEAT EXCHANGER & HEATED PUMP CORE

An automatic heat exchanger system shall be provided in the pump. Antifreeze from the vehicle engine shall flow through the pump core jacket. Water flow from the fire pump shall be used to cool the engine antifreeze. This feature shall assist against the pump freezing in cold climates.

One (1)
11-11-1000

MASTER DRAIN

One (1) rotary style master drain shall be installed with the control installed on the lower portion of the side control panel. It shall be of brass construction and use a rotary screw mechanism against a rubber sealing surface. Each port shall be isolated. The drain valve shall be mounted as low as necessary to drain the lowest ports on the pump, but as high as possible to provide as much ground clearance as possible under the pump. An "open and closed" label with arrows indicating direction shall be installed on the drain valve control.

One (1)
11-11-5100

1/4 TURN DRAINS - LIFT TO OPEN

Each gated 1.5" or larger inlet and discharge shall have a quarter turn drain valve installed. The drain valves shall be located along the bottom on each pump panel and are operated by lifting the handle to

W.S. Darley & Co.

open the drain/bleeder. Inlets & discharges shall be plumbed to each drain at the lowest point. Each drain/bleeder shall be plumbed with low pressure hose to drain below the module and be directed away from the pump operator. Each drain valve shall have a long handled control lever with a color coded function label installed near the respective drain control.

One (1)
12-01-4000

SUCTION INLETS

One (1)
12-03-7800

6" LEFT SIDE INLET WITH BUTTERFLY

One (1) 6" suction steamer inlet with male NH threads shall be provided, on the left side pump panel. The inlet shall have a removable screen. The inlet shall have a 6" butterfly valve with an automatic relief and electric control installed in the side suction sleeve casting, completely behind the panel.

A switch with indicator lights shall be mounted on the operator's control panel. The relief valve shall be mounted on the intake side of butterfly valve and factory preset to 185 psi with a maximum pressure of 300 psi. The valve shall relieve excess pressure to atmosphere.

A green "open" indicator light and a red "closed" indicator light shall be provided.

There shall be no exception to the above requirements.

One (1)
12-04-2000

INLET CAP

The inlet shall have a polished chrome cap, engraved with the pump manufacturer's logo and name. The logo and name shall be painted with a high quality urethane paint.

One (1)
12-03-8600

6" RIGHT SIDE INLET

One (1) 6" suction steamer inlet with male NH threads shall be provided, on the right side pump panel. The inlet shall have a removable screen.

One (1)
12-04-2000

INLET CAP

The inlet shall have a polished chrome cap, engraved with the pump manufacturer's logo and name. The logo and name shall be painted with a high quality urethane paint.

One (1)
11-10-2000

PLUMBING SYSTEM (STAINLESS/BRASS)

All auxiliary suction and discharge plumbing related fittings, waterways, and manifolds shall be fabricated with stainless steel pipe, brass or high pressure hose with stainless steel couplings. Galvanized components and/or iron pipe components are not acceptable.

Upon completion, the entire system shall be fully pressure tested.

The plumbing and valve arrangement shall be capable of delivering water to the pump at a minimum flow rate of 500 GPM while pumping at 150 psi pressure.

W.S. Darley & Co.

Each gated intake shall be equipped with a 3/4 inch bleeder valve located in close proximity to the intake. All intakes shall be provided with suitable closures (valves or caps) capable of withstanding 500 PSI.

When any 3" or larger intake or discharge is gated (except tank to pump valve), the valve shall have a mechanism to allow the valve to fully open or fully close no faster than 3 seconds.

Any 2.5" or larger discharge outlet, mounted 42" or higher from ground, which hose is to be connected, and which is not in a hose storage area, shall be supplied with a sweep elbow of at least 30 degrees.

All 1.5" and larger intakes and discharges shall be equipped with drains. All drain valves shall be operational without the operator having to get under the plumbing area. All drains shall be detailed elsewhere in these specifications.

All discharges and intakes shall terminate with chrome NST adapters, with chrome caps and chains, unless detailed otherwise in these specifications.

One (1)
12-07-1000

2.5" SUCTION(S) - LEFT SIDE (Darley)

One (1) 2.5" brass suction valve(s) shall be installed on the left pump panel with the valve body mounted behind the pump panel. The control handle(s) shall be the quarter turn ball type, of the fixed pivot design, and located alongside the suction valve.

The suction(s) shall terminate with a 2.5" female NST chrome inlet swivel, a chrome male plug, chain, and a brass inlet strainer.

The valve(s) shall be Darley brand with a polished stainless steel ball.

One (1)
12-18-0500

TANK TO PUMP LINE (MANUAL)

One (1) 3" tank to pump line shall be provided for connection between the water tank and the fire pump. The valve shall be a 3" bronze, quarter turn ball type. The line shall terminate 4", for water tanks 500 gallons and more; and shall terminate 3", for water tanks under 500 gallons. The valve shall be manually controlled from the pump operator's panel.

One (1)
12-19-3000

CHECK VALVE

One (1) 3" swing type check valve shall be provided inline of the 3" water tank to pump line.

One (1)
13-01-2000

2" TANK FILL

One (1) 2" pump to tank fill shall be provided with a 2" inline bronze valve. The valve shall be manually controlled and properly labeled at the pump operator's panel.

One (1)
14-03-2500

AUTOCAFS - COMPRESSED AIR FOAM SYSTEM

W.S. Darley & Co.

There shall be provided, a high energy, automatic compressed air foam system (AutoCAFS). The system shall be designed to meet all applicable NFPA requirements. It shall be sized to provide at least 240 gallons per minute water flow and 120 cubic feet per minute air flow at 125 PSI.

The air compressor shall be a high quality, industrial rated, modulating, continuous duty, rotary screw design. The air compressor shall be mechanically gear driven by the main pump split shaft transfer case and shall be so designed as to provide optimum performance at 70% of rated engine RPM.

The air compressor gear train shall provide a means to engage and disengage air compressor as required.

The air compressor system shall include a pressurized oil lubrication system, oil separator, oil filter, inlet air filter, and modulating inlet air control. The air compressor shall be provided with an automatic air pressure control valve located in the pump house to automatically balance air to water pressure for CAFS use. The air compressor system shall also have mounted on the panel a compressor engaged light and an oil temperature gauge with high temp alarm. Gauges and controls shall be positioned and clearly marked to provide simple and easy operation.

Each of the components of this Automatic Compressed Air Foam System - (air compressor, drive system, foam proportioner, control and instrumentation system) shall be sized, driven and controlled to produce a well operating and reliable CAFS unit.

This automatic compressed air foam system (AutoCAFS) shall be completely installed and tested before delivery by the factory.

FOAM OUTLETS

The compressed air foam system shall be plumbed to provide both foam solution and compressed air to the specified discharges. Detailed descriptions of these discharges shall be provided elsewhere in these specifications.

One (1)
11-00-5000

CAFS AIR COMPRESSOR SHIFT

An air powered (CAFS) air compressor shift shall be installed to engage the air compressor complete with a single green colored "ENGAGED" indicator light. The air compressor shift shall include an interlock system, installed to eliminate the possibility of improperly shifting the compressor while the water pump is rotating. The compressor can be engaged only when the water pump is disengaged, and the apparatus is in a stationary position. NO EXCEPTIONS

One (1)
14-10-3500

CAFS AIR PRESSURE GAUGE

The compressed air foam system shall utilize an air pressure gauge. It shall be installed on the operator control panel. This CAFS gauge shall be installed by the CAFS pumping system manufacturer.

One (1)
14-12-1000

AIR OUTLET 1/4" CAFS SUPPLY

W.S. Darley & Co.

There shall be a brass 1/4" female air hose quick disconnect fitting mounted on the right side pump panel. The fitting shall be connected to the CAFS air compressor. There shall be an adjustable regulator installed to provide compressed air to the side panel. A male quick disconnect fitting shall also be supplied.

One (1)
14-20-2000

FOAM PROPORTIONER (2001 System)

A FoamPro 2001 Class A automatic, electronic, direct injection, foam proportioning system shall be installed on the discharge side of the pump. It shall provide foam to predetermined foam discharge(s). This foam system is completely automatic and requires only one push button to turn it on before the system is functioning.

The system shall incorporate a paddle wheel flow meter to measure the water flow and based on the foam percentage selected at the controller the direct injection pump shall inject the proper amount of foam into the foam discharge(s).

The system is capable of providing precise foam solution concentration rates from 0.1% to 3% and is operator adjustable with the push button digital display control.

System Capacity - Foam Pump is capable of 2.5 gpm of foam output @ 150 psi. Pump motor is 1/2 HP 12 volt.

The system shall include an "auto on" feature.

Foam Concentration.....Water Flow Range

0.1%.....	20-2600 gpm
0.2%.....	20-1300 gpm
0.3%.....	20-833 gpm
0.5%.....	20-520 gpm
1.0%.....	20-260 gpm
3.0%.....	20-85 gpm

A check valve shall be installed between the flowmeter and the injection fitting to avoid foam contamination back into the rest of the pump.

System Features: Four (4) selectable modes for operator information:

- 1) Flow mode: Displays the total amount of water being flowed out of the foam discharge(s). Foam system need not be enabled to function in this mode.
- 2) Total Water mode: When selected shows the total amount of water flowed out of the foam discharge(s) since the unit was in operation.
- 3) Foam Percentage % mode: When selected shows the percentage rate that foam is being injected at if the system was turned on. This percentage can be changed by pressing the up or down arrow buttons at the bottom of the display.

W.S. Darley & Co.

4) Total Foam mode: When selected shows the total amount of foam that has been injected since the unit was turned on.

The system shall be provided with a low foam tank level switch which shall alert the operator of low foam concentrate level and shall automatically shut unit off after two minutes.

Foam system flushing is achieved by simply turning off the unit and flowing water out of the discharge(s) that were previously flowing foam solution.

The system shall be completely installed inside the pump compartment, with digital control unit and instruction plate mounted on the pump operator's control panel. An installation and operation manual shall be included with the system. The system shall be installed by a certified FoamPro dealer only and shall be fully calibrated and tested for proper operation prior to delivery.

One (1)
14-21-1250

DARLEY FOAM TANK REFILL

A Darley 12 volt power foam tank fill system DFRS001-KIT shall be installed to eliminate the need to climb up onto the hosebed to fill the foam tank through the fill tower. The system shall operate completely while standing on the ground. The system shall operate by attaching a suction hose to a pre-plumbed panel connection using a stainless steel cam-lock fitting. The pick-up wand shall then be placed in the foam concentrate container. The operator then lifts a toggle switch to activate the 12 volt pumping system, which manually fills and stops only when the switch is released. When the "on board" foam tank is full, a green light will illuminate. All components are designed to be used with Class A foam and therefore require no flushing.

System includes:

- High-capacity concentrate pump
- Continuous-duty 12-volt motor
- "Tank Full" Indicator light
- Panel plate
- Stainless fittings and cap
- 1" concentrate pick-up wand
- Check valves
- 6' of one inch hard suction hose with wand

One (1)
14-21-1295

POWERFILL CONTROL

The Foam Tank refill inlet and control shall be at the right side pump module.

One (1)
14-21-5000

SECONDARY FOAM PICKUP HOSE

This unit will be provided with a secondary foam pickup tube. This alternate source to the foam proportioner will be provided with a manual 3/4" three way valve to disconnect foam flow from the tank and allow foam to be drawn from a pail or other source through a 3/4" inside diameter hose approximately four foot long. This hose will be provided near the pump panel on the side of the truck and is intended to work best with the pail of foam setting on the running board.

One (1)

W.S. Darley & Co.

15-18-5992

RIGHT SIDE CONTROLS

The right side discharges shall be controlled from the left side module pump operator's panel, and also from the right side module, as a Darley standard.

One (1)
15-20-0400

2.5" LEFT SIDE DISCHARGES (Darley)

Two (2) 2.5" discharge outlets with 2.5" pipe and valve with NST threads shall be supplied at the left side panel. Each valve shall be a quarter turn ball type, self-locking, fixed pivot design and shall be operated with a lever control from the pump operator's panel.

Each valve shall be Darley bronze valve with a high polished stainless steel ball.

One (1)
15-50-6150

Each valve shall have a chrome 30 degree elbow, with a chrome cap and a stainless steel retaining chain. Each cap shall be a vented rocker lug chrome plated brass cap, as per NFPA.

One (1)
17-42-3555

PRESSURE GAUGES

Two (2) 2.5" liquid filled gauges, each with a stainless steel bezel shall be provided for the discharges. Each gauge shall be located on the pump operator's panel near the respective discharge control.

Each gauge shall be a back lit 2.5" glycerin filled pressure gauge with the following features:

- | | |
|--|--|
| ---Glycerin filled | ---LED lighted |
| ---Full 2.5" dial for easy readability | ---Freeze and clog proof |
| ---Case material: Zytel nylon | ---Bezel material: chrome plated nylon |
| ---Pointer: Aluminum | ---Made in the USA |

One (1)
15-30-0300

2.5" RIGHT SIDE DISCHARGE (Darley)

One (1) 2.5" discharge outlet with 2.5" pipe and valve and NST threads shall be supplied at the right side panel. The valve shall be a quarter turn ball type, self-locking, fixed pivot design and shall be operated with a lever control from the operator's panel.

The valve shall be Darley bronze valve with a high polished stainless steel ball.

One (1)
15-50-6100

The valve shall have a chrome 30 degree elbow, with a chrome cap and a stainless steel retaining chain. The cap shall be a vented rocker lug chrome plated brass cap, as per NFPA.

One (1)
17-42-3500

PRESSURE GAUGE

A 2.5" liquid filled gauge with a stainless steel bezel shall be provided for the discharge. The gauge shall be located on the pump operator's panel near the discharge control.

W.S. Darley & Co.

The gauge shall be a back lit 2.5" glycerin filled pressure gauge with the following features:

- Glycerin filled
- Full 2.5" dial for easy readability
- Case material: Zytel nylon
- Pointer: Aluminum
- LED lighted
- Freeze and clog proof
- Bezel material: chrome plated nylon
- Made in the USA

One (1)
15-30-3000

3" RIGHT SIDE DISCHARGE

One (1) 3" discharge outlet with 3" pipe and valve and NST threads shall be supplied at the right side panel. The valve shall be a bronze valve. The valve shall be a quarter turn ball type, self-locking, fixed pivot design and shall be operated with a manual control from the operator's panel.

One (1)
15-50-6750

STORZ ADAPTER

The discharge shall have a 3" NSTF x 4" Storz 30 degree elbow with cap and retaining cable.

One (1)
17-42-3500

PRESSURE GAUGE

A 2.5" liquid filled gauge with a stainless steel bezel shall be provided for the discharge. The gauge shall be located on the pump operator's panel near the discharge control.

The gauge shall be a back lit 2.5" glycerin filled pressure gauge with the following features:

- Glycerin filled
- Full 2.5" dial for easy readability
- Case material: Zytel nylon
- Pointer: Aluminum
- LED lighted
- Freeze and clog proof
- Bezel material: chrome plated nylon
- Made in the USA

One (1)
15-68-2865

THREE CROSSLAYS 2 x 1.5" & 1 x 2.5" (CAFS)

Two (2) crosslays for storage of 1-3/4" hose shall be installed above the pump. Each crosslay shall have capacity for 200 ft. of 1.75" double jacket fire hose. The crosslays shall each have 2" plumbing and 2" self-locking valve and terminate with a 1.5" NSTM chicksan type swivel up through the center of the crosslay flooring. The swivels shall allow hose deployment out either side of the crosslay.

One (1) 2.5" crosslay shall also be installed above the pump. The crosslay shall have capacity for 200 ft. of 2.5" double jacket fire hose. The crosslay shall have 2.5" plumbing and a 2.5" self-locking valve and terminate with a 2.5" NSTM chicksan type swivel up through the center of the crosslay flooring. The swivel shall allow hose out of either side of the crosslay.

The outside edges of each side opening shall be trimmed with polished stainless steel. A manual valve control shall be furnished at the pump operator's panel for each.

CAFS/FOAM CAPABLE

W.S. Darley & Co.

Each crosslay shall be piped, including the required check valves, CAFS air injection switch, and 1/4 turn, adjustable air flow control valves to provide water, foam solution, plain air, or compressed air foam.

One (1)
15-69-3610

HOSE STRAPS

Three (3) Fire Research JackStraps shall be provided; designed to attach hose ends to the apparatus, to help prevent fire hose from inadvertently coming off the apparatus while responding to or returning from an incident.

The JackStraps shall be made of heavy duty 2-inch wide polypropylene webbing. An adjustable hose loop shall fit on supply and working hose from 1.5 to 5 inches. A separate shoulder loop shall help the firefighter when pulling a supply line or help support a working hand line. When used on a hydrant line, the shoulder loop shall be capable of firmly holding hose to the hydrant during a hose stretch. There shall be a side pocket on the shoulder loop to hold a hydrant tool.

One (1)
17-42-3560

PRESSURE GAUGES

Three (3) 2.5" liquid filled gauges, each with a stainless steel bezel shall be provided for the discharges. Each gauge shall be located on the pump operator's panel near the respective discharge control.

Each gauge shall be a back lit 2.5" glycerin filled pressure gauge with the following features:

- Glycerin filled
- Full 2.5" dial for easy readability
- Case material: Zytel nylon
- Pointer: Aluminum
- LED lighted
- Freeze and clog proof
- Bezel material: chrome plated nylon
- Made in the USA

One (1)
15-69-3000

ALUMINUM CROSSLAY COVER

There shall be an aluminum cover for the crosslay(s). The cover shall be constructed of a minimum of 1/8" aluminum tread plate and be hinged with a stainless steel knuckle hinge. The cover shall be hinged to open toward the chassis cab. The cover shall have a hold down system that shall hold the cover down. A rubber type bumper shall be used to protect the cab paint from the cover.

One (1)
17-34-1250

DUNNAGE AREA

A recessed, removable dunnage (storage) compartment shall be provided above the pump compartment and shall be full width of the pump compartment. The compartment shall be smooth aluminum material. The ends shall be left open with hinged doors on each side of the pump house.

One (1)
17-35-1000

PUMP PANEL ID PLATE

An identification plate, prepared by the fire pump manufacturer, shall be installed on the pump operator control panel to identify the fire pump serial number, model number, and performance.

One (1)
17-35-1200

W.S. Darley & Co.

WARNING - PUMP OPERATOR

A sign shall be provided on the pump operator's panel that states the following:

"WARNING - SERIOUS INJURY OR DEATH COULD OCCUR IF INLET(S) ARE SUPPLIED BY A PRESSURIZED SOURCE WHEN THE VALVE IS CLOSED". "SEE PUMP MANUAL FOR COMPLETE OPERATION INSTRUCTIONS".

One (1)
17-41-7010

WATER LEVEL GAUGE

One (1) Fire Research "**Tank Vision**" water tank level gauge shall be installed on the pump operator's panel. The gauge shall have an LED display, which flashes when the tank level reaches 25% of capacity. A built-in calibration system shall allow a bottom tank mounted transducer to be mounted with any tank configuration.

One (1)
17-41-7200

FOAM LEVEL GAUGE

One (1) Fire Research "**Tank Vision**" foam tank level gauge shall be installed on the pump operator's panel. The gauge shall have an LED display which flashes when the tank level reaches 25% of capacity. A calibration system shall allow the tank bottom transducer to be calibrated to work with most any tank configuration.

One (1)
17-80-4010

PUMP MODULE HANDRAILS

There shall be a handrail installed on each upper corner of the pump module. The handrails are to assist in climbing up onto the top of the module or to access the hosebed area. Each shall be 1-1/4" aluminum extrusion, approximately 16" long, with rubber inserts, mounted in chrome plated stanchions. Rubber gaskets shall be placed between the handrail stanchions and the module surface, if needed.

--The handrails shall be located on the upper side of the left and right sides of the pump module.

W.S. Darley & Co.

One (1)
19-00-5100

WATER TANK, FIRE BODY & RELATED COMPONENTS

BODY CONSTRUCTION

The body and water tank shall be fabricated using special high strength copolymer materials; providing a durable, impact resistant, corrosion resistant, and lightweight design.

One (1)
19-01-0425

INTEGRAL BODY/TANK CONSTRUCTION

The water tank shall be integral with the body. The body and water tank shall be fabricated using the same special high strength copolymer materials; providing a durable, impact resistant, corrosion resistant, and lightweight design. Due to the added strength and durability provided with this integral design, there shall be NO EXCEPTION to this requirement.

One (1)
31-03-0100

COPOLYMER BODY CONSTRUCTION

The body shall be fabricated using special high strength, copolymer sheet materials, providing a durable, impact resistant, corrosion resistant, and lightweight body. The body shall be fabricated using Aristech TI-4007-L polymer (or equal) extruded sheets. All seams shall be fully welded. All outside corners on the body shall have a minimum 1/2" radius. The entire body shall be a welded assembly; assembled and painted prior to mounting on the sub frame and the chassis.

Due to the importance of the strength and impact resistance of the copolymer material, there shall be no exception to these requirements.

Only builders who can show examples of previously constructed copolymer bodies shall be accepted.

One (1)
31-19-0500

REAR TOW EYES

Two (2) heavy duty laser cut steel tow eyes, 1/2" thick with a 1.5" I.D. cutout, shall each be bolted to the rear chassis frame rails with 3/4" grade 8 bolts. The tow eyes shall extend through the rear panel. The tow eyes shall be black.

One (1)
31-24-3050

COMPARTMENT CONSTRUCTION

The compartments, including the floors, shall be constructed of the same heavy duty smooth copolymer material as used for the body. All seams shall be completely welded. Divider walls between compartments shall be single wall construction with a minimum wall thickness of 3/8". Compartment floors shall be a minimum of 1-1/8" thick and shall have a minimum of a 3/4" lip above bottom of the door opening, providing a sweep out design. All compartment door opening lips shall be protected with polished stainless steel trim. For adequate ventilation and air displacement, each compartment shall be properly louvered with square black heavy plastic vents. The forward wall of the front compartments, and rearmost wall of the rear compartments, shall have removable panels, constructed from the same body

W.S. Darley & Co.

material, to cover and protect all 12 volt electrical accessories mounted on the walls. The panels shall be removable to provide access to those components. Compartment interiors shall be provided in a natural unpainted finish.

One (1)
31-30-1000

FENDER PANELS

Side fender panels above the rear wheels shall be heavy duty smooth copolymer material. Each shall be painted the same color as the exterior body.

FENDER LINERS

Copolymer fender liners shall be welded into the wheel well area, above the rear wheels. Adequate clearance shall be provided for the installation of single tire chains. The inner liners shall be textured black copolymer material.

One (1)
31-40-1050

HOSE BED CONSTRUCTION

The hose bed walls shall be of the same copolymer material as the body, reinforced at the corners. The upper, outer edges shall have a solid tube type design for strength and stiffness. The hose bed shall be free from all projections, which may interfere with the unloading of hose.

One (1)
31-41-1155

HOSE BED CAPACITY

The hose bed shall have the recommended minimum cubic foot of usable capacity for a hose load.

One (1)
31-42-0750

HOSE BED FLOORING

A hose bed floor shall be provided and constructed of textured black copolymer slat style material. The slats shall be properly spaced to allow passage of air between the hose and the booster tank.

Two (2)
31-43-1500

HOSE BED DIVIDER(S)

Two (2) adjustable polymer hose bed divider(s) shall be provided and installed in extruded tracks to allow adjustment from side to side for alternate hose capacities. The divider(s) shall have a textured black finish and shall have a radius corner with a slotted hand hold cut-out on the rear portion.

Two (2)
31-46-6015

HOSE STRAP(S)

Two (2) Fire Research JackStrap(s) shall be provided; designed to attach hose ends to the apparatus, to help prevent fire hose from inadvertently coming off the apparatus while responding to or returning from an incident.

The JackStrap shall be made of heavy duty 2-inch wide polypropylene webbing. An adjustable hose loop shall fit on supply and working hose from 1.5 to 5 inches. A separate shoulder loop shall help the

W.S. Darley & Co.

firefighter when pulling a supply line or help support a working hand line. When used on a hydrant line, the shoulder loop shall be capable of firmly holding hose to the hydrant during a hose stretch. There shall be a side pocket on the shoulder loop to hold a hydrant tool.

One (1)
31-46-0500

HOSE BED COVER (Dealer/Buyer-End User)

The apparatus Dealer and/or the apparatus Buyer-End User shall be responsible for providing a hose bed cover or tarp, or other means; to hold items in the hose bed, as recommended by NFPA, prior to the apparatus being put into service.

There are no requirements in these specifications, for the apparatus manufacturer to provide these items.

One (1)
31-50-0100

FASTENERS

All fasteners used to mount or secure components to the body shall be of stainless steel construction. Items fastened directly into the copolymer shall use sheet metal screws, stainless steel T-nuts or threaded brass inserts, depending on application. Upon request by the department, the manufacturer shall be required to provide a sample of the fasteners to be used in the body construction.

One (1)
31-51-0575

TREADPLATE AND TRIM

All treadplate shall be bright aluminum. Any horizontal surfaces with aluminum treadplate shall be overlaid with embossed 1/8" bright aluminum treadplate. The aluminum treadplate shall meet recommended requirements for non-slip surfaces.

One (1)
31-70-1100

RUB RAILS

Rub rails shall be installed using solid black rubber material designed to help protect the lower body and cushion against accidental contact. Each shall be mounted below the lower side compartments. Each end shall have a hard black rubber end cap.

There shall be bright polished scuff strips mounted between the body surface and the rub rails.

One (1)
31-80-0300

FRONT FOLDING STEPS LEFT - LIGHTED

Three (3) large, heavy duty lighted folding steps shall be furnished and located at the front body face of the left side compartments. There shall be a barrier material installed between the body surface and the steps.

One (1)
31-80-2300

FRONT FOLDING STEPS RIGHT - LIGHTED

Three (3) large, heavy duty lighted folding steps shall be furnished and located at the front body face of the right side compartments. There shall be a barrier material installed between the body surface and the steps.

One (1)

W.S. Darley & Co.

31-80-4300

REAR FOLDING STEPS - LIGHTED

Four (4) large, heavy duty chrome, lighted folding steps shall be furnished and located, two each side, at the apparatus rear. There shall be a barrier material installed between the body surface and the steps.

One (1)
31-92-1000

REAR VERTICAL HANDRAILS

Two (2) vertically mounted handrails, approximately 30" long, shall be provided, one each side at the apparatus rear. Each shall be 1-1/4" extruded aluminum tubing with rubber grip inserts, mounted in chrome stanchions. There shall be a barrier material installed between the body surface and the handrails.

One (1)
31-92-4200

HORIZONTAL REAR CROSS RAIL

One (1) horizontal rear cross rail shall be provided at the upper rear portion of the rear body panel. The rail shall be the approximate width of the rear body, between the width of any side compartments. It shall be 1.25" extruded aluminum tubing with rubber grip inserts, mounted in chrome stanchions. There shall be a barrier material installed between the body surface and the handrail.

One (1)
20-03-5100

300 GALLON TANK - COPOLYMER

A 300 gallon water (booster) tank shall be provided. The booster tank shall be constructed of a copolymer material, properly baffled.

The tank shall be provided with at least one (1) full length swash partition (baffle) and a sufficient number of widthwise baffles so that the maximum dimension of any spaces in the tank, either transverse or longitudinal, shall not exceed 46", and not less than 23".

Baffles shall have openings at both the top and bottom to permit movement of air and water between spaces to allow maximum flow requirements. Baffles shall form an integral part of the tank, and design shall be to provide and maintain safe road stability regardless of water level.

Tank shall have an overflow designed to prevent damage to the tank under high flow conditions and enclosed in front tank filler. The overflow is to be designed and located to prevent water loss on fast stops or starts, and is also to be located not to affect traction on the rear tires.

Tank outlet connection shall be designed with a 12" anti-swirl baffle plate above tank outlet to prevent air from mixing with the water when pumping from the tank.

A fill tower shall be installed in the tank top. It shall be of adequate size, minimum 10" X 10", to accommodate overflow and vents, to have a hinged cover and screen installed.

The tank shall be mounted to the chassis frame, per manufacturer's requirements.

One (1)
20-30-9050

TANK DRAIN VALVE

W.S. Darley & Co.

A manual, 1/4 turn, corrosion resistant, 3/4" bronze drain valve with a stainless steel ball shall be installed on the bottom of the tank clean out sump. It shall act as a tank drain and can also be used to flush any sand or sediment from the sump of the water tank quickly and easily.

One (1)
20-30-9501

TANK OVERFLOW

The fill tower shall have a 3" overflow that shall discharge beneath the tank, at or behind the rear wheels.

One (1)
21-10-2000

FOAM TANK

One (1) 25 gallon foam tank shall be provided, integral with the water tank and shall have a rectangular fill tower, approximately 10" x 10", with a hinged cover and a removable screen. A tank drain shall be provided inside the pump compartment.

One (1)
12-15-6010

2.5" LEFT REAR AUTO TANK FILL

One (1) 2.5" electronic tank fill shall be provided at the left rear of the apparatus. It shall have a chrome female swivel with strainer, plug and chain, and NST threads.

A quarter turn 3/4" drain bleeder valve shall be supplied and installed with the control knob approximately 6" below the inlet swivel. A drain hose shall be extended through the compartment floor to remove the water from the piping outboard of the electric 2.5" AutoFill valve.

The left rear direct tank fill shall include an automatic direct water tank fill system.

The system shall operate refilling operations independently, without monitoring by the engineer. Refill operation shall not require apparatus or fire pump to be running. The system shall be capable of handling pressurized sources up to 300 psi. The system gets an electronic signal from the water level gauge.

The water level gauge supplies a programmed signal to stop filling when the tank level is at 85% full, and resume filling when the tank level reaches 50%. Valve system shall be able to be manually overridden in case of electric failure.

The controller shall have three toggle positions, with command signals to the fill valve:

- 1) Auto - Fully automates the water fill process, opens and closes the valve from signals sent by the water level gauge
- 2) Off - Closes the valve
- 3) Open - Opens the valve

The system shall enable the operator to perform the following control / operation functions and status indicators for the refill operation:

- 1) Provide toggle positions for Auto/Off/Open for control of electric refill valve
- 2) Solid green light advises the valve is open
- 3) Solid red light advises the valve is closed

One (1)

W.S. Darley & Co.

12-17-7800

DIRECT FILL CONTROL

The direct fill control shall be on the pump operator's panel.

One (1)
31-12-0380

SUBFRAME HOT DIPPED GALVANIZED

The body shall be attached to and supported by a heavy duty, spring loaded, steel subframe bolted to the truck frame. The subframe shall be spring mounted to the chassis frame to allow for independent flexing of the body in relation to the chassis frame. The subframe shall be constructed from structural steel angle and C-channels. No welding shall be allowed to the truck frame. Isolator strips shall be installed at all contact points between body and subframe.

The subframe shall be carbon steel, sandblasted, then be treated with a hot dipped galvanizing process to offer the best protection against corrosion.

Due to the importance of the subframe flexibility and corrosion resistance, there shall be no exception to these requirements.

One (1)
31-31-1000

FENDERETTES

Bright anodized aluminum fenderettes shall be bolted to the wheel well openings.

One (1)
31-61-2100

REAR TAILBOARD

The rear tailboard shall be bolted to a heavy-duty, hot dipped galvanized, steel support assembly attached to the chassis frame. The rear tailboard shall be approximately 13" deep x 47" wide and constructed of embossed fire apparatus quality bright aluminum treadplate with an extruded aluminum grip type insert. The insert and aluminum treadplate shall meet recommended requirements for non-slip surfaces.

The rear tailboard shall be bolted to the support assembly with a drain gap provided at the rear and each side of the tailboard.

One (1)
33-01-1140

COPOLYMER COMPARTMENTS

LEFT SIDE

- 1.) One (1) compartment ahead of the left side rear wheels, approximately 15" wide x 55" high x 21" deep. The framed door opening shall be approximately 15" wide x 53" high.
- 2.) One (1) compartment over the left side rear wheels, approximately 40" wide x 38" high x 21" deep. The framed door opening shall be approximately 40" wide x 36" high.
- 3.) One (1) compartment behind the left side rear wheels, approximately 33.75" wide x 55" high x 21" deep. The framed door opening shall be approximately 33.75" wide x 53" high.

W.S. Darley & Co.

RIGHT SIDE

4.) One (1) compartment ahead of the right side rear wheels, approximately 15" wide x 55" high x 21" deep. The framed door opening shall be approximately 15" wide x 53" high.

5.) One (1) compartment over the right side rear wheels, approximately 40" wide x 38" high x 21" deep. The framed door opening shall be approximately 40" wide x 36" high.

6.) One (1) compartment behind the right side rear wheels, approximately 33.75" wide x 55" high x 21" deep. The framed door opening shall be approximately 33.75" wide x 53" high.

One (1)
33-07-0140

REAR COMPARTMENT

7.) One (1) compartment at the back of the apparatus, with interior dimensions of approximately 48" wide x 30" high x 25" deep. The framed door opening shall be approximately 42" wide x 21" high.

The compartment shall have a roll up door.

One (1)
35-17-0202

REAR ROLL UP DOOR FINISH

The rear roll up door shall be in a natural, anodized aluminum satin finish.

One (1)
35-02-1070

ROLL UP DOORS

The side compartment door openings shall be fitted with roll-up style doors.

One (1)
35-90-1175

ROLL UP DOOR CONSTRUCTION

There shall be aluminum roll-up shutter doors installed. Each shutter slat, track, bottom rail, and drip rail shall be constructed from anodized aluminum. Shutter slats shall feature an interlocking end shoe to prevent side to side binding of the shutter door during operation. Slat must have interlocking joints with an inverted locking flange. Slat inner seal design shall be such to prevent metal to metal contact while minimizing dirt and water from entering the compartment.

Shutter door track shall be one piece design with integral overlapping flange to provide a clean finished look without the need of caulk.

A magnetic door ajar switch shall be provided and installed within the shutter door strike block. Strike block shall be mounted to the door track outside of the compartment. Door switch shall be controlled by a magnetic end cap installed into the shutter lift bar.

The shutter door assembly shall be manufactured and assembled in the United States.

One (1)
35-17-0102

SIDE ROLL UP DOOR FINISH

W.S. Darley & Co.

The side roll up doors shall be in a natural anodized aluminum satin finish.

One (1)
37-02-1000

ENCLOSED LADDER STORAGE - SLIDE IN - RIGHT

A slide in ladder storage compartment shall be provided at the right side of the apparatus above the body compartments. It shall be located at the same height as the hose bed. Access shall be from the rear of the apparatus. Appropriate stops shall be provided, if needed, at the front of the ladders.

A horizontally hinged aluminum door with a push button style latch shall be provided to enclose the ladders at the rear. A switch shall be provided to activate compartment door ajar circuit.

One (1)
37-10-2290

The ladder storage shall have capacity for one (1) aluminum 20 ft. three section extension ladder (measuring 100" collapsed), and one (1) aluminum 8 foot roof ladder.

One (1)
37-10-2590

There shall be a single pike pole storage tube included.

One (1)
37-21-1900

SUCTION STORAGE - LEFT

A slide in, suction hose storage compartment shall be provided at the left side of the apparatus above the body compartments. It shall be located at the same height as the hose bed. Access shall be from the rear of the apparatus. Appropriate stops shall be provided at the front of the compartment, if needed depending upon hose length selected, to keep the hoses from sliding in beyond reach.

A horizontally hinged aluminum door with a push button style latch shall be provided to enclose and secure the two (2) suction hoses at the back of the truck. A switch shall be provided to activate compartment door ajar circuit.

A stainless steel scuff plate shall be provided at the bottom edge of door opening.

One (1)
37-21-1924

SUCTION HOSE STORAGE - LEFT SIDE OF HOSE BED

A suction hose storage compartment shall be provided in the left side of the apparatus hose bed, to store one (1) approximately 6 foot long hard suction hose. It shall be fabricated of unpainted smooth aluminum and measure roughly 11" wide x 9" high and allow for the fit of a long handled 6" hard suction hose.

Access shall be from the rear of the apparatus. Appropriate stops shall be provided at the front, if required, for the hose.

One (1)
37-22-1000

LONG TOOL STORAGE COMPARTMENTS

There shall be two (2) slide in, long tool storage compartments, one each side. They shall be accessed from the rear of the truck and include a hinged door with securing latch. They shall measure about 9" wide x 7" high and help to utilize the otherwise unused space in the upper side compartments up behind the roll of the roll-up doors. These compartments can accommodate pike poles or similar long handled tools up to 8 feet in length. The right side compartment shall include storage for up to an 8' folding attic

W.S. Darley & Co.

ladder and a pair of tubes designed for pike poles. Note: The attic ladder will protrude out the front of the body and a few inches into the dunnage compartment area.

Seven (7)
38-00-0200

SHELVING TRACKS

Unistrut type tracks shall be provided in seven (7) body compartment(s). The tracks shall be mounted vertically from floor to ceiling. A minimum of four (4) tracks shall be provided for each compartment specified.

All 7 compartments shall have unistrut track installed.

One (1)
38-00-0300

HORIZONTAL TRACKS

Unistrut type tracks shall be provided in one (1) body compartment(s). The tracks shall be mounted horizontally on the back wall of the specified compartment(s). The tracks shall be used to mount components such as air bottle brackets. The tracks shall allow side to side adjustment of mounted components. A minimum of two (2) tracks shall be provided for each compartment specified.

The following compartments shall have unistrut track installed:

---One (1) set in the left side body compartment #2 over the rear wheel well.

Two (2)
38-01-0100

ADJUSTABLE SHELVES (NONE)

There are no adjustable shelves specified at this time. Shelving and other compartment storage solutions are optional and priced specifically for each compartment. Please evaluate your equipment list and request shelving, pull out trays, and tool-boards based on your specific fire department equipment storage needs.

One (1)
40-00-0000

PAINT, STRIPING, AND LETTERING SECTION

One (1)
40-10-1950

PAINT FINISH

The apparatus shall be painted with DuPont/Axalta system paint. The compartment doors, if painted, shall be painted separately to ensure proper paint coverage on the body edges. The apparatus shall be prepared and painted using the following procedures.

All surfaces to be painted shall be properly prepared and cleaned. Painting, including primers and final coatings to be applied per the paint manufacturer's recommendations and instructions.

The compartment interiors shall be unpainted and in their natural white finish.

A pint of touch up paint shall be provided for each color used.

W.S. Darley & Co.

One (1)
40-12-0950

PAINT COLOR

The apparatus body paint shall be "cross referenced" from the chassis paint, and shall be painted to match the main chassis color as close as possible.

One (1)
40-13-4000

WHEEL RIMS

The chassis wheels shall be as furnished by the chassis OEM. No additional finishes shall be provided by the apparatus manufacturer.

One (1)
40-20-0100

LETTERING

The lettering for the apparatus shall be supplied and installed by the Purchaser/End User following payment and delivery of the apparatus.

One (1)
40-25-0200

REFLECTIVE STRIPE

Reflective striping shall be applied to the side of the vehicle chassis and body on at least 50% of the overall length of the vehicle. At least 50% of the rear and 25% of the front of the vehicle width shall have reflective striping applied. Striping shall be 3M Scotchlite with ControlTac adhesive brand reflective striping (or equal).

One (1)
40-25-1000

The stripe shall be a **4"** wide reflective stripe

One (1)
40-25-2000

The reflective stripe color shall be **WHITE**.

One (1)
40-25-4123

The reflective stripe shall be applied in a straight line along each lower side of the chassis and onto the front compartment. An angled design going upward towards the second compartment shall then be achieved with the stripe then continuing back horizontally along the second body compartment door on each side and then continuing straight to the rear corners of the truck.

One (1)
40-26-4100

CAB DOOR REFLECTIVE MATERIAL

There shall be a reflective material installed on the lower interior portion of each cab door.

One (1)
40-26-4150

CAB DOOR REFLECTIVE MATERIAL

The reflective material shall be installed on the interior portion of the driver and officer cab doors, and each of the two crew doors.

One (1)
40-26-4300

W.S. Darley & Co.

One (1)
40-27-8100

The color of the reflective material shall be **WHITE**.

REAR CHEVRON STRIPING

There shall be alternating reflective striping provided at the apparatus rear, in a chevron stripe pattern. At least 50% of the apparatus rear shall have retroreflective chevron striping.

The chevron pattern shall slant downward on both sides of the vehicle at an angle of 45 degrees, pointing in the direction of the bottom rear corners of the apparatus. The pattern shall resemble an inverted "V", with the point of the chevron pattern at the top center of the apparatus.

One (1)
40-27-8212

CHEVRON STRIPE WIDTH (6")

The chevron stripes shall each be 6" wide.

One (1)
40-27-8310

CHEVRON COLORS

The chevron pattern shall be alternating RED and LEMON YELLOW stripes.

One (1)
50-00-0000

12 VOLT ELECTRICAL SECTION

One (1)
50-00-0720

12 VOLT ELECTRICAL SYSTEM (Multiplexing)

MULTIPLEXING

A multiplexed wiring system shall be installed, controlling all electrical functions installed by the apparatus manufacturer. The system shall be driven by "nodes" in key locations around the vehicle.

ELECTRICAL LOAD MANAGEMENT

Electrical Load management shall also be part of this multiplex system, allowing diminished and load shedding capabilities of particular functions.

GENERAL WIRING

Apparatus body wiring shall be high temperature compatible wire, insulated with chemically cross-linked polyethylene and to withstand prolonged temperatures of up to 350 degrees Fahrenheit. The wiring shall be resistant to grease, oil, fluids, and abrasion and shall meet or exceed S.A.E. Certification J1128. It shall be stranded copper alloy conductors of a gauge rated to carry 125% of the maximum current for which the circuit is protected. Wiring not within the multiplexed system shall be individually color coded and function labeled every three (3) inches on the insulation.

W.S. Darley & Co.

All required testing shall be performed before the apparatus is delivered. All required test documents shall be supplied at the time of apparatus delivery.

All wiring for the apparatus shall be installed in accordance with quality electrical standards, protected in loom or conduit. Grommets shall be installed where wire passes through body panels, where applicable.

WIRING DIAGRAMS

Electrical wiring diagrams of the specific apparatus shall be furnished with the completed apparatus.

One (1)
50-00-2300

12 VOLT SWITCHES (CENTER CONSOLE)

There shall be a rocker switch panel provided in the cab console between the driver and officer seats.

This switch panel shall control warning lights and 12 volt accessories. The switches shall be rocker style switches. Each switch shall have a pilot light indicating the "on" position. There shall be a main master rocker switch to cut power to all warning light rocker switches. The master switch shall be red in color with a red pilot light. Each switch shall be labeled as to its function.

One (1)
50-01-0200

RUNNING LIGHTS & REFLECTORS

There shall be LED running lights and reflectors mounted on the body. The lights shall be recess mounted in rub rails or the body. They shall be at any running boards, body sides, and rear tail board. The lights and reflectors shall meet USA Federal Motor Vehicle Safety Standard #108.

One (1)
50-01-0800

LICENSE PLATE HOLDER & LED LIGHT

A license plate holder with LED light shall be provided on the rear of the apparatus body. The light shall be wired to illuminate with the parking/headlights.

One (1)
50-02-2123

REAR DIRECTIONALS (M6 LED)

Rear directional lighting shall be supplied as follows:

Two (2) 6" x 4" LED brake and tail lights, one each side - Red.
Two (2) 6" x 4" LED turn signals with arrow, one each side - Amber.
Two (2) 6" x 4" LED back up lights, one each side - Clear.

One (1)
50-02-5223

HOUSINGS FOR DIRECTIONALS

The M6 signal lights shall each be housed in a bezel designed to hold four (4) lights each. The fourth light location shall be utilized for lower rear warning lights.

One (1)
50-03-0200

REAR STEP LIGHTS (LED)

W.S. Darley & Co.

Two (2) clear LED step lights shall be furnished and shall be located, one each side at the apparatus, rear to illuminate respective stepping surfaces. Lighted folding steps also satisfy this requirement.

The lights shall be activated with a switch located in the cab.

One (1)
50-03-0800

FRONT BODY STEP LIGHTS (LED)

Two (2) clear LED step lights shall be furnished and located, one each side, at the front face of the apparatus body to illuminate the respective stepping surfaces. Lighted folding steps, if provided, also satisfy this requirement.

The lights shall be activated with a switch located in the cab.

One (1)
50-05-4050

COMPARTMENT LIGHTING (LED)

Each body compartment shall contain one (1) LED clear vertical strip light assembly. The compartments over the body wheel and the rear compartment shall have two strip lights, one on each side of the door.

Each LED light strip provided shall be full height of the compartment. Strip lighting provides uniform light dispersion throughout the compartment even when shelves are installed. The compartment strip lighting shall be automatically activated whenever a compartment door is opened.

One (1)
50-05-5100

Each roll up door shall have an integral "door open" indicator magnet in the lift bar. If the bar is not properly closed, it shall activate the "Door Open" light in the cab.

One (1)
50-05-5550

"DO NOT MOVE APPARATUS" LIGHT (LED)

A flashing red LED light, properly labeled with the words "Warning - Do Not Move Apparatus When Light Is On", shall be located in the cab. The light shall be activated automatically when any cab or body compartment door is opened, as long as the chassis parking brake is not applied.

In addition, accessories such as a telescoping light(s) shall also be connected to this ajar circuit, to activate the light when any of these items are not properly nested, and the vehicle parking brake is not set.

One (1)
50-07-0400

FOUR DOOR CAB GROUND LIGHTING (LED)

The four (4) door cab shall have a clear LED ground light below each stepping area of each entry door to illuminate the ground at the step area. The lights shall be wired to activate when the apparatus parking brake is set.

One (1)
50-07-1000

UNDER BODY GROUND LIGHTS (LED)

W.S. Darley & Co.

Four (4) clear LED ground lights shall be provided. Each shall have a clear lens and shall be mounted on brackets, angled outward, beneath the apparatus. The lights shall be wired to activate when the apparatus parking brake is set.

The lights shall be mounted as follows:

- Two (2) at the pump module running boards, one each side.
- Two (2) at the rear tailboard, one each side.

One (1)
51-00-1100

WARNING LIGHT SYSTEM

The following warning lights shall be installed in zones and properly switched.

One (1)
54-12-1350

LIGHT BAR

Zone A - (Upper Front) - One (1) 60" lightbar model #F4N0VLED shall be provided and installed. The lightbar shall incorporate an anodized extruded heavy duty aluminum base and cover chassis with two front and rear red corner modules, two interior white modules, and two interior red modules.

The front and rear of each corner module shall consist of 12 red Linear Super-LEDs installed on a conformal coated PCB board with a thermal pad/aluminum bracket heat sink assembly. The long red interior Linear Super-LED lights shall incorporate 12 red Super-LED installed on a conformal coated PCB board with a thermal pad/aluminum bracket heat sink assembly.

The long white interior Linear Super-LED lights shall incorporate 12 white Super-LEDs installed on a conformal coated PCB board with a thermal pad/aluminum bracket heat sink assembly.

All lighthoods shall be installed in the F4N0VLED with the aid of black polycarbonate snap-in mounting brackets. The solid state lightbar shall be vibration resistant. All electronic components are covered by a five year factory warranty. The lightbar shall include a permanent mount kit with hardware.

One (1)
54-20-1000

Light bar shall be mounted on the centered forward section of the cab roof.

One (1)
54-21-1200

The light colors shall be as follows:

Driver's Side of Lightbar

- Two red LED corners (front & rear)
- One clear LED front – will also be switched as FRONT SCENE LIGHTING
- One red LED front

Passenger Side of Lightbar

- Two red LED corners (front & rear)
- One clear LED front – will also be switched as FRONT SCENE LIGHTING
- One red LED front

One (1)
54-30-4085

W.S. Darley & Co.

Zone A (Lower Front) - Two (2) TLIR series, or equal, LED warning lights shall be mounted, one each side, on the front face of the chassis cab, cab grille, or grille guard.

The standard and preferred location is recessed into the upper rib of the chassis grille, see drawing or shop notes for further detail.

One (1)
54-32-1000

The light color shall be as follows:

Driver's Side - **Red**, Officer's Side - **Red**

One (1)
54-40-3120

Zone B (Right Side) - Four (4) LED warning lights, shall be mounted on the right side of the vehicle. One at the lower front fender area, one towards the rear in the wheelwell and two on the upper sides of the apparatus body.

Zone D (Left Side) - Four (4) LED warning lights, shall be mounted on the left side of the vehicle. One at the lower front fender area, one towards the rear in the wheelwell and two on the upper sides of the apparatus body.

One (1)
54-42-1000

The light colors shall be as follows:

Driver's Side - **Red**
Officer's Side - **Red**

One (1)
54-60-0552

Zone C (Rear-Upper) - Two (2) M6 LED warning lights shall be provided and installed one each side on the upper back body sides.

One (1)
54-62-1100

The light colors shall be as follows:

Driver's Side - **Red**
Officer's Side - **Red**

One (1)
54-70-0425

Zone C (Rear-Lower) - Two (2) 6x4s LED warning lights shall be mounted, one each side, at the lower rear of the apparatus.

One (1)
54-72-1000

The light colors shall be as follows:

Driver's Side - **Red**.
Officer's Side - **Red**.

One (1)
57-30-3420

TRAFFIC ADVISOR (LED)

A Traffic Advisor model #TAM65 shall be provided. The traffic advisor shall incorporate a rectangular extruded black powder coated aluminum chassis with six amber TIR6™ Super-LED® lights with waterproof connectors. The TIR6 lights shall be installed in a clear optic hard coated polycarbonate lens. The TIR6 lights shall incorporate six amber Super-LEDs, a clear horizontal optic hard coated

W.S. Darley & Co.

polycarbonate lens, and utilize a TIR reflector for maximum output. The hard coated lens housing shall provide extended life/luster protection against UV and chemical stresses. The TIR6 lens/reflector assembly and conformal coated PC board shall provide additional protection against environmental elements. The TIR6 lights are installed with waterproof connectors. The solid state traffic advisor shall be vibration resistant.

The TAM65 shall include a model TACTL5 control head that includes remote flash control. The TACTL5 shall have four programmable directional sequence flash patterns of left, right, split, and flash. The LED display on the control head shall replicate the TAM65 directional sequence. The traffic advisor control head shall have a rear panel dip switch for the ability to set eight additional Scan-Lock™ flash patterns. The TACTL5 shall contain a 10 amp external fuse for reverse polarity protection. The TACTL5 shall include a bail strap mounting kit. The TAM65 will contain a 15' 9/C 14/18 AWG interconnecting cable with quick disconnect feature.

Voltage: +12v

Size: H=2.84", W=36.01", D=2.24"

Amp Draw: 630 mA Peak, 315 mA Average per Light head

Lens Color: Amber

One (1)
57-32-1000

RECESSED MOUNTING

The rear directional light bar shall be recessed into the rear Poly body panel of the apparatus, centered at the upper rear portion. The recessed pocket in the body shall be trimmed with a decorative stainless steel enclosure around the arrowstick.

One (1)
58-00-0610

SIREN AMPLIFIER

One (1) Siren Amplifier model #295SLSA1 shall be provided. The siren amplifier shall incorporate a 12V/200W siren installed on an aluminum alloy chassis covered by a black polycarbonate powder coated housing for maximum protection. The 295SLSA1 shall have the ability for either 100 or 200 watt output. The front overlay shall be made of velvet Lexan™ with a matte finish. The lettering and artwork on the overlay shall be illuminated with adjustable backlighting of soft LED non-glaring green. The operating controls will consist of a power switch, manual button, PA volume switch, horn button, and rotary switch. The 295SLSA1 PC board shall have input polarity protection, output short circuit protection. The siren amplifier shall include a 20A/32V fuse. The solid state siren speaker amplifier shall be vibration resistant. The microphone shall be hardwired to the 295SLSA1.

One (1)
58-09-1400

The electronic siren control shall be recessed in center console between driver and officer seats.

One (1)
58-10-1600

SIREN SPEAKER

One (1) siren speaker, with a 100 watt driver shall be provided and installed at the front bumper.

One (1)
58-10-9423

The siren speaker(s) shall be mounted behind the front bumper in a protected location that optimizes the sound projection from the speaker.

One (1)
58-60-1010

W.S. Darley & Co.

BACK-UP CAMERA INSTALLATION

A rear view, "back-up camera", system shall be installed as part of the chassis supplied package. The system shall include one (1) camera mounted at the upper rear center of the body (when possible) and adjusted to provide a clear view of the back of the truck's tailboard and at least 30 feet behind the vehicle. One (1) LCD color display monitor shall be supplied in the chassis cab. The rear camera display shall activate when the vehicle's transmission is placed in reverse.

One (1)
59-00-0100

12V SCENE LIGHTING

There shall be 12 volt scene lighting installed on the apparatus as follows:

One (1)
59-00-5396

BODY SIDE SCENE LIGHTS (LED)

Four (4) M9 model EZ Scene LED lights featuring a unique clear lens shape and patented Linear-LED® reflector assembly for unmatched high-intensity illumination with low current consumption, shall be surface mounted on the upper sides of the body, two each side.

One (1)
59-00-5397

BODY REAR SCENE LIGHTS (LED)

Two (2) M9 model EZ Scene LED lights featuring a unique clear lens shape and patented Linear-LED® reflector assembly for unmatched high-intensity illumination with low current consumption, shall be surface mounted on the upper rear of the body, one each side.

FRONT SCENE LIGHTS (LED)

The white facing LED lights in the lightbar shall be switched as front scene lights from in the cab only.

One (1)
59-09-9320

LIGHT SWITCHING

The 12 volt scene lights on the sides and back shall be switched in cab and at the pump operator's panel. Three switches, at each location, labeled with an indicator light, shall control all the scene lights specified. One switch shall control all left side lights, one switch shall control all right side lights, and one switch shall control the rear scene lights.

W.S. Darley & Co.

One (1)
70-00-0050

EQUIPMENT SECTION

EQUIPMENT

The following equipment (if listed below) shall be supplied with the apparatus. It shall be shipped loose unless detailed below or otherwise in these specifications.

One (1)
70-00-0700

One (1) 8 ft. DS #585-A aluminum folding ladder, with slip resistant safety end shoes, shall be provided.

One (1)
70-00-7008

One (1) 8 ft. DS #775-A aluminum roof ladder, with folding roof hooks and prong feet, shall be provided.

One (1)
70-01-3200

One (1) 20 ft. DS #20-912 three-section aluminum extension ladder(s), with prong feet, shall be provided.

One (1)
71-06-6036

Three (3) sections of 6" clear Kochek or equal suction hose, with pyrolite, NST 6" rocker lug couplings shall be provided.

---Two (2) sections shall be 6" x 8 ft (in the enclosed suction hose compartment). One (1) section shall be mounted in the left side of the hosebed and be approximately 6 to 7 feet long.

One (1)
75-01-0400

One (1) pair of Zico AC-1 wheel chocks shall be provided, along with QCH-1 holders, mounted.

One (1)
99-99-1000

PURCHASER RESPONSIBILITY

It shall be the responsibility of the Purchaser to furnish any NFPA recommended items not detailed in these specifications.